

## TEST REPORT

Applicant/Manufacturer: Shenzhen Huafului Technology Co., Ltd.  
Address : Unit 1401 & 1402, 14/F, Jinqi Zhigu Mansion (No.4 Building of Chongwen Garden), Crossing of the Liuxian Street and Tangling Road, Taoyuan Street, Nanshan District, Shenzhen, P.R. China  
Report Number : SZ1230223-08060E-RF

### Test Standard (s)

EN 62479:2010; EN 50663:2017

### Sample Description

Product Type: SmartWatch  
Model No.: C21  
Multiple Model(s) No.: N/A  
Trade Mark: CUBOT  
Date Received: 2023/02/23  
Report Date: 2023/03/10

Test Result:	Pass*
--------------	-------

\* In the configuration tested, the EUT complied with the standards above.

### Prepared and Checked By:

### Approved By:



Michelle Zeng  
RF Engineer

Jacob Kong  
RF Supervisor

Note: BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '\*'. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

### Bay Area Compliance Laboratories Corp. (Shenzhen)

5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China  
Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

## **TABLE OF CONTENTS**

<b>DOCUMENT REVISION HISTORY .....</b>	<b>3</b>
<b>GENERAL INFORMATION.....</b>	<b>4</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....	4
OBJECTIVE .....	4
TEST FACILITY .....	4
RF EXPOSURE MEASUREMENT .....	5
<b>EN 62479:2010 §4.1 &amp; §4.2 - MAXIMUM EMITTED AVERAGE POWER.....</b>	<b>8</b>
TEST PROCEDURE .....	8
EVALUATED DATA.....	8
<b>EXHIBIT A - EUT PHOTOGRAPHS.....</b>	<b>9</b>

**DOCUMENT REVISION HISTORY**

Revision Number	Report Number	Description of Revision	Date of Revision
0	SZ1230223-08060E-RF	Original Report	2023-03-10

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

Frequency Range	Bluetooth: 2402-2480MHz BLE 1M/2M: 2402-2480MHz
Maximum EIRP	BT: 1.26dBm BLE: 6.22dBm
Antenna Specification*	0.5dBi(It is provided by the manufacturer)
Voltage Range	DC 3.8V from battery or DC 5V from USB charging port
Sample serial number	Bluetooth: 22V5_2 BLE :22FD_1 (Assigned by BACL, Shenzhen)
Sample/EUT Status	Good condition

### Objective

This test report is in accordance with EN 62479: 2010 Assessment of the compliance of low power electronic and electrical equipment with the basic restrictions related to human exposure to electromagnetic fields (10 MHz to 300 GHz); EN 50663:2017 Generic standard for assessment of low power electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (10 MHz - 300 GHz).

The objective is to determine the compliance of EUT with EN 62479: 2010, EN 50663:2017.

### Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

Each test item follows test standards and with no deviation.

## RF Exposure Measurement

### 1. Introduction

This generic standard applies to low power electronic and electrical apparatus for which no dedicated product – or product family standard regarding human exposure to electromagnetic fields applies.

The frequency range covered is 10 MHz to 300 GHz.

The object of this standard is to demonstrate the compliance of such apparatus with the basic restrictions on exposure of the general public to electric, magnetic and electromagnetic fields and contact current.

### 2. Compliance Criteria

#### 2.1 General considerations

Compliance of electromagnetic emissions from electronic and electrical equipment with the basic restrictions usually is determined by measurements and, in some cases, calculation of the exposure level. If the electrical power used by or radiated by the equipment is sufficiently low, the electromagnetic fields emitted will be incapable of producing exposures that exceed the basic restrictions. This standard provides simple EMF assessment procedures for this low power equipment.

Any relevant compliance assessment procedure which is consistent with the state of the art, reproducible and gives valid results can be used.

For transmitters intended for use with more than one antenna configuration option, the combination of transmitter and antenna(s) which generates the highest available antenna power and/or average total radiated power shall be assessed.

Four routes, which as described as follows, can be used to demonstrate compliance with this standard:

A Typical usage, installation and the physical characteristics of equipment make it inherently compliant with the applicable EMF exposure levels such as those listed in the bibliography. This low-power equipment includes unintentional (or non-intentional) radiators, for example incandescent light bulbs and audio/visual (A/V) equipment, information technology equipment (ITE) and multimedia equipment (MME) that does not contain radio transmitters. NOTE Equipment is described as A/V equipment, ITE or MME if its main use is playback/recording of music, voice or images, or processing of digital information.

B The input power level to electrical or electronic components that are capable of radiating electromagnetic energy in the relevant frequency range is so low that the available antenna power and/or the average total radiated power cannot exceed the low-power exclusion level defined in 2.2.

C The available antenna power and/or the average total radiated power are limited by product standards for transmitters to levels below the low-power exclusion level defined in 2.2.

D Measurements or calculations show that the available antenna power and/or the average total radiated power are below the low-power exclusion level defined in 2.2.

If none of these routes can be used, then the equipment is deemed to be out of the scope of this standard and EMF assessment for conformity assessment purposes shall be made according to other standards, such as IEC 62311 or other EMF product standards.

#### 2.2 Low-power exclusion level ( $P_{max}$ )

Low-power electronic and electrical equipment is deemed to comply with the provisions of this standard if it can be demonstrated using routes B, C or D that the available antenna power and/or the average total radiated power is less than or equal to the applicable low-power exclusion level  $P_{max}$ .

Annex A contains example values for  $P_{\max}$  derived from existing exposure limits listed in the bibliography, such as the ICNIRP guidelines [1], IEEE Std C95.1-1999 [2], and IEEE Std C95.1-2005 [3].

For wireless devices operated close to a person's body with available antenna powers and/or average total radiated powers higher than the  $P_{\max}$  values given in Annex A, the alternative  $P_{\max}$  values (called  $P_{\max}'$ ), described in Annex B can also be used.

For low power equipment using pulsed signals, other limits may apply in addition to those considered in Annex A and Annex B. Both ICNIRP guidelines [1] and IEEE standards [2], [3] have specific restrictions on exposures to pulsed fields, and the requirements of those standards with respect to exposure to pulses shall be met. Annex C discusses this topic further.

### 2.3 Exposure to multiple transmitting sources

If equipment under test (EUT) is equipped with multiple intentional radiators, the overall conformity assessment might require more than just the assessment of conformity of each one of the radiators separately. The effect of multiple intentional radiators should be considered in the conformity assessment process.

Technical Report IEC 62630 [8] provides generic guidance on how to assess the EMFs generated by multiple intentional radiators.

## 3. Limit

### 3.1 Annex A

**Table A.1 – Example values of SAR-based  $P_{\max}$  for some cases described by ICNIRP, IEEE Std C95.1-1999 and IEEE Std C95.1-2005**

Guideline / Standard	SAR limit, $SAR_{\max}$ W/kg	Averaging mass, $m$ g	$P_{\max}$ mW	Exposure tier <sup>a</sup>	Region of body <sup>a</sup>
ICNIRP [1]	2	10	20	General public	Head and trunk
	4	10	40	General public	Limbs
	10	10	100	Occupational	Head and trunk
	20	10	200	Occupational	Limbs
IEEE Std C95.1-1999 [2]	1,6	1	1,6	Uncontrolled environment	Head, trunk, arms, legs
	4	10	40	Uncontrolled environment	Hands, wrists, feet and ankles
	8	1	8	Controlled environment	Head, trunk, arms, legs
	20	10	200	Controlled environment	Hands, wrists, feet and ankles
IEEE Std C95.1-2005 [3]	2	10	20	Action level	Body except extremities and pinnae
	4	10	40	Action level	Extremities and pinnae
	10	10	100	Controlled environment	Body except extremities and pinnae
	20	10	200	Controlled environment	Extremities and pinnae

<sup>a</sup> Consult the appropriate standard for more information and definitions of terms.

## 3.2 Annex B

$$P_{\max}' = \exp \left[ A s + B s^2 + C \ln(BW) + D \right] \quad (\text{B.1})$$

For compliance with the SAR limit of  $SAR_{\max} = 2 \text{ W/kg}$  averaged over  $m = 10 \text{ g}$  in ICNIRP Guidelines [1] and IEEE Std C95.1-2005 [3], use Equations (B.2) to (B5) in Equation (B.1):

$$A = (-0,4588f^3 + 4,407f^2 - 6,112f + 2,497)/100 \quad (\text{B.2})$$

$$B = (0,1160f^3 - 1,402f^2 + 3,504f - 0,4367)/1000 \quad (\text{B.3})$$

$$C = (-0,1333f^3 + 11,89f^2 - 110,8f + 301,4)/1000 \quad (\text{B.4})$$

$$D = -0,03540f^3 + 0,5023f^2 - 2,297f + 6,104 \quad (\text{B.5})$$

**EN 62479:2010 §4.1 & §4.2 - MAXIMUM EMITTED AVERAGE POWER****Test Procedure**

Refer to EN 62479:2010 §4.1 & §4.2

**Evaluated Data**

For Worst case:

Mode	Maximum Tested EIRP <sup>(note 1)</sup> (dBm)	Maximum Tune Up EIRP * <sup>(note 2)</sup> (dBm)	Maximum Tune Up EIRP (mW)	Limit (mW)	Result
BT	1.26	1.5	1.41	20	Pass
BLE	6.13	6.5	4.47	20	Pass

Note 1: Data comes from RF test reports (SZ1230223-08060E-RF-22A, SZ1230223-08060E-RF-22B).

Note 2: Data provided by the applicant, which not higher than test data 2dB.

**Conclusion:**

The RF Exposure is compliance.



## **EXHIBIT A - EUT PHOTOGRAPHS**

---

Please refer to the report number is SZ1230223-08060E-EUT.

**\*\*\*\*\* END OF REPORT \*\*\*\*\***