
RF Test Report

Report No.: AGC00552190803EE03

PRODUCT DESIGNATION : Smart Phone
BRAND NAME : CUBOT
MODEL NAME : P30
APPLICANT : Shenzhen Huafurui Technology Co., Ltd.
DATE OF ISSUE : Sep. 04, 2019
STANDARD(S) : EN 301 511 V12.5.1: 2017-03
REPORT VERSION : V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd

CAUTION:

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Sep. 04, 2019	Valid	Initial release



TABLE OF CONTENTS

1. TEST REPORT CERTIFICATION.....	5
2. GENERAL INFORMATION	6
2.1. DESCRIPTION OF EUT.....	6
2.2. TYPE OF MOBILE STATION AND ADDITIONAL INFORMATION	7
3. IDENTIFICATION OF THE RESPONSIBLE TESTING LOCATION.....	8
4. MEASUREMENT UNCERTAINTY.....	10
5. TEST RESULT.....	11
5.1. APPLIED REFERENCE DOCUMENTS	11
5.2. TEST ENVIRONMENT/CONDITIONS	11
5.3. ITEMS USED IN THE TEST RESULTS LIST	11
5.4. TEST RESULTS LIST	13
Appendix A.Transmitter - Frequency error and phase error	21
Appendix B.Frequency error under multipath and interference conditions	23
Appendix C.Frequency error and phase error in GPRS multislot configuration	24
Appendix D.Transmitter output power and burst timing	26
Appendix E.Transmitter – Output RF spectrum	36
Appendix F.Transmitter output power in GPRS multislot configuration	46
Appendix G.Output RF spectrum in GPRS multislot configuration.....	56
Appendix H.Conducted spurious emissions - MS allocated a channel.....	66
Appendix I.Conducted spurious emissions- MS in idle mode	83
Appendix J.Receiver Blocking and spurious response – speech channel.....	91
Appendix K. Intermodulation rejection - speech channels	92
Appendix L.Frequency error and Modulation accuracy in EGPRS Configuration	93
Appendix M. Frequency error under multipath and interference conditions in EGPRS Configuration.....	94
Appendix N.EGPRS Transmitter output power	95
Appendix O.Output RF spectrum in EGPRS configuration	105
Appendix P. Blocking and spurious response in EGPRS configuration.....	115
Appendix Q. AM suppression - speech channels	116
Appendix R. Intermodulation rejection - EGPRS.....	117
Adjacent S. Adjacent channel rejection – EGPRS.....	118
Appendix T .Adjacent channel rejection - speech channels (TCH/FS).....	119
Appendix U. Reference sensitivity - TCH/FS	120
Appendix V. Reference sensitivity - FACCH/F.....	121
Appendix W. Minimum Input level for Reference Performance - GPRS.....	122

Appendix X. Minimum Input level for Reference Performance – EGPRS.....	123
Appendix Y. Radiated spurious emissions - MS in idle mode	124
APPENDIX Z. RADIATED SPURIOUS EMISSIONS TEST RESULT	125
APPENDIX A1: PHOTOGRAPHS OF TEST SETUP	129



1. TEST REPORT CERTIFICATION

Applicant	Shenzhen Huafurui Technology Co., Ltd.
Address	Unit 1401 &1402, 14/F, Jin qi zhi gu mansion (No. 4 building of Chong wen Garden), Crossing of the Liu xian street and Tang ling road, Tao yuan street, Nan shan district, Shenzhen,P.R. China
Manufacturer	Shenzhen Huafurui Technology Co., Ltd.
Address	Unit 1401 &1402, 14/F, Jin qi zhi gu mansion (No. 4 building of Chong wen Garden), Crossing of the Liu xian street and Tang ling road, Tao yuan street, Nan shan district, Shenzhen,P.R. China
Factory Name	Shenzhen Huafurui Technology Co., Ltd.
Address	Unit 1401 &1402, 14/F, Jin qi zhi gu mansion (No. 4 building of Chong wen Garden), Crossing of the Liu xian street and Tang ling road, Tao yuan street, Nan shan district, Shenzhen,P.R. China
Product Designation	Smart Phone
Brand Name	CUBOT
Test Model	P30
Date of test	Aug. 22, 2019~Sep. 04, 2019
Deviation	None
Condition of Test Sample	Normal
Report Template	AGCRT-EC-2.5G2/RF

We, Attestation of Global Compliance (Shenzhen) Co., Ltd., for compliance with the requirements set forth in the European Standard ETSI EN 301 511 V12.5.1. The results of testing in this report apply to the product/system which was tested only. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

The test results of this report relate only to the tested sample identified in this report.


Prepared By



Jeast Zhan
(Project Engineer)

Sep. 04, 2019


Reviewed By



Max Zhang
(Reviewer)

Sep. 04, 2019

Approved By



Forrest Lei
Authorized Officer

Sep. 04, 2019

2. GENERAL INFORMATION

2.1. DESCRIPTION OF EUT

2.1.1. FINAL EQUIPMENT BUILD STATUS

Details of technical specification refer to the description in follows:

Product Name	Smart Phone
Brand Name	CUBOT
Test Model	P30
Product Type	GSM
Hardware Version	Q935_MB_V1.0
Software Version	CUBOT_P30_9091C-V01_20190807
Frequency Bands	<input checked="" type="checkbox"/> GSM 900 <input checked="" type="checkbox"/> DCS 1800 (EU Frequency) <input checked="" type="checkbox"/> GSM 850 <input checked="" type="checkbox"/> PCS1900 (none EU Frequency)
Modulation Mode	GMSK, 8PSK
Antenna Type	PIFA Antenna
Antenna Gain	GSM900: 1.2dBi, DCS1800: 1.5dBi
Power Class	GSM900: 4, DCS1800: 1
GSM Release Version	N/A
GPRS Class	Class 12
SIM Card Description	There are dual-SIM cards for GSM, just one for GSM/WCDMA/LTE and the other only for GSM.

2.1.2. PHOTOGRAPHS OF THE EUT

Please see photographs of the EUT.

2.1.3. IDENTIFICATION OF SAMPLES EUT

The EUT Identity consists of numerical and letter characters (see the table below), the first five numerical characters indicates the Type of the EUT defined by AGC, the next letter character indicates the test sample, and the following two numerical characters indicates the software version of the test sample.

SAMPLE A01

Sample Reference Number	A01
Factory Name	Shenzhen Huafului Technology Co., Ltd.
Test Model	P30
Product Type	GSM
Frequency Bands	GSM 900: 880 -915 MHz (TX); 925 - 960 MHz (RX) DCS1800: 1710 -1785 MHz (TX); 1805-1880 MHz (RX)

2.2. TYPE OF MOBILE STATION AND ADDITIONAL INFORMATION

Table A.2: Type of Mobile Station (Re. ETSI EN 301 511 Annex A)

Item	Type of Mobile Station	Support	Mnemonic
1	HSCSD Multislot MS	NO	Type_HSCSD_Multislot
2	R-GSM MS	NO	Type_R-GSM
3	Support of GPRS Multislot class on the uplink	YES	Type_GPRS_Multislot_uplink
4	EGPRS	YES	Type_EGPRS
5	EGPRS capable of 8PSK in Uplink, of all Multislot classes	YES	Type_EGPRS_8PSK_uplink
6	ER-GSM MS	NO	Type-GSM
7	DLMC MS	NO	Type DLMC

Type A.3: Additional information (Re. ETSI EN 301 511 Annex A)

Item	Additional Information	Support	Mnemonic
1	Telephony	YES	TSPC_Serv_TS11
2	Permanent Antenna Connector	YES	TSPC_AddInfo_PermAntenna

Note: Telephony means make a phone call.



3. IDENTIFICATION OF THE RESPONSIBLE TESTING LOCATION

Test Site-1	Attestation of Global Compliance (Shenzhen) Co., Ltd
Location	1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao 'an District, Shenzhen, Guangdong, China

Note: Blocking and spurious response test within the scope of TAF approval.

LIST OF EQUIPMENTS USED OF AGC

No.	Type	Manufacturer	S/N	Cal. Date	Cal. Due
1	H & T Chamber ETH225-40A	Test EQ	WIT-05121302	Feb. 27, 2019	Feb. 26, 2020
2	CMU200	R&S	120237	Feb. 27, 2019	Feb. 26, 2020
3	Wireless communication test set 8960	Agilent	GB46200384	July 11, 2019	July 10, 2020
4	Power Splitter 11636A	Agilent	34	Sep.20, 2018	Sep.19, 2019
5	Attenuator	JFW	50FHC-006-50	June 12, 2019	June 11, 2020
6	Vector Signal Generator SMU200A	R&S	104332	Sep.20, 2018	Sep.19, 2019
7	VECTOR ANALYZER E4440A	Agilent	MY44303916	June 12, 2019	June 11, 2020
8	MXG Vector Signal Generator N5182A	AGILENT	MY50140530	Sep.20, 2018	Sep.19, 2019
9	PSG Analog Signal Generator E8257D	AGILENT	MY45141029	Sep.20, 2018	Sep.19, 2019
10	MXA Signal Analyzer N9020A	AGILENT	W1312-60196	Feb. 27, 2019	Feb. 28, 2020
11	Universal Switch Control Unit	JS TONSCEND	N/A	---	---
12	Programmable Power Supply PPT-1830	GW INSTEK	EM907629	Aug.18, 2018	Aug.17, 2019
12	Programmable Power Supply PPT-1830	GW INSTEK	EM907629	Aug.16, 2019	Aug.15, 2020
13	DC Power Source	N/A	GBD-60V30A	Feb. 27, 2019	Feb. 26, 2020
14	Attenuator	JFW	50FHC-006-50	June 12, 2019	June 11, 2020
15	EMI Test Receiver ESCI	R&S	100694	June 12, 2019	June 11, 2020
16	Double-Ridged Waveguide Horn Antenna 3117	ETS LINDGREN	00034609	Mar. 01, 2018	Feb. 28, 2020
17	Trilog Broadband Antenna VULB 9168	SCHWARZBECK	494	Mar. 01, 2018	Feb. 28, 2020
18	LOOP ANTENNA SAS-562B	A.H	/	Mar. 01, 2018	Feb. 28, 2020

No.	Type	Manufacturer	S/N	Cal. Date	Cal. Due
19	Artificial Mains Network ENV4200	R&S	101116	July 11, 2019	July 11, 2020
20	Artificial Mains Network ENV216	R&S	101242	July 11, 2019	July 11, 2020
21	Filter Bank Notch 1(880-915MHz)	MICRO-TRONIC S	010	Feb. 27, 2019	Feb. 26, 2020
22	Filter Bank Notch 2(1710-1785MHz)	MICRO-TRONIC S	009	Feb. 27, 2019	Feb. 26, 2020
23	Filter Bank Notch 3(1920-1980MHz)	MICRO-TRONIC S	008	Feb. 27, 2019	Feb. 26, 2020



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118

4. MEASUREMENT UNCERTAINTY

The uncertainty is calculated using the methods suggested in the “Guide to the Expression of Uncertainty in Measurement” (GUM) published by ISO.

- Uncertainty of Radio Frequency, $U_c = \pm 1 \times 10^{-5}$
- Uncertainty of total RF power, conducted, $U_c = \pm 1.5\text{dB}$
- Uncertainty of RF power density, conducted, $U_c = \pm 3\text{dB}$
- Uncertainty of spurious emissions, conducted, $U_c = \pm 3\text{dB}$
- Uncertainty of spurious emissions, radiated, $U_c = \pm 6\text{dB}$
- Uncertainty of Temperature: $\pm 1^\circ\text{C}$
- Uncertainty of Humidity: $\pm 5\%$
- Uncertainty of DC and low frequency voltages: $\pm 3\%$



5. TEST RESULT

5.1. APPLIED REFERENCE DOCUMENTS

Leading reference documents for testing:

No.	Identity	Document Title
1	ETSI EN 301 511	Global System for Mobile communications (GSM); Mobile Stations (MS) equipment; Harmonised Standard covering the essential requirements of article 3.2 of Directive 2014/53/EU

Specific reference documents for testing:

No.	Identity	Document Title
2	ETSI TS 151 010-1	3 rd Generation Partnership Project; Technical Specification Group GSM/EDGE Radio Access Network Digital cellular telecommunications system (Phase 2+); Mobile Station (MS) conformance specification; Part 1: Conformance specification

5.2. TEST ENVIRONMENT/CONDITIONS

Normal Temperature (NT)	15 ... 35 °C
Relative Humidity	30 ... 75 %
Air Pressure	980 ... 1020 kPa
Adapter Test Model Name	HJ-0502000W2-EU
Details of Power Supply (Rated Input)	AC100-240V, 50/60Hz, 0.3A
Details of Power Supply (Rated Output)	DC5.0V,2000mA
Extreme Temperature	Low Temperature (TL) = -10°C High Temperature (TH) = +40°C
Extreme Voltage of the EUT	Low Voltage = DC 3.27V Normal Voltage= DC 3.85V High Voltage = DC 4.40V

Note: The Limit Voltage 4.40V was declared by manufacturer, The EUT couldn't be operate normally with higher voltage.
The maximum temperature of 40 is not a standard requirement and is measured according to the maximum service temperature stated by the manufacturer.

5.3. ITEMS USED IN THE TEST RESULTS LIST

Terms in the column "Verdict" for the test results list of the section:

Verdict	Description
PASS	EUT passed this test case
FAIL	EUT failed this test case
INC.	EUT did not pass and did not fail this test case, therefore the verdict is inconclusive

Verdict	Description
N/A	Test case not applicable for the EUT, see the column "Note" for detailed



5.4. TEST RESULTS LIST

Table A.1: The EN Requirements Table (EN-RT) (Re. ETSI EN 301 511 Annex A) for SIM Card 1

Test Case (ETSI TS 151010-1)	Test Case (EN 301 511)	Parameter	GSM 900		GSM 1800		Note
			Sample	Result	Sample	Result	
12.1.1	4.2.12	Conducted spurious emissions - MS allocated a channel					
		NT / NV	A01	PASS	A01	PASS	
		NT / LV	A01	PASS	A01	PASS	
		NT / HV	A01	PASS	A01	PASS	
12.1.2	4.2.13	Conducted spurious emissions - MS in idle mode					
		NT / NV	A01	PASS	A01	PASS	
		NT / LV	A01	PASS	A01	PASS	
		NT / HV	A01	PASS	A01	PASS	
12.2.1	4.2.16	Radiated spurious emissions - MS allocated a channel					
		NT / NV	A01	PASS	A01	PASS	
		NT / LV	A01	PASS	A01	PASS	
		NT / HV	A01	PASS	A01	PASS	
12.2.2	4.2.17	Radiated spurious emissions - MS in idle mode					
		NT / NV	A01	PASS	A01	PASS	
		NT / LV	A01	PASS	A01	PASS	
		NT / HV	A01	PASS	A01	PASS	
13.1	4.2.1	Transmitter - Frequency error and phase error					
		NT / NV	A01	PASS	A01	PASS	
		LT / LV	A01	PASS	A01	PASS	
		LT / HV	A01	PASS	A01	PASS	
		HT / LV	A01	PASS	A01	PASS	
		HT / HV	A01	PASS	A01	PASS	
		Vibration X-axis	A01	PASS	A01	PASS	
		Vibration Y-axis	A01	PASS	A01	PASS	
Vibration Z-axis	A01	PASS	A01	PASS			
13.2	4.2.2	Transmitter - Frequency error under multipath and interference conditions					
		NT / NV	A01	PASS	A01	PASS	
		LT / LV	A01	PASS	A01	PASS	
		LT / HV	A01	PASS	A01	PASS	
		HT / LV	A01	PASS	A01	PASS	
		HT / HV	A01	PASS	A01	PASS	



13.3	4.2.5	Transmitter output power and burst timing				
		NT / NV	A01	PASS	A01	PASS
		LT / LV	A01	PASS	A01	PASS
		LT / HV	A01	PASS	A01	PASS
		HT / LV	A01	PASS	A01	PASS
		HT / HV	A01	PASS	A01	PASS
13.4	4.2.6	Transmitter - Output RF spectrum				
		NT / NV	A01	PASS	A01	PASS
		LT / LV	A01	PASS	A01	PASS
		LT / HV	A01	PASS	A01	PASS
		HT / LV	A01	PASS	A01	PASS
		HT / HV	A01	PASS	A01	PASS
13.16.1	4.2.4	Frequency error and phase error in GPRS multislot configuration				
		NT / NV	A01	PASS	A01	PASS
		LT / LV	A01	PASS	A01	PASS
		LT / HV	A01	PASS	A01	PASS
		HT / LV	A01	PASS	A01	PASS
		HT / HV	A01	PASS	A01	PASS
		Vibration X-axis	A01	PASS	A01	PASS
		Vibration Y-axis	A01	PASS	A01	PASS
13.16.2	4.2.10	Transmitter output power in GPRS multislot configuration				
		NT / NV	A01	PASS	A01	PASS
		LT / LV	A01	PASS	A01	PASS
		LT / HV	A01	PASS	A01	PASS
		HT / LV	A01	PASS	A01	PASS
		HT/HV	A01	PASS	A01	PASS
13.16.3	4.2.11	Output RF spectrum in GPRS multislot configuration				
		NT / NV	A01	PASS	A01	PASS
		LT / LV	A01	PASS	A01	PASS
		LT / HV	A01	PASS	A01	PASS
		HT / LV	A01	PASS	A01	PASS
		HT/HV	A01	PASS	A01	PASS
14.2.1	4.2.42	Reference sensitivity - TCH/FS				
		NT / NV	A01	PASS	A01	PASS



		NT / LV	A01	PASS	A01	PASS	
		NT / HV	A01	PASS	A01	PASS	
14.2.3	4.2.43	Reference sensitivity - FACCH/F					
		NT / NV	A01	PASS	A01	PASS	
14.16.1	4.2.44	Minimum Input level for Reference Performance - GPRS					
		NT / NV	A01	PASS	A01	PASS	
		NT / LV	A01	PASS	A01	PASS	
		NT / HV	A01	PASS	A01	PASS	
14.6.1	4.2.32	Intermodulation rejection-speech channels					
		NT / NV	A01	PASS	A01	PASS	
		NT / LV	A01	PASS	A01	PASS	
		NT / HV	A01	PASS	A01	PASS	
14.8.1	4.2.35	AM suppression-speech channels					
		NT / NV	A01	PASS	A01	PASS	
		NT / LV	A01	PASS	A01	PASS	
		NT / HV	A01	PASS	A01	PASS	
14.5.1	4.2.38	Adjacent channel rejection-speech channels (TCH/FS)					
		NT / NV	A01	PASS	A01	PASS	
		NT / LV	A01	PASS	A01	PASS	
		NT / HV	A01	PASS	A01	PASS	
14.7.1	4.2.20	Blocking and spurious response – speech channels					
		NT / NV	A01	PASS	A01	PASS	
		NT / LV	A01	PASS	A01	PASS	
		NT / HV	A01	PASS	A01	PASS	
14.18.3	4.2.40	Adjacent channel rejection - EGPRS					
		NT / NV	A01	PASS	A01	PASS	
		NT / LV	A01	PASS	A01	PASS	
		NT / HV	A01	PASS	A01	PASS	
14.18.4	4.2.34	Intermodulation rejection - EGPRS					
		NT / NV	A01	PASS	A01	PASS	
		NT / LV	A01	PASS	A01	PASS	
		NT / HV	A01	PASS	A01	PASS	
13.17.1	4.2.26	Frequency error and Modulation accuracy in EGPRS Configuration					
		NT / NV	A01	PASS	A01	PASS	
		NT / LV	A01	PASS	A01	PASS	

		NT / HV	A01	PASS	A01	PASS	
13.17.2	4.2.27	Frequency error under multipath and interference conditions in EGPRS Configuration					
		NT / NV	A01	PASS	A01	PASS	
		NT / LV	A01	PASS	A01	PASS	
		NT / HV	A01	PASS	A01	PASS	
13.17.3	4.2.28	EGPRS Transmitter output power					
		NT / NV	A01	PASS	A01	PASS	
		NT / LV	A01	PASS	A01	PASS	
		NT / HV	A01	PASS	A01	PASS	
13.17.4	4.2.29	Output RF spectrum in EGPRS configuration					
		NT / NV	A01	PASS	A01	PASS	
		NT / LV	A01	PASS	A01	PASS	
		NT / HV	A01	PASS	A01	PASS	
14.18.1	4.2.45	Minimum Input level for Reference Performance - EGPRS					
		NT / NV	A01	PASS	A01	PASS	
		NT / LV	A01	PASS	A01	PASS	
		NT / HV	A01	PASS	A01	PASS	
14.18.5	4.2.30	Blocking and spurious response in EGPRS configuration					
		NT / NV	A01	PASS	A01	PASS	
		NT / LV	A01	PASS	A01	PASS	
		NT / HV	A01	PASS	A01	PASS	



Table A.2: The EN Requirements Table (EN-RT) (Re. ETSI EN 301 511 Annex A) for SIM Card 2

Test Case (ETSI TS 151010-1)	Test Case (EN 301 511)	Parameter	GSM 900		GSM 1800		Note
			Sample	Result	Sample	Result	
12.1.1	4.2.12	Conducted spurious emissions - MS allocated a channel					
		NT / NV	A01	PASS	A01	PASS	
		NT / LV	A01	PASS	A01	PASS	
		NT / HV	A01	PASS	A01	PASS	
12.1.2	4.2.13	Conducted spurious emissions - MS in idle mode					
		NT / NV	A01	PASS	A01	PASS	
		NT / LV	A01	PASS	A01	PASS	
		NT / HV	A01	PASS	A01	PASS	
12.2.1	4.2.16	Radiated spurious emissions - MS allocated a channel					
		NT / NV	A01	PASS	A01	PASS	
		NT / LV	A01	PASS	A01	PASS	
		NT / HV	A01	PASS	A01	PASS	
12.2.2	4.2.17	Radiated spurious emissions - MS in idle mode					
		NT / NV	A01	PASS	A01	PASS	
		NT / LV	A01	PASS	A01	PASS	
		NT / HV	A01	PASS	A01	PASS	
13.1	4.2.1	Transmitter - Frequency error and phase error					
		NT / NV	A01	PASS	A01	PASS	
		LT / LV	A01	PASS	A01	PASS	
		LT / HV	A01	PASS	A01	PASS	
		HT / LV	A01	PASS	A01	PASS	
		HT / HV	A01	PASS	A01	PASS	
		Vibration X-axis	A01	PASS	A01	PASS	
		Vibration Y-axis	A01	PASS	A01	PASS	
		Vibration Z-axis	A01	PASS	A01	PASS	
13.2	4.2.2	Transmitter - Frequency error under multipath and interference conditions					
		NT / NV	A01	PASS	A01	PASS	
		LT / LV	A01	PASS	A01	PASS	
		LT / HV	A01	PASS	A01	PASS	
		HT / LV	A01	PASS	A01	PASS	
		HT / HV	A01	PASS	A01	PASS	
13.3	4.2.5	Transmitter output power and burst timing					

		NT / NV	A01	PASS	A01	PASS	
		LT / LV	A01	PASS	A01	PASS	
		LT / HV	A01	PASS	A01	PASS	
		HT / LV	A01	PASS	A01	PASS	
		HT / HV	A01	PASS	A01	PASS	
13.4	4.2.6	Transmitter - Output RF spectrum					
		NT / NV	A01	PASS	A01	PASS	
		LT / LV	A01	PASS	A01	PASS	
		LT / HV	A01	PASS	A01	PASS	
		HT / LV	A01	PASS	A01	PASS	
		HT / HV	A01	PASS	A01	PASS	
13.16.1	4.2.4	Frequency error and phase error in GPRS multislot configuration					
		NT / NV	A01	PASS	A01	PASS	
		LT / LV	A01	PASS	A01	PASS	
		LT / HV	A01	PASS	A01	PASS	
		HT / LV	A01	PASS	A01	PASS	
		HT / HV	A01	PASS	A01	PASS	
		Vibration X-axis	A01	PASS	A01	PASS	
		Vibration Y-axis	A01	PASS	A01	PASS	
		Vibration Z-axis	A01	PASS	A01	PASS	
13.16.2	4.2.10	Transmitter output power in GPRS multislot configuration					
		NT / NV	A01	PASS	A01	PASS	
		LT / LV	A01	PASS	A01	PASS	
		LT / HV	A01	PASS	A01	PASS	
		HT / LV	A01	PASS	A01	PASS	
		HT/HV	A01	PASS	A01	PASS	
13.16.3	4.2.11	Output RF spectrum in GPRS multislot configuration					
		NT / NV	A01	PASS	A01	PASS	
		LT / LV	A01	PASS	A01	PASS	
		LT / HV	A01	PASS	A01	PASS	
		HT / LV	A01	PASS	A01	PASS	
		HT/HV	A01	PASS	A01	PASS	
14.2.1	4.2.42	Reference sensitivity - TCH/FS					
		NT / NV	A01	PASS	A01	PASS	
		NT / LV	A01	PASS	A01	PASS	



		NT / HV	A01	PASS	A01	PASS	
14.2.3	4.2.43	Reference sensitivity - FACCH/F					
		NT / NV	A01	PASS	A01	PASS	
14.16.1	4.2.44	Minimum Input level for Reference Performance - GPRS					
		NT / NV	A01	PASS	A01	PASS	
		NT / LV	A01	PASS	A01	PASS	
		NT / HV	A01	PASS	A01	PASS	
14.6.1	4.2.32	Intermodulation rejection-speech channels					
		NT / NV	A01	PASS	A01	PASS	
		NT / LV	A01	PASS	A01	PASS	
		NT / HV	A01	PASS	A01	PASS	
14.8.1	4.2.35	AM suppression-speech channels					
		NT / NV	A01	PASS	A01	PASS	
		NT / LV	A01	PASS	A01	PASS	
		NT / HV	A01	PASS	A01	PASS	
14.5.1	4.2.38	Adjacent channel rejection-speech channels (TCH/FS)					
		NT / NV	A01	PASS	A01	PASS	
		NT / LV	A01	PASS	A01	PASS	
		NT / HV	A01	PASS	A01	PASS	
14.7.1	4.2.20	Blocking and spurious response – speech channels					
		NT / NV	A01	PASS	A01	PASS	
		NT / LV	A01	PASS	A01	PASS	
		NT / HV	A01	PASS	A01	PASS	
14.18.3	4.2.40	Adjacent channel rejection - EGPRS					
		NT / NV	A01	PASS	A01	PASS	
		NT / LV	A01	PASS	A01	PASS	
		NT / HV	A01	PASS	A01	PASS	
14.18.4	4.2.34	Intermodulation rejection - EGPRS					
		NT / NV	A01	PASS	A01	PASS	
		NT / LV	A01	PASS	A01	PASS	
		NT / HV	A01	PASS	A01	PASS	
		NT / HV	A01	PASS	A01	PASS	
13.17.1	4.2.26	Frequency error and Modulation accuracy in EGPRS Configuration					
		NT / NV	A01	PASS	A01	PASS	
		NT / LV	A01	PASS	A01	PASS	

		NT / HV	A01	PASS	A01	PASS	
13.17.2	4.2.27	Frequency error under multipath and interference conditions in EGPRS Configuration					
		NT / NV	A01	PASS	A01	PASS	
		NT / LV	A01	PASS	A01	PASS	
		NT / HV	A01	PASS	A01	PASS	
13.17.3	4.2.28	EGPRS Transmitter output power					
		NT / NV	A01	PASS	A01	PASS	
		NT / LV	A01	PASS	A01	PASS	
		NT / HV	A01	PASS	A01	PASS	
13.17.4	4.2.29	Output RF spectrum in EGPRS configuration					
		NT / NV	A01	PASS	A01	PASS	
		NT / LV	A01	PASS	A01	PASS	
		NT / HV	A01	PASS	A01	PASS	
14.18.1	4.2.45	Minimum Input level for Reference Performance - EGPRS					
		NT / NV	A01	PASS	A01	PASS	
		NT / LV	A01	PASS	A01	PASS	
		NT / HV	A01	PASS	A01	PASS	
14.18.5	4.2.30	Blocking and spurious response in EGPRS configuration					
		NT / NV	A01	PASS	A01	PASS	
		NT / LV	A01	PASS	A01	PASS	
		NT / HV	A01	PASS	A01	PASS	

Note: The worst test case is SIM Card 1.

Appendix A. Transmitter - Frequency error and phase error

Note: All test modes were carried out for all operation modes and record the worst test mode (GSM 900/1800 TN/VN) of fellow:

GSM900

RMS phase error(degree)	Power control LEVEL	Result			
		GSM900			
		ARFCN			
		LCH	MCH	HCH	Result
TN VN	5	0.5	0.6	0.5	PASS
	19	0.5	0.5	0.5	PASS
When the MS is being vibrated	5	0.5	0.6	0.4	PASS
	19	0.5	0.6	0.5	PASS

Peak phase error(degree)	Power control LEVEL	Result			
		GSM900			
		ARFCN			
		LCH	MCH	HCH	Result
TN VN	5	1.5	1.7	1.5	PASS
	19	1.5	1.6	1.5	PASS
When the MS is being vibrated	5	1.4	1.8	1.4	PASS
	19	1.7	1.8	1.5	PASS

frequency error(Hz)	Power control LEVEL	Result			
		GSM900			
		ARFCN			
		LCH	MCH	HCH	Result
TN VN	5	3	7	6	PASS
	19	4	5	3	PASS
When the MS is being vibrated	5	9	5	7	PASS
	19	6	3	2	PASS

DCS1800

RMS phase error(degree)	Power control LEVEL	Result			
		DCS1800			
		ARFCN			
		LCH	MCH	HCH	Result
TN VN	0	0.7	0.5	0.5	PASS
	15	0.6	0.5	0.5	PASS
When the MS is being vibrated	0	0.5	0.5	0.6	PASS
	15	0.6	0.5	0.5	PASS

Peak phase error(degree)	Power control LEVEL	Result			
		DCS1800			
		ARFCN			
		LCH	MCH	HCH	Result
TN VN	0	2.3	2.2	1.5	PASS
	15	1.8	1.8	1.6	PASS
When the MS is being vibrated	0	1.5	1.6	1.9	PASS
	15	1.9	2.6	1.7	PASS

frequency error(Hz)	Power control LEVEL	Result			
		DCS1800			
		ARFCN			
		LCH	MCH	HCH	Result
TN VN	0	9	11	12	PASS
	15	15	11	13	PASS
When the MS is being vibrated	0	11	13	12	PASS
	15	11	16	14	PASS

Appendix B.Frequency error under multipath and interference conditions

Note: All test modes were carried out for all operation modes and record the worst test mode (GSM 900/1800 TN/VN) of fellow:

GSM900

Fading set	Test conditions	Power control LEVEL	Result			
			GSM900			
			ARFCN			
			LCH	MCH	HCH	Result
RA250	TNVN	5	-2	3	6	PASS
		19	4	4	4	PASS
HT100	TNVN	5	1	9	3	PASS
		19	3	3	8	PASS
TU50	TNVN	5	3	4	2	PASS
		19	4	8	3	PASS
TU3	TNVN	5	4	4	4	PASS
		19	1	4	3	PASS

DCS1800

Fading set	Test conditions	Power control LEVEL	Result			
			DCS1800			
			ARFCN			
			LCH	MCH	HCH	Result
RA130	TNVN	0	14	14	15	PASS
		15	13	12	14	PASS
HT100	TNVN	0	9	10	14	PASS
		15	14	11	14	PASS
TU50	TNVN	0	11	12	13	PASS
		15	12	13	15	PASS
TU1.5	TNVN	0	13	11	7	PASS
		15	10	13	14	PASS

Appendix C.Frequency error and phase error in GPRS multislot configuration

Note: All test modes were carried out for all operation modes and record the worst test mode (GSM 900/1800 TN/VN) of fellow:

GSM900

RMS phase error(degree)	Power control LEVEL	Result			
		GSM900			
		ARFCN			
		LCH	MCH	HCH	Result
TN VN	5	0.5	0.7	0.5	PASS
	19	0.5	0.5	0.5	PASS
When the MS is being vibrated	5	0.5	0.5	0.6	PASS
	19	0.6	0.5	0.5	PASS

Peak phase error(degree)	Power control LEVEL	Result			
		GSM900			
		ARFCN			
		LCH	MCH	HCH	Result
TN VN	5	1.5	1.9	1.5	PASS
	19	1.7	1.6	1.5	PASS
When the MS is being vibrated	5	1.6	1.4	1.6	PASS
	19	1.8	1.5	1.4	PASS

frequency error(Hz)	Power control LEVEL	Result			
		GSM900			
		ARFCN			
		LCH	MCH	HCH	Result
TN VN	5	6	4	5	PASS
	19	5	3	6	PASS
When the MS is being vibrated	5	4	5	5	PASS
	19	6	6	2	PASS

DCS1800

RMS phase error(degree)	Power control LEVEL	Result			
		DCS1800			
		ARFCN			
		LCH	MCH	HCH	Result
TN VN	0	0.5	0.5	0.5	PASS
	15	0.5	0.6	0.5	PASS
When the MS is being vibrated	0	0.5	0.5	0.5	PASS
	15	0.5	0.5	0.6	PASS

Peak phase error(degree)	Power control LEVEL	Result			
		DCS1800			
		ARFCN			
		LCH	MCH	HCH	Result
TN VN	0	1.6	1.6	1.6	PASS
	15	1.7	1.8	1.6	PASS
When the MS is being vibrated	0	1.6	1.6	1.6	PASS
	15	1.6	1.6	1.7	PASS

frequency error(Hz)	Power control LEVEL	Result			
		DCS1800			
		ARFCN			
		LCH	MCH	HCH	Result
TN VN	0	6	8	7	PASS
	15	8	10	14	PASS
When the MS is being vibrated	0	8	5	6	PASS
	15	7	9	8	PASS



Appendix D. Transmitter output power and burst timing

Note: All test modes were carried out for all operation modes and record the worst test mode (GSM 900/1800 TN/VN) of fellow:

A. output power

Transmitter Output power(dBm)	Power level	Result			
		Traffic Channels			
		LCH	MCH	HCH	Result
GSM900					
TN,VN	5	33.26	33.18	33.19	PASS
	12	20.11	20.08	20.04	PASS
	19	4.91	4.83	4.72	PASS

Transmitter Output power(dBm)	Power level	Result			
		Traffic Channels			
		LCH	MCH	HCH	Result
DCS1800					
TN,VN	0	30.00	30.74	30.94	PASS
	8	14.57	15.39	15.39	PASS
	15	1.15	2.03	1.91	PASS

B. Power VS Time


Power VS Time Graph	ACCESS BURST	Result		
		Traffic Channels		
		LCH	MCH	HCH
GSM900	Power level			
TN,VN	5	PASS	PASS	PASS
	12	PASS	PASS	PASS
	19	PASS	PASS	PASS

Power VS Time Graph	ACCESS BURST	Result		
		Traffic Channels		
		LCH	MCH	HCH
DCS1800	Power level			
TN,VN	0	PASS	PASS	PASS
	8	PASS	PASS	PASS
	15	PASS	PASS	PASS


Graphs of output power and burst timing

GSM 900 TN,VN


Channel LCH PCL 5




Channel MCH PCL 5




Channel HCH PCL 5




Channel LCH PCL 12




Channel MCH PCL 12




Channel HCH PCL 12



Channel LCH PCL 19



Channel MCH PCL 19



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.


Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com


Service Hotline: 400 089 2118

Channel HCH PCL 19




DCS1800 TN,VN


Channel LCH PCL 0




Channel MCH PCL 0




Channel HCH PCL 0




Channel LCH PCL 8




Channel MCH PCL 8




Channel HCH PCL 8




Channel LCH PCL 8



Channel MCH PCL 15



Channel HCH PCL 15



Appendix E. Transmitter – Output RF spectrum

Note: All test modes were carried out for all operation modes and record the worst test mode (GSM 900/1800 TN/VN) of fellow:


Modulation& switch Spectrum	Power level	Result		
		Traffic Channels		
GSM900		LCH	MCH	HCH
TN,VN	5	PASS	PASS	PASS
	12	PASS	PASS	PASS
	19	PASS	PASS	PASS

Modulation& switch Spectrum	Power level	Result		
		Traffic Channels		
DCS1800		LCH	MCH	HCH
TN,VN	0	PASS	PASS	PASS
	8	PASS	PASS	PASS
	15	PASS	PASS	PASS


Graphs of output RF spectrum

GSM 900 TN,VN

Channel LCH PCL 5



Channel MCH PCL 5



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.


Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088


E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118

Channel HCH PCL 5



Channel LCH PCL 12



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,


Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088


E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118

Channel MCH PCL 12



Channel HCH PCL 12



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.


Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088


E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118

Channel LCH PCL 19



Channel MCH PCL 19



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.


Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088


E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118


Channel HCH PCL 19




DCS1800 TN,VN Channel LCH PCL 0




Channel MCH PCL 0




Channel HCH PCL 0




Channel LCH PCL 8




Channel MCH PCL 8




Channel HCH PCL 8




Channel LCH PCL 8



Channel MCH PCL 15



Channel HCH PCL 15



Appendix F. Transmitter output power in GPRS multislot configuration

Note: All test modes were carried out for all operation modes and record the worst test mode (GSM 900/1800 TN/VN) of fellow:

A. output power

Transmitter Output power(dBm)	Power level	Result			
		Traffic Channels			
GSM900		LCH	MCH	HCH	Result
TN,VN	5	30.14	30.01	29.99	PASS
	12	20.12	20.08	19.94	PASS
	19	5.08	4.96	4.83	PASS

Transmitter Output power(dBm)	Power level	Result			
		Traffic Channels			
DCS1800		LCH	MCH	HCH	Result
TN,VN	0	26.05	26.48	26.70	PASS
	8	14.13	14.92	14.99	PASS
	15	1.00	1.93	1.81	PASS

B. Power VS Time


Power VS Time Graph	ACCESS BURST	Result		
		Traffic Channels		
GSM900	Power level	LCH	MCH	HCH
TN,VN	5	PASS	PASS	PASS
	12	PASS	PASS	PASS
	19	PASS	PASS	PASS

Power VS Time Graph	ACCESS BURST	Result		
		Traffic Channels		
DCS1800	Power level	LCH	MCH	HCH
TN,VN	0	PASS	PASS	PASS
	8	PASS	PASS	PASS
	15	PASS	PASS	PASS


Graphs of output power in GPRS multislot configuration

GSM 900 TN,VN

Channel LCH PCL 5



Channel MCH PCL 5



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.


Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088


E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118


Channel HCH PCL 5




Channel LCH PCL 12




Channel MCH PCL 12




Channel HCH PCL 12




Channel LCH PCL 19




Channel MCH PCL 19




Channel HCH PCL 19




DCS1800 TN,VN Channel LCH PCL 0



Channel MCH PCL 0



Channel HCH PCL 0



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.


Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088


E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118


Channel LCH PCL 8




Channel MCH PCL 8




Channel HCH PCL 8




Channel LCH PCL 15



Channel MCH PCL 15



Channel HCH PCL 15



Appendix G. Output RF spectrum in GPRS multislot configuration

Note: All test modes were carried out for all operation modes and record the worst test mode (GSM 900/1800 TN/VN) of fellow:


Modulation& switch Spectrum	Power level	Result		
		Traffic Channels		
GSM900		LCH	MCH	HCH
TN,VN	5	PASS	PASS	PASS
	12	PASS	PASS	PASS
	19	PASS	PASS	PASS

Modulation& switch Spectrum	Power level	Result		
		Traffic Channels		
DCS1800		LCH	MCH	HCH
TN,VN	0	PASS	PASS	PASS
	8	PASS	PASS	PASS
	15	PASS	PASS	PASS


Graphs of output RF spectrum in GPRS multislot configuration

GSM 900 TN,VN

Channel LCH PCL 5



Channel MCH PCL 5



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.


Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088


E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118


Channel HCH PCL 5




Channel LCH PCL 12




Channel MCH PCL 12




Channel HCH PCL 12




Channel LCH PCL 19



Channel MCH PCL 19




Channel HCH PCL 19




DCS1800 TN,VN


Channel LCH PCL 0




Channel MCH PCL 0




Channel HCH PCL 0




Channel LCH PCL 8




Channel MCH PCL 8




Channel HCH PCL 8




Channel LCH PCL 15



Channel MCH PCL 15



Channel HCH PCL 15



Appendix H. Conducted spurious emissions - MS allocated a channel

Note: All test modes were carried out for all operation modes and record the worst test mode (GSM 900/1800 MCH VN) of follow:


Conducted spurious emissions	GSM900;VN			
Frequency range	RBW(Hz)	Max.Limit(dBm)	MCH(dBm)	Result
100kHz~50MHz	10k	-36	-58.62	PASS
50MHz~500MHz	100k	-36	-55.31	PASS
500MHz~850MHz	3M	-36	-43.55	PASS
850MHz~860MHz	1M	-36	-48.48	PASS
860MHz~870MHz	300k	-36	-52.33	PASS
870MHz~880MHz	100k	-36	-57.72	PASS
915MHz~925MHz	100k	-36	-57.92	PASS
960MHz~1GHz	3M	-36	-44.38	PASS
1GHz~1805MHz	3M	-30	-44.56	PASS
1880MHz~12.75GHz	3M	-30	-33.84	PASS
896.6MHz~900.8MHz	30K	-36	-62.44	PASS
904.4MHz~908.6MHz	30K	-36	-61.94	PASS
880MHz~896.6MHz	100K	-36	-57.42	PASS
908.6MHz~915MHz	100K	-36	-57.59	PASS

Conducted spurious emissions	DCS1800;VN			
Frequency range	RBW(Hz)	Max.Limit(dBm)	MCH(dBm)	Result
100kHz~50MHz	10k	-36	-57.04	PASS
50MHz~500MHz	100k	-36	-54.77	PASS
500MHz~925MHz	3M	-36	-42.86	PASS
960MHz~1GHz	3M	-36	-48.97	PASS
1GHz~1680MHz	3M	-30	-44.41	PASS
1680MHz~1690MHz	1M	-30	-49.49	PASS
1690MHz~1700MHz	300k	-30	-55.02	PASS
1700MHz~1710MHz	100k	-30	-58.88	PASS
1785MHz~1795MHz	100K	-30	-59.11	PASS
1795MHz~1805MHz	300k	-30	-54.86	PASS
1880MHz~12.75GHz	3M	-30	-33.68	PASS
1741.4MHz~1745.6MHz	30K	-36	-63.90	PASS
1749.2MHz~1753.4MHz	30K	-36	-64.58	PASS
1710MHz~1741.4MHz	100K	-36	-58.96	PASS
1753.4MHz~1785MHz	100K	-36	-58.71	PASS

Graphs of conducted spurious emission-MS allocated a channel

GSM900: channel MCH VN

100kHz~50MHz



Date: 28.AUG.2019 20:39:44



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.


Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com


Service Hotline: 400 089 2118

50MHz~500MHz




Date: 28.AUG.2019 20:39:58

500MHz~850MHz




Date: 28.AUG.2019 20:40:12

850MHz~860MHz




Date: 28.AUG.2019 20:40:26

860MHz~870MHz



Date: 28.AUG.2019 20:40:40

870MHz~880MHz




Date: 28.AUG.2019 20:40:54

915MHz~925MHz




Date: 28.AUG.2019 20:41:08


960MHz~1GHz



1GHz~1805MHz




1880MHz~12.75GHz




Date: 28.AUG.2019 20:41:50

896.6MHz~900.8MHz




Date: 28.AUG.2019 20:42:04

904.4MHz~908.6MHz




Date: 28.AUG.2019 20:42:18

880MHz~896.6MHz



Date: 28.AUG.2019 20:42:32


908.6MHz~915MHz



Date: 28.AUG.2019 20:42:46


DCS1800: channel MCH VN

9kHz~100kHz




Date: 29.AUG.2019 09:55:20


100kHz~50MHz




50MHz~500MHz




500MHz~925MHz



960MHz~1GHz




1GHz~1680MHz




Date: 29.AUG.2019 09:56:30

1680MHz~1690MHz




Date: 29.AUG.2019 09:56:44

1690MHz~1700MHz




Date: 29.AUG.2019 09:56:58

1700MHz~1710MHz




Date: 29.AUG.2019 09:57:12

1785MHz~1795MHz




Date: 29.AUG.2019 09:57:26

1795MHz~1805MHz




Date: 29.AUG.2019 09:57:39

1880MHz~12.75GHz




Date: 29.AUG.2019 09:57:53

1741.4MHz~1745.6MHz




Date: 29.AUG.2019 09:58:07

1749.2MHz~1753.4MHz




Date: 29.AUG.2019 09:58:21

1710MHz~1741.4MHz



Date: 29.AUG.2019 09:58:35

1753.4MHz~1785MHz



Date: 29.AUG.2019 09:58:49



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118

Appendix I. Conducted spurious emissions- MS in idle mode

Note: All test modes were carried out for all operation modes and record the worst test mode (GSM 900/1800 MCH VN) of fellow:


Conducted spurious emissions	GSM900;VN			
Frequency range	RBW(Hz)	Max.Limit(dBm)	MCH(dBm)	Result
100kHz~50MHz	10k	-57	-67.57	PASS
50MHz~880MHz	100k	-57	-63.02	PASS
880MHz~915MHz	100k	-59	-62.57	PASS
915MHz~1000MHz	100k	-57	-57.70	PASS
1GHz~1710MHz	100k	-47	-59.45	PASS
1710MHz~1785MHz	100k	-53	-59.33	PASS
1785MHz~12.75GHz	100k	-47	-47.78	PASS

Conducted spurious emissions	DCS1800;VN			
Frequency range	RBW(Hz)	Max.Limit(dBm)	MCH(dBm)	Result
100kHz~50MHz	10k	-57	-68.43	PASS
50MHz~880MHz	100k	-57	-63.28	PASS
880MHz~915MHz	100k	-59	-61.43	PASS
915MHz~1000MHz	100k	-57	-57.21	PASS
1GHz~1710MHz	100k	-47	-59.59	PASS
1710MHz~1785MHz	100k	-53	-57.78	PASS
1785MHz~12.75GHz	100k	-47	-48.08	PASS

Graphs of conducted spurious emission-MS in idle mode


GSM900: channel MCH VN

100kHz~50MHz




Date: 28.AUG.2019 20:43:26

50MHz~880MHz




Date: 28.AUG.2019 20:43:39

880MHz~915MHz




Date: 28.AUG.2019 20:44:09

915MHz~1000MHz




Date: 28.AUG.2019 20:44:22

1GHz~1710MHz




Date: 28.AUG.2019 20:44:35

1710MHz~1785MHz



Date: 28.AUG.2019 20:44:48


1785MHz~12.75GHz



Date: 28.AUG.2019 20:45:01


DCS1800: channel MCH VN

100kHz~50MHz




Date: 29.AUG.2019 10:05:20

50MHz~880MHz




Date: 29.AUG.2019 10:05:32

880MHz~915MHz




Date: 29.AUG.2019 10:06:03

915MHz~1000MHz




Date: 29.AUG.2019 10:06:16

1GHz~1710MHz




Date: 29.AUG.2019 10:06:28

1710MHz~1785MHz



1785MHz~12.75GHz



Appendix J.Receiver Blocking and spurious response – speech channel

GSM900

FREQUENCY	Measurement Result	
	GSM900	
	Small MS	
	Interference Level in dBμVemf()	Result
FR +/- 600 kHz to FR +/- 800 kHz	70	PASS
FR +/- 800 kHz to FR +/- 1.6 MHz	70	PASS
FR +/- 1.6 MHz to FR +/- 3 MHz	80	PASS
915 MHz to FR - 3 MHz	90	PASS
FR + 3 MHz to 980 MHz	90	PASS
835 MHz to <915 MHz	113	PASS
>980 MHz to 1000 MHz	113	PASS
100 kHz to <835 MHz	90	PASS
>1000 MHz to 12.75 GHz	90	PASS

DCS1800

FREQUENCY	Measurement Result	
	DCS1800	
	Small MS	
	Interference Level in dBμVemf()	Result
FR +/- 600 kHz to FR +/- 800 kHz	70	PASS
FR +/- 800 kHz to FR +/- 1.6 MHz	70	PASS
FR +/- 1.6 MHz to FR +/- 3 MHz	80	PASS
1785 MHz to FR - 3 MHz	87	PASS
FR + 3 MHz to 1920 MHz	87	PASS
100 kHz to 1705 MHz	113	PASS
>1705 MHz to <1785 MHz	101	PASS
>1920 MHz to 1980 MHz	101	PASS
>1980 MHz to 12.75 GHz	90	PASS



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118

Appendix K. Intermodulation rejection - speech channels

Note: All test modes were carried out for all operation modes and record the worst test mode (GSM 900/1800 TNVN) of fellow:

GSM900

	Intermodulation Test Signal Levels		Result
TNVN	Wanted Signal dBuVemf()	15	Pass
	First Interferer dBuVemf()	64	Pass
	Second Interferer dBuVemf()	63	Pass

GSM1800

	Intermodulation Test Signal Levels		Result
TNVN	Wanted Signal dBuVemf()	15	Pass
	First Interferer dBuVemf()	68	Pass
	Second Interferer dBuVemf()	68	Pass



Appendix L.Frequency error and Modulation accuracy in EGPRS Configuration

Note: All test modes were carried out for all operation modes and record the worst test mode (GSM 900/1800 TNVN) of fellow:

GSM900

TN,VN			≤9%	≤15%	≤30%	≤10E-7	Result
BAND	ARFCN	PCL	RMS EVM	the 95% EVM	Peak EVM	Frequency error	
GSM900	LCH	8	1.1	1.9	2.5	7	PASS
		19	0.5	1.1	1.6	6	PASS
	MCH	8	1.1	1.9	2.6	5	PASS
		19	0.6	1.1	1.7	4	PASS
	HCH	8	1.1	1.9	2.7	4	PASS
		19	0.6	1.2	1.7	6	PASS

DCS1800

TN,VN			≤9%	≤15%	≤30%	≤10E-7	Result
BAND	ARFCN	PCL	RMS EVM	the 95% EVM	Peak EVM	Frequency error	
DCS1800	LCH	2	1.0	1.9	2.7	7	PASS
		15	1.5	2.6	3.5	4	PASS
	MCH	2	1.0	1.9	2.8	9	PASS
		15	1.5	2.5	3.4	7	PASS
	HCH	2	1.0	1.8	2.6	6	PASS
		15	1.4	2.5	3.4	10	PASS



Appendix M. Frequency error under multipath and interference conditions in EGPRS Configuration

Note: All test modes were carried out for all operation modes and record the worst test mode (GSM 900/1800 TNVN) of fellow:

GSM900

Fading set	Test conditions	Result			
		GSM900			
		ARFCN			
		LCH	MCH	HCH	Result
RA250	TNVN	7	8	6	PASS
HT100	TNVN	8	5	4	PASS
TU50	TNVN	7	6	6	PASS
TU3	TNVN	6	7	7	PASS

DCS1800

Fading set	Test conditions	Result			
		DCS1800			
		ARFCN			
		LCH	MCH	HCH	Result
RA130	TNVN	8	10	12	PASS
HT100	TNVN	7	13	12	PASS
TU50	TNVN	8	12	9	PASS
TU1.5	TNVN	8	12	12	PASS

Appendix N. EGPRS Transmitter output power

Note: All test modes were carried out for all operation modes and record the worst test mode (GSM 900/1800 TNVN) of fellow:

A. output power

Transmitter Output power(dBm)	Power level	Result			
		Traffic Channels			
		LCH	MCH	HCH	Result
GSM900					
TN,VN	8	26.47	26.28	26.34	PASS
	12	18.63	18.48	18.43	PASS
	19	4.33	3.94	4.16	PASS

Transmitter Output power(dBm)	Power level	Result			
		Traffic Channels			
		LCH	MCH	HCH	Result
DCS1800					
TN,VN	2	25.80	25.58	25.32	PASS
	8	13.80	13.67	13.43	PASS
	15	-0.84	-0.85	-1.26	PASS

B. Power VS Time


Power VS Time Graph	ACCESS BURST	Result		
		Traffic Channels		
		LCH	MCH	HCH
GSM900	Power level			
TN,VN	8	PASS	PASS	PASS
	12	PASS	PASS	PASS
	19	PASS	PASS	PASS

Power VS Time Graph	ACCESS BURST	Result		
		Traffic Channels		
		LCH	MCH	HCH
DCS1800	Power level			
TN,VN	2	PASS	PASS	PASS
	8	PASS	PASS	PASS
	15	PASS	PASS	PASS


Graphs of EGPRS Transmitter output power

GSM 900 TN,VN

Channel LCH PCL 8



Channel MCH PCL 8



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.


Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088


E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118


Channel HCH PCL 8




Channel LCH PCL 12




Channel MCH PCL 12




Channel HCH PCL 12



Channel LCH PCL 19



Channel MCH PCL 19



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com


Service Hotline: 400 089 2118

Channel HCH PCL 19




DCS1800 TN,VN


Channel LCH PCL 2



Channel MCH PCL 2



Channel HCH PCL 2



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.


Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088


E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118

Channel LCH PCL 8



Channel MCH PCL 8



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088


E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118


Channel HCH PCL 8




Channel LCH PCL 8



Channel MCH PCL 15



Channel HCH PCL 15



Appendix O. Output RF spectrum in EGPRS configuration

Note: All test modes were carried out for all operation modes and record the worst test mode (GSM 900/1800 TNVN) of fellow:


Modulation& switch Spectrum	Power level	Result		
		Traffic Channels		
GSM900		LCH	MCH	HCH
TN,VN	8	PASS	PASS	PASS
	12	PASS	PASS	PASS
	19	PASS	PASS	PASS

Modulation& switch Spectrum	Power level	Result		
		Traffic Channels		
DCS1800		LCH	MCH	HCH
TN,VN	2	PASS	PASS	PASS
	8	PASS	PASS	PASS
	15	PASS	PASS	PASS


Graphs of output RF spectrum in EGPRS multislot configuration

GSM 900 TN,VN


Channel LCH PCL 8




Channel MCH PCL 8




Channel HCH PCL 8




Channel LCH PCL 12




Channel MCH PCL 12




Channel HCH PCL 12



Channel LCH PCL 19



Channel MCH PCL 19



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.


Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088


E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118


Channel HCH PCL 19




DCS1800 TN,VN
Channel LCH PCL 2




Channel MCH PCL 2




Channel HCH PCL 2




Channel LCH PCL 8




Channel MCH PCL 8




Channel HCH PCL 8




Channel LCH PCL 15



Channel MCH PCL 15



Channel HCH PCL 15



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118

Appendix P. Blocking and spurious response in EGPRS configuration

GSM900

FREQUENCY	Measurement Result	
	GSM900	
	Small MS	
	Interference Level in dBμVemf()	Result
FR +/- 600 kHz to FR +/- 800 kHz	70	PASS
FR +/- 800 kHz to FR +/- 1,6 MHz	70	PASS
FR +/- 1,6 MHz to FR +/- 3 MHz	80	PASS
915 MHz to FR - 3 MHz	90	PASS
FR + 3 MHz to 980 MHz	90	PASS
835 MHz to <915 MHz	113	PASS
>980 MHz to 1000 MHz	113	PASS
100 kHz to <835 MHz	113	PASS
>1000 MHz to 12,75 GHz	113	PASS

DCS1800

FREQUENCY	Measurement Result	
	DCS1800	
	Small MS	
	Interference Level in dBμVemf()	Result
FR +/- 600 kHz to FR +/- 800 kHz	70	PASS
FR +/- 800 kHz to FR +/- 1,6 MHz	70	PASS
FR +/- 1,6 MHz to FR +/- 3 MHz	80	PASS
1785 MHz to FR - 3 MHz	87	PASS
FR + 3 MHz to 1920 MHz	87	PASS
100 kHz to 1705 MHz	113	PASS
>1705 MHz to <1785 MHz	101	PASS
>1920 MHz to 1980 MHz	101	PASS
>1980 MHz to 12,75 GHz	113	PASS



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118

Appendix Q. AM suppression - speech channels

GSM900

Channel	Propagation conditions	Type of measurement	Test limit error rate %	Minimum No. of max-samples	Result	
TCH/FS Class II	Static	RBER	2,439	8200	0.632%	Pass

GSM1800

Channel	Propagation conditions	Type of measurement	Test limit error rate %	Minimum No. of max-samples	Result	
TCH/FS Class II	Static	RBER	2,439	8200	0.812%	Pass



Appendix R. Intermodulation rejection - EGPRS

Note: All test modes were carried out for all operation modes and record the worst test mode (GSM 900/1800 TNVN) of fellow:

GSM900

	Intermodulation Test Signal Levels	Small MS	Result
TNVN	FIRST INTERFERER dBμVemf()	64	Pass
	SECOND INTERFERER dBμVemf()	63	Pass

GSM1800

	Intermodulation Test Signal Levels	Small MS	Result
TNVN	FIRST INTERFERER dBμVemf()	68	Pass
	SECOND INTERFERER dBμVemf()	68	Pass



Adjacent S. Adjacent channel rejection – EGPRS

Note: All test modes were carried out for all operation modes and record the worst test mode (GSM 900/1800 TNVN) of fellow:

GSM900

	Channel types	Block per s	Channel types	Derived test limit	Target number of samples	Target test time /s	Target test time /hh:mm:ss	Result
TNVN	USF/MCS-1 to 9	50	0,01	0,01234	27958	559	00:09:19	Pass

GSM1800

	Channel types	Block per s	Channel types	Derived test limit	Target number of samples	Target test time /s	Target test time /hh:mm:ss	Result
TNVN	USF/MCS-1 to 9	50	0,01	0,01234	27958	559	00:09:19	Pass



Appendix T .Adjacent channel rejection - speech channels (TCH/FS)

Note: All test modes were carried out for all operation modes and record the worst test mode (GSM 900/1800 TNVN) of fellow:

GSM900

	Channel	Interference at	Type of Measurement	Test limit error rate %	Minimum No. of samples	Result
TNVN	TCH/FS class Ib class II	200 kHz	FER RBER RBER	6,742* α 0,420/ α 8,333	8 900 1 000 000 600 000	Pass
	TCH/FS class Ib class II	400 kHz	FER RBER RBER	11,461* α 0,756/ α 9,167	8 900 1 000 000 600 000	Pass

GSM1800

	Channel	Interference at	Type of Measurement	Test limit error rate %	Minimum No. of samples	Result
TNVN	TCH/FS class Ib class II	200 kHz	FER RBER RBER	3,371* α 0,270/ α 8,333	17 800 2 000 000 1 200 000	Pass
	TCH/FS class Ib class II	400 kHz	FER RBER RBER	5,714* α 0,483/ α 9,167	10 500 1 200 000 720 000	Pass



Appendix U. Reference sensitivity - TCH/FS

Note: All test modes were carried out for all operation modes and record the worst test mode (GSM 900/1800 TNVN) of fellow:

GSM900

	Channels	Propagation conditions TUhigh		Propagation conditions RA		Propagation conditions HT		Static conditions		Result
		Test limit Error rate %	Minimum No. of samples	Test limit error rate %	Minimum No. of samples	Test limit error rate %	Minimum No. of samples	Test limit error rate %	Minimum No. of samples	
TNVN	TCH/FS	1	8 900					1	164 000	Pass
	FER class Ib(RBER)	0,06	1 000000	6,55	24 000	5,49	60 000	0,07	20000000	
	class II(RBER)	4,1	120 000					6,58	8 200	

GSM1800

	Channels	Propagation conditions TUhigh		Propagation conditions RA		Propagation conditions HT		Static conditions		Result
		Test limit Error rate %	Minimum No. of samples	Test limit error rate %	Minimum No. of samples	Test limit error rate %	Minimum No. of samples	Test limit error rate %	Minimum No. of samples	
TNVN	TCH/FS	1	13 400					1	164 000	Pass
	FER class Ib(RBER)	0,06	1500000	5,75	24 000	5,64	30 000	0,07	20000000	
	class II(RBER)	5,44	60 000					6,58	8 200	



Appendix V. Reference sensitivity - FACCH/F

GSM900

Channel	Propagation	Type of Measurement	Test limit error rate %	Result	
FACCH/F	TUhigh	FER	7.728	3.246%	Pass

GSM1800

Channel	Propagation	Type of Measurement	Test limit error rate %	Result	
FACCH/F	TUhigh	FER	8.064	3.128%	Pass



Appendix W. Minimum Input level for Reference Performance - GPRS

Note: All test modes were carried out for all operation modes and record the worst test mode (GSM 900/1800 TNVN) of fellow:

GSM900

	Type of channel	Propagation conditions							
		static	TUhigh (no FH)	TUhigh (ideal FH)	RA (no FH)	HT (no FH)	BLER	Result	
GSM 900									
TNVN	PDTCH/CS-1 dBm	-104	-104	-104	-104	-103	10 %	0.1 %	Pass
	PDTCH/CS-2 dBm	-104	-100	-101	-101	-99	10 %	0.1 %	Pass
	PDTCH/CS-3 dBm	-104	-98	-99	-98	-96	10 %	0.1 %	Pass
	PDTCH/CS-4 dBm	-101	-90	-90	--		10 %	0.1 %	Pass
	USF/CS-1 dBm	< -104	<-101	<-103	<-103	<-101	1 %	0.1 %	Pass
	USF/CS-2to 4 dBm	< -104	<-103	<-104	<-104	<-104	1 %	0.1 %	Pass

GSM1800

	Type of channel	Propagation conditions							Result
		static	TUhigh (no FH)	TUhigh (ideal FH)	RA (no FH)	HT (no FH)	BLER		
	GSM 1800								
TNVN	PDTCH/CS-1 dBm	-104	-104	-104	-104	-109	10 %	0.1 %	Pass
	PDTCH/CS-2 dBm	-104	-100	-100	-101	-99	10 %	0.1 %	Pass
	PDTCH/CS-3 dBm	-104	-98	-98	-98	-94	10 %	0.1 %	Pass
	PDTCH/CS-4 dBm	-101	-88	-88	--		10 %	0.1 %	Pass
	USF/CS-1 dBm	< -104	<-103	<-103	<-103	<-101	1 %	0.1 %	Pass
	USF/CS-2to 4 dBm	< -104	<-104	<-104	<-104	<-103	1 %	0.1 %	Pass

Appendix X. Minimum Input level for Reference Performance – EGPRS

Note: All test modes were carried out for all operation modes and record the worst test mode (GSM 900/1800 TNVN) of fellow:

GSM900

	Type of Channel	Propagation conditions					Result
		static	TUhigh (no FH)	TUhigh (ideal FH)	RA (no FH)	HT (no FH)	
TNVN	USF/MCS-5 to 9 dBm	-102	-97,5	-99	-100	-99	Pass

GSM1800

	Type of Channel	Propagation conditions					Result
		static	TUhigh (no FH)	TUhigh (ideal FH)	RA (no FH)	HT (no FH)	
TNVN	USF/MCS-5 to 9 dBm	-102	-97,5	-99	-100	-99	Pass



Appendix Y. Radiated spurious emissions - MS in idle mode

Note: All test modes were carried out for all operation modes and record the worst test mode (GSM 900/1800 MCH VN) of fellow

GSM900

Radiated spurious emissions	GSM900 VN			
Frequency range	RBW(Hz)	Max.Limit(dBm)	MCH(dBm)	Result
30MHz~880MHz	10k	-57	-60.25	PASS
880MHz~915MHz	10k	-59	-61.94	PASS
915MHz~1000MHz	100k	-57	-61.00	PASS
1GHz~1710MHz	100k	-47	-66.13	PASS
1710MHz~1785MHz	100k	-53	-60.47	PASS
1785MHz~4GHz	100k	-47	-59.36	PASS

GSM1800

Radiated spurious emissions	GSM1800 VN			
Frequency range	RBW(Hz)	Max.Limit(dBm)	MCH(dBm)	Result
30MHz~880MHz	10k	-57	-61.42	PASS
880MHz~915MHz	10k	-59	-66.33	PASS
915MHz~1000MHz	100k	-57	-65.17	PASS
1GHz~1710MHz	100k	-47	-66.99	PASS
1710MHz~1785MHz	100k	-53	-67.24	PASS
1785MHz~4GHz	100k	-47	-58.27	PASS




APPENDIX Z. RADIATED SPURIOUS EMISSIONS TEST RESULT

All test modes were carried out for all operation modes

The (middle channel) was showed as the follow:


Note: The filter has been used in this test.

RADIATED SPURIOUS EMISSIONS GSM 900- HORIZONTAL



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	52.3100	-98.33	-65.34	-36.00	29.34	32.99	46	Horizontal
2	154.1600	-101.15	-71.82	-36.00	35.82	29.33	80	Horizontal
3	612.0000	-100.52	-60.64	-36.00	24.64	39.88	215	Horizontal
4	1268.8269	-51.32	-55.02	-30.00	25.02	-3.70	359	Horizontal
5	2164.1164	-53.21	-51.40	-30.00	21.40	1.81	181	Horizontal
6	3194.4194	-53.09	-47.45	-30.00	17.45	5.64	265	Horizontal

RADIATED SPURIOUS EMISSIONS GSM 900- VERTICAL



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	52.3100	-93.18	-63.01	-36.00	27.01	30.17	273	Vertical
2	137.6700	-99.90	-65.67	-36.00	29.67	34.23	163	Vertical
3	404.4200	-99.78	-64.73	-36.00	28.73	35.05	256	Vertical
4	1392.7393	-51.43	-49.98	-30.00	19.98	1.45	315	Vertical
5	2232.2232	-52.12	-50.24	-30.00	20.24	1.88	18	Vertical
6	3031.2031	-53.59	-48.33	-30.00	18.33	5.26	256	Vertical



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.


Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118

RADIATED SPURIOUS EMISSIONS GSM 1800- HORIZONTAL



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	52.3100	-98.48	-65.49	-36.00	29.49	32.99	229	Horizontal
2	142.520	-101.13	-71.76	-36.00	35.76	29.37	75	Horizontal
3	489.780	-101.11	-64.98	-36.00	28.98	36.13	126	Horizontal
4	1182.71	-50.87	-54.75	-30.00	24.75	-3.88	281	Horizontal
5	2048.60	-51.44	-50.53	-30.00	20.53	0.91	151	Horizontal
6	3704.17	-53.81	-46.99	-30.00	16.99	6.82	290	Horizontal



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.


Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118

RADIATED SPURIOUS EMISSIONS GSM 1800- VERTICAL



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	48.4300	-94.98	-65.43	-36.00	29.43	29.55	321	Vertical
2	138.6400	-102.05	-67.75	-36.00	31.75	34.30	94	Vertical
3	466.5000	-101.24	-65.32	-36.00	29.32	35.92	146	Vertical
4	1361.8362	-50.94	-49.70	-30.00	19.70	1.24	190	Vertical
5	1881.7882	-52.31	-51.49	-30.00	21.49	0.82	9	Vertical
6	3182.4182	-53.72	-48.20	-30.00	18.20	5.52	120	Vertical



APPENDIX A1: PHOTOGRAPHS OF TEST SETUP

RADIATED SPURIOUS EMISSION TEST SETUP



RADIATED SPURIOUS EMISSION ABOVE 1G TEST SETUP



----END OF REPORT----