



RADIO TEST REPORT

ETSI EN 301 908-1 V13.1.1 (2019-11)

ETSI EN 301 908-2 V13.1.1 (2020-06)

Product : Smartphone

Trade Mark : CUBOT

Model Name : KINGKONG 5

Family Model : N/A

Report No. : S21042201103005

Prepared for

Shenzhen Huafurui Technology Co., Ltd.

Unit 1401 & 1402, 14/F, Jinqi Zhigu Mansion (No. 4 Building of Chongwen Garden),
Crossing of the Liuxian Street and Tangling Road, Taoyuan Street, Nanshan District,
Shenzhen, P.R. China

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street
Bao'an District, Shenzhen 518126 P.R. China

Tel. 400-800-6106, 0755-2320 0050, 0755-2320 0090

Website: <http://www.ntek.org.cn>

TEST RESULT CERTIFICATION

Applicant's name Shenzhen Huafurui Technology Co., Ltd.
Address Unit 1401 & 1402, 14/F, Jinqi Zhigu Mansion (No. 4 Building of Chongwen Garden), Crossing of the Liuxian Street and Tangling Road, Taoyuan Street, Nanshan District, Shenzhen, P.R. China

Manufacturer's Name .. Shenzhen Huafurui Technology Co., Ltd.
Address Unit 1401 & 1402, 14/F, Jinqi Zhigu Mansion (No. 4 Building of Chongwen Garden), Crossing of the Liuxian Street and Tangling Road, Taoyuan Street, Nanshan District, Shenzhen, P.R. China

Product description

Product name Smartphone
Trademark CUBOT
Model Name KINGKONG 5
Family Model N/A

Standards ETSI EN 301 908-1 V13.1.1 (2019-11)
 ETSI EN 301 908-2 V13.1.1 (2020-06)

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with the article 3.2 of the Directive 2014/53/EU requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personnel only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests Apr 22, 2021 ~May 19, 2021
Date of Issue..... May 19, 2021
Test Result..... **Pass**

Testing Engineer : Cheng Jiawen
 (Cheng Jiawen)

Technical Manager : Jason Chen
 (Jason Chen)

Authorized Signatory : Alex
 (Alex Li)

Table of Contents**Page**

1 . SUMMARY OF TEST RESULTS	5
1.1 TEST FACILITY	6
1.2 MEASUREMENT UNCERTAINTY	6
2 . GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 LIST OF TEST EQUIPMENTS	8
2.3 TEST ENVIRONMENT/CONDITIONS	9
2.4 TEST Mode	10
3 . SUMMARY OF TEST REPORT	11
4. TEST PROCEDURES AND RESULTLS	12
4.1 TERMS IN THE COLUMN “VERDICT” FOR THE TEST RESULTS LIST OF THISSECTION:	12
4.2 TABLE 1 EN REQUIREMENTS TABLE	12
4.3 ETSI EN 301 908-1	14
§4.3.1 – RADIATED EMISSIONS (UE)	14
Applicable Standard & Limits	14
Test Procedure	14
Test Data	14
§4.3.2 –Control and monitoring functions (UE)	19
Definition & Limits	19
Test method	19
Test Data	19
§4.3.3 —Out-of-synchronization handling of output power	20
Test Procedure	21
Test Data	21
5. PHOTOGRAPHS OF THE TEST SETUP	22

1. SUMMARY OF TEST RESULTS

Leading Reference Documents For Testing:

No.	Identity	Document Title
1	ETSI EN 301 908-1	IMT cellular networks; Harmonised Standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU; Part 1: Introduction and common requirements
2	ETSI EN 301 908-2	IMT cellular networks; Harmonised Standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU; Part 2: CDMA Direct Spread (UTRA FDD) User Equipment (UE)

Specific Reference Documents For Testing:

No.	Identity	Document Title
3	3GPP TS 34.121-1	3 rd Generation Partnership Project; Technical Specification Group Radio Access Network ; Terminal conformance specification; Radio transmission and reception (FDD)
4	3GPP TS 34.121-2	3 rd Generation Partnership Project; Technical Specification Group Radio Access Network User Equipment (UE) conformance specification; Radio transmission and reception (FDD); Part 2: Implementation Conformance Statement (ICS)

1.1 TEST FACILITY

Shenzhen NTEK Testing Technology Co., Ltd.

Add. : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen 518126 P.R. China

FCC Registered No.: 463705 IC Registered No.:9270A-1

CNAS Registration No.:L5516

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95 %**.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power,conducted	$\pm 0.16\text{dB}$
3	Spurious emissions,conducted	$\pm 0.21\text{dB}$
4	All emissions,radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^\circ\text{C}$
7	Humidity	$\pm 2\%$

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment :	Smartphone
Trade Mark:	CUBOT
Model Name:	KINGKONG 5
Family Model:	N/A
Model Difference:	N/A
Support Band:	<input checked="" type="checkbox"/> WCDMA Band I (2100MHz) <input type="checkbox"/> WCDMA Band II (1900MHz) <input type="checkbox"/> WCDMA Band V (850MHz) <input checked="" type="checkbox"/> WCDMA Band VIII(900MHz)
Release Version:	R99
Frequency Bands:	Uplink: WCDMA Band I :1920~1980MHz WCDMA Band VIII:880~915MHz
	Downlink: WCDMA Band I :2110~2170MHz WCDMA Band VIII:925~960MHz
Modulation Mode:	WCDMA(HSDPA/HSUPA):QPSK
Power Class:	3
Antenna Description:	FPC antenna (Band I : 0.75dBi, Band VIII: 0.52dBi)
Battery	DC 3.85V, 5000mAh, 19.25Wh
Adapter	Model: HJ-0502000W2-EU Input: AC 100-240V~50/60Hz 0.3A Output: DC 5V---2.0A 10.0W
Power Supply	DC 3.85V from battery or DC 5V from Adapter
Hard Ware Version	TE826_MAIN_PCB_V1.1
Soft Ware Version	CUBOT_KINGKONG 5_B023C_V02_20210513

2.2 LIST OF TEST EQUIPMENTS

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2020.05.11 2021.04.27	2021.05.10 2022.04.26	1 year
2	Test Receiver	R&S	ESPI7	101318	2020.05.11 2021.04.27	2021.05.10 2022.04.26	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2021.03.29	2022.03.28	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200983705	2020.05.11	2023.05.10	3 year
5	Spectrum Analyzer	Agilent	N9020A	MY46471732	2020.05.11 2021.04.27	2021.05.10 2022.04.26	1 year
6	Horn Antenna	EM	EM-AH-20180	2011071402	2021.03.29	2022.03.28	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2020.11.20	2021.11.19	1 year
8	Amplifier	EMC	EMC051835S E	980246	2020.07.13	2021.07.12	1 year
9	Loop Antenna	ARA	PLA-2030/B	1029	2020.05.11 2021.04.27	2021.05.10 2022.04.26	1 year
10	Temperature & Humidity Chamber	GIANT FORCE	GTH-056P	GF-94454-1	2020.07.13	2021.07.12	1 year
11	LTE Wireless Communications Test Set	R&S	CMW500	1100.008.02	2021.03.29	2022.03.28	1 year
12	Power Splitter	Mini-Circuits	ZN2PD-63-S+	SF025101428	2020.04..07	2023.04.06	3 year
13	Wireless Communication Test	Anritsu	MT8821C	6262192315	2020.11.10	2021.11.09	1 year
14	Power Meter	DARE	RPR3006W	15I00041SNO8 4	2020.07.13	2021.07.12	1 year
15	ESG VETCTOR SIGNAL GENERAROR	Agilent	E4438C	MY45093347	2020.05.11 2021.04.27	2021.05.10 2022.04.26	1 year
16	Spectrum Analyzer	R&S	FSV40	101417	2020.08.07	2021.08.06	1 year

2.3 TEST ENVIRONMENT/CONDITIONS

Normal Temperature (NT):	20 ... 25 °C
Relative Humidity:	30 ... 75 %
Air Pressure:	980 ... 1020 hPa
Extreme Temperature:	Low Temperature (LT) = -10°C High Temperature (HT) = 40°C
Extreme Voltage of the EUT (Declared by manufacturer):	Normal Voltage (NV) = 3.85V Low Voltage (LV) = 3.4V High Voltage (HV) = 4.2V

Note:

The High Voltage 4.2V and Low Voltage 3.4V was declared by manufacturer, The EUT couldn't be operate normally with higher or lower voltage. The High temperature and Low temperature was declared by manufacturer.

2.4 TEST Mode

The following tests were completed according to the test requirements outlined in section 5.2 of the 3GPP TS34.121-1 specification. The EUT supports power Class 3, which has a nominal maximum output power of 24 dBm (1.7/-3.7) 12.2kps RMC is used for this testing. Power control set to All bits up. A summary of these settings are illustrated below:

Test Mode	Test Channel
WCDMA Band I mode	Low:Ch 9612
	Mid:Ch 9750
	High:Ch 9888

Test Mode	Test Channel
WCDMA Band VIII mode	Low:Ch 2712
	Mid:Ch 2788
	High:Ch 2863

3. SUMMARY OF TEST REPORT

ETSI EN 301 908-1	Description of Test	Test Result
§4.2.2	Radiated emissions (UE)	Pass
§4.2.3	Radiated emissions (BS and repeater)	N/A
§4.2.4	Control and monitoring functions (UE)	Pass

ETSI EN 301 908-2	Description of Test	Test Result
§4.2.2	Transmitter maximum output power	Pass
§4.2.3	Transmitter spectrum emission mask	Pass
§4.2.4	Transmitter spurious emissions	Pass
§4.2.5	Transmitter minimum output power	Pass
§4.2.6	Receiver Adjacent Channel Selectivity (ACS)	Pass
§4.2.7	Receiver blocking characteristics	Pass
§4.2.8	Receiver spurious response	Pass
§4.2.9	Receiver intermodulation characteristics	Pass
§4.2.10	Receiver spurious emissions	Pass
§4.2.11	Out-of-synchronization handling of output power	Pass
§4.2.12	Transmitter Adjacent Channel Leakage power Ratio (ACLR)	Pass
§4.2.13	Receiver Reference Sensitivity level	Pass

Note:

- (1) N/A: Test not applicable
- (2) PASS: EUT Pass this test case

4. TEST PROCEDURES AND RESULTS

4.1 TERMS IN THE COLUMN “VERDICT” FOR THE TEST RESULTS LIST OF THIS SECTION:

Verdict	Description
PASS	EUT passed this test case
FAIL	EUT failed this test case
Decl.	“Declaration”: NTEK has received documents from the applicant and/or manufacturer which show conformity to the applied standards for this test case.
N/A	Test case not applicable for the EUT, please see the column “Note” for detailed

4.2 TABLE 1 EN REQUIREMENTS TABLE

Testcase in ETSI EN 301 908-2	Description	Condition	Band I		Band VIII		Test Data
			Sample	Result	Sample	Result	
Section 4.2.2	Transmitter maximum output power	NT / NV	A01	PASS	A01	PASS	Appendix A - WCDMA -Normal
		LT / LV	A01	PASS	A01	PASS	Appendix B - WCDMA -Extreme
		LT / HV	A01	PASS	A01	PASS	Appendix B - WCDMA -Extreme
		HT / LV	A01	PASS	A01	PASS	Appendix B - WCDMA -Extreme
		HT / HV	A01	PASS	A01	PASS	Appendix B - WCDMA -Extreme
Section 4.2.3	Transmitter spectrum emission mask	NT / NV	A01	PASS	A01	PASS	Appendix A - WCDMA -Normal
Section 4.2.4	Transmitter spurious emissions	NT / NV	A01	PASS	A01	PASS	Appendix A - WCDMA -Normal
Section 4.2.5	Transmitter minimum output power	NT / NV	A01	PASS	A01	PASS	Appendix A - WCDMA -Normal
		LT / LV	A01	PASS	A01	PASS	Appendix B - WCDMA -Extreme
		LT / HV	A01	PASS	A01	PASS	Appendix B - WCDMA -Extreme
		HT / LV	A01	PASS	A01	PASS	Appendix B - WCDMA -Extreme
		HT / HV	A01	PASS	A01	PASS	Appendix B - WCDMA -Extreme
Section 4.2.6	Receiver Adjacent Channel Selectivity (ACS)	NT / NV	A01	PASS	A01	PASS	Appendix A - WCDMA -Normal
Section 4.2.7	Receiver blocking characteristics	NT / NV	A01	PASS	A01	PASS	Appendix C - WCDMA -blocking

Testcase in ETSI EN 301 908-2	Description	Condition	Band I		Band VIII		Test Data
			Sample	Result	Sample	Result	
Section 4.2.8	Receiver spurious response	NT / NV	A01	PASS	A01	PASS	Appendix A - WCDMA -Normal
Section 4.2.9	Receiver intermodulation characteristics	NT / NV	A01	PASS	A01	PASS	Appendix A - WCDMA -Normal
Section 4.2.10	Receiver spurious emissions	NT / NV	A01	PASS	A01	PASS	Appendix A - WCDMA -Normal
Section 4.2.11	Out-of-synchronization handling of output power	NT / NV	A01	PASS	A01	PASS	See section 4.3.3 of this report
Section 4.2.12	Transmitter Adjacent Channel Leakage power Ratio (ACLR)	NT / NV	A01	PASS	A01	PASS	Appendix A - WCDMA -Normal
		LT / LV	A01	PASS	A01	PASS	Appendix B - WCDMA -Extreme
		LT / HV	A01	PASS	A01	PASS	Appendix B - WCDMA -Extreme
		HT / LV	A01	PASS	A01	PASS	Appendix B - WCDMA -Extreme
		HT / HV	A01	PASS	A01	PASS	Appendix B - WCDMA -Extreme
Section 4.2.13	Receiver Reference Sensitivity level	NT / NV	A01	PASS	A01	PASS	Appendix A - WCDMA -Normal

4.3 ETSI EN 301 908-1

§4.3.1 – RADIATED EMISSIONS (UE)

Applicable Standard & Limits

The frequency boundary and reference bandwidths for the detailed transitions of the limits between the requirements for out-of-band emissions and spurious emissions are based on ITU-R

Recommendations SM.329-10 [3] and SM.1539-1 [4].

The requirements shown in table 4.2.2.2-1 are only applicable for frequencies in the spurious domain.

Table 4.2.2.2-1: Radiated spurious emissions requirements (UE)

Frequency	Minimum requirement (e.r.p.)/ reference bandwidth idle mode	Minimum requirement (e.r.p.)/ reference bandwidth traffic mode	Applicability
$30 \text{ MHz} \leq f < 1\,000 \text{ MHz}$	-57 dBm/100 kHz	-36 dBm/100 kHz	All
$1 \text{ GHz} \leq f < 12,75 \text{ GHz}$	-47 dBm/1 MHz	-30 dBm/1 MHz	All
$f_c - 2,5 \times 5 \text{ MHz} < f < f_c + 2,5 \times 5 \text{ MHz}$		Not defined	UTRA FDD, UTRA TDD, 3,84 Mcps option, cdma2000, spreading rate 3
$f_c - 2,5 \times BW_{\text{Channel}} \text{ MHz} < f < f_c + 2,5 \times BW_{\text{Channel}} \text{ MHz}$		Not defined	E-UTRA FDD, E-UTRA TDD, Mobile WiMAX, UMB
$f_c - 2,5 \times 10 \text{ MHz} < f < f_c + 2,5 \times 10 \text{ MHz}$		Not defined	UTRA TDD, 7,68 Mcps option
$f_c - 4 \text{ MHz} < f < f_c + 4 \text{ MHz}$		Not defined	UTRA TDD, 1,28 Mcps option cdma2000, spreading rate 1
$f_c - 500 \text{ kHz} < f < f_c + 500 \text{ kHz}$		Not defined	UWC 136, 200 kHz option
$f_c - 250 \text{ kHz} < f < f_c + 250 \text{ kHz}$		Not defined	UWC 136, 30 kHz option

NOTE: f_c is the UE transmit centre frequency.

Test Procedure

Test Data

Environmental Conditions

Temperature	18~22° C
Relative Humidity	45~66%
ATM Pressure	101.1~101.7kPa

Test Result: Pass.

Please refer to following data table.

Idle Mode

WCDMA2100

Frequency (MHz)	Polar (H/V)	Level (dBm)	Factor	Absolute Level (dBm)	Limit (dBm)	Margin (dB)
operation frequency:Low channel						
2947.785	H	-65.44	11.07	-54.37	-47.00	-7.37
8932.928	H	-75.15	15.98	-59.17	-47.00	-12.17
4757.111	V	-66.72	14.64	-52.08	-47.00	-5.08
8859.090	V	-79.89	18.85	-61.04	-47.00	-14.04
operation frequency:Middle channel						
3485.748	H	-66.54	6.93	-59.61	-47.00	-12.61
5400.859	H	-76.57	20.10	-56.47	-47.00	-9.47
3592.941	V	-65.62	10.62	-55.00	-47.00	-8.00
6266.935	V	-75.39	20.59	-54.80	-47.00	-7.80
operation frequency: High channel						
3883.723	H	-65.84	10.83	-55.01	-47.00	-8.01
6632.193	H	-76.68	13.46	-63.22	-47.00	-16.22
2116.634	V	-66.07	7.38	-58.69	-47.00	-11.69
5861.501	V	-78.27	14.86	-63.41	-47.00	-16.41

Polar (H/V)	Frequency (MHz)	Meter Reading (dBm)	Factor (dB)	Emission Level (dBm)	Limits (dBm)	Margin (dB)	Detector Type
V	33.637	-78.35	2.58	-75.77	-57	-18.77	peak
V	101.661	-78.40	3.55	-74.85	-57	-17.85	peak
V	209.283	-70.99	6.68	-64.31	-57	-7.31	peak
V	502.981	-72.45	6.81	-65.64	-57	-8.64	peak
V	593.871	-75.06	3.66	-71.40	-57	-14.40	peak
H	45.936	-78.23	8.08	-70.15	-57	-13.15	peak
H	76.971	-70.23	4.19	-66.04	-57	-9.04	peak
H	161.571	-73.01	2.97	-70.04	-57	-13.04	peak
H	433.702	-79.17	1.80	-77.37	-57	-20.37	peak
H	599.028	-77.76	1.79	-75.97	-57	-18.97	peak

Remark:

Emission Level= Meter Reading+ Factor, Margin= Limit- Emission Level.

WCDMA900

Frequency (MHz)	Polar (H/V)	Level (dBm)	Factor	Absolute Level (dBm)	Limit (dBm)	Margin (dB)
operation frequency:Low channel						
3053.083	H	-67.72	14.09	-53.63	-47.00	-6.63
7344.440	H	-77.19	16.18	-61.01	-47.00	-14.01
2701.025	V	-68.31	10.10	-58.21	-47.00	-11.21
7390.338	V	-79.15	14.87	-64.28	-47.00	-17.28
operation frequency:Middle channel						
4766.103	H	-65.99	5.84	-60.15	-47.00	-13.15
5993.678	H	-77.30	20.97	-56.33	-47.00	-9.33
3977.141	V	-67.43	11.38	-56.05	-47.00	-9.05
5356.696	V	-79.79	20.88	-58.91	-47.00	-11.91
operation frequency: High channel						
2744.459	H	-65.74	10.59	-55.15	-47.00	-8.15
6848.109	H	-75.24	18.67	-56.57	-47.00	-9.57
3383.558	V	-68.63	13.60	-55.03	-47.00	-8.03
8653.881	V	-77.49	14.80	-62.69	-47.00	-15.69

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	
V	54.129	-79.46	3.77	-75.69	-57	-18.69	peak
V	109.596	-70.86	8.06	-62.80	-57	-5.80	peak
V	185.749	-74.31	8.42	-65.89	-57	-8.89	peak
V	379.770	-78.18	6.80	-71.38	-57	-14.38	peak
V	587.551	-72.92	6.92	-66.00	-57	-9.00	peak
H	56.636	-70.31	5.34	-64.97	-57	-7.97	peak
H	110.287	-74.21	6.73	-67.48	-57	-10.48	peak
H	233.309	-70.81	7.74	-63.07	-57	-6.07	peak
H	507.349	-71.95	1.34	-70.61	-57	-13.61	peak
H	558.650	-76.58	6.85	-69.73	-57	-12.73	peak

Remark:

Emission Level= Meter Reading+ Factor, Margin= Limit- Emission Level.

Traffic Mode
WCDMA2100

Frequency (MHz)	Polar (H/V)	Level (dBm)	Factor	Absolute Level (dBm)	Limit (dBm)	Margin (dB)
operation frequency:Low channel						
2762.265	H	-51.60	12.20	-39.40	-30.00	-9.40
6157.679	H	-56.74	21.39	-35.35	-30.00	-5.35
3756.311	V	-49.98	12.85	-37.13	-30.00	-7.13
6290.257	V	-58.31	17.55	-40.76	-30.00	-10.76
operation frequency:Middle channel						
4801.610	H	-51.55	12.55	-39.00	-30.00	-9.00
9015.024	H	-57.00	20.63	-36.37	-30.00	-6.37
2365.936	V	-49.90	8.25	-41.65	-30.00	-11.65
5173.668	V	-59.49	21.64	-37.85	-30.00	-7.85
operation frequency: High channel						
3475.476	H	-48.44	14.98	-33.46	-30.00	-3.46
6902.277	H	-58.07	13.95	-44.12	-30.00	-14.12
4262.095	V	-50.98	10.96	-40.02	-30.00	-10.02
7510.824	V	-60.31	21.11	-39.20	-30.00	-9.20

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	
V	68.786	-54.82	1.68	-53.14	-36.00	-17.14	peak
V	111.662	-54.05	6.16	-47.89	-36.00	-11.89	peak
V	154.924	-54.06	2.83	-51.23	-36.00	-15.23	peak
V	435.397	-54.24	3.42	-50.82	-36.00	-14.82	peak
V	795.489	-53.79	4.12	-49.67	-36.00	-13.67	peak
H	70.369	-52.87	1.10	-51.77	-36.00	-15.77	peak
H	100.278	-51.39	8.78	-42.61	-36.00	-6.61	peak
H	201.853	-54.51	3.44	-51.07	-36.00	-15.07	peak
H	454.597	-54.13	8.81	-45.32	-36.00	-9.32	peak
H	783.848	-53.09	5.65	-47.44	-36.00	-11.44	peak

Remark:

Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit

WCDMA900

Frequency (MHz)	Polar (H/V)	Level (dBm)	Factor	Absolute Level (dBm)	Limit (dBm)	Margin (dB)
operation frequency:Low channel						
4248.224	H	-47.52	7.84	-39.68	-30.00	-9.68
5368.166	H	-58.80	13.00	-45.80	-30.00	-15.80
4944.250	V	-48.49	14.74	-33.75	-30.00	-3.75
5764.092	V	-57.27	14.70	-42.57	-30.00	-12.57
operation frequency:Middle channel						
2347.199	H	-50.78	10.57	-40.21	-30.00	-10.21
6398.333	H	-59.18	13.41	-45.77	-30.00	-15.77
2154.067	V	-50.36	9.41	-40.95	-30.00	-10.95
8326.791	V	-58.10	15.77	-42.33	-30.00	-12.33
operation frequency: High channel						
3475.885	H	-49.70	11.24	-38.46	-30.00	-8.46
6107.356	H	-59.10	19.16	-39.94	-30.00	-9.94
4174.099	V	-47.24	14.58	-32.66	-30.00	-2.66
5142.633	V	-58.72	13.17	-45.55	-30.00	-15.55

Polar (H/V)	Frequency (MHz)	Meter Reading (dBm)	Factor (dB)	Emission Level (dBm)	Limits (dBm)	Margin (dB)	Detector Type
V	57.013	-54.32	2.39	-51.93	-36.00	-15.93	peak
V	73.767	-50.25	7.17	-43.08	-36.00	-7.08	peak
V	134.879	-51.90	8.89	-43.01	-36.00	-7.01	peak
V	487.049	-53.13	4.67	-48.46	-36.00	-12.46	peak
V	617.271	-54.50	5.16	-49.34	-36.00	-13.34	peak
H	69.129	-50.99	3.35	-47.64	-36.00	-11.64	peak
H	105.958	-52.74	2.29	-50.45	-36.00	-14.45	peak
H	243.764	-54.33	6.12	-48.21	-36.00	-12.21	peak
H	327.456	-54.68	7.01	-47.67	-36.00	-11.67	peak
H	782.736	-52.49	5.78	-46.71	-36.00	-10.71	peak

Remark:

Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit

§4.3.2 –Control and monitoring functions (UE)

Definition & Limits

This requirement, together with other control and monitoring technical requirements identified in the table of cross references in the applicable part, verifies that the control and monitoring functions of the UE prevent it from transmitting in the absence of a valid network.

This test is applicable to radio communications equipment and ancillary equipment in the operating band defined in the applicable part of this multi-part harmonised standard.

This test shall be performed on the radio communications equipment and/or a representative configuration of the ancillary equipment.

Limits:

The maximum measured power during the duration of the test shall not exceed -30 dBm.

Test method

- a) At the start of the test, the UE shall be switched off. The UE antenna connector shall be connected to a power measuring equipment, with the following characteristics:
 - the RF bandwidth shall exceed the total operating transmit frequency range of the UE for operation with an applicable part;
 - the response time of the power measuring equipment shall be such that the measured power has reached within 1 dB of its steady state value within 100 µs of a CW signal being applied;
 - it shall record the maximum power measured.

NOTE: The equipment may include a video low pass filter to minimize its response to transients or Gaussian noise peaks.

- b) The UE shall be switched on for a period of approximately fifteen minutes, and then switched off.
- c) The EUT shall remain switched off for a period of at least thirty seconds, and shall then be switched on for a period of approximately one minute.
- d) The maximum power emitted from the UE throughout the duration of the test shall be recorded. The results obtained shall be compared to the limits in clause 4.2.4.2 in order to prove compliance.

Test Data

Test Condition	Monitoring band	Max Measured Power(dBm)	Limit(dBm)	Result
Normal	The whole band range	-41.25	-30	Pass

§4.3.3 —Out-of-synchronization handling of output power

Definition

The UE shall monitor the DPCCH quality in order to detect a loss of the signal on Layer 1. The threshold Q_{out} specifies at what DPCCH quality levels the UE shall shut its power off. The threshold is not defined explicitly, but is defined by the conditions under which the UE shall shut its transmitter off, as stated in this clause.

The DPCCH quality shall be monitored in the UE and compared to the threshold Q_{out} for the purpose of monitoring synchronization. The threshold Q_{out} should correspond to a level of DPCCH quality where no reliable detection of the TPC commands transmitted on the downlink DPCCH can be made. This can be at a TPC command error ratio level of e.g. 20 %.

Limits

When the UE estimates the DPCCH quality over the last 160 ms period to be worse than a threshold Q_{out} , the UE shall shut its transmitter off within 40 ms.

The quality level at the thresholds Q_{out} correspond to different signal levels depending on the downlink conditions DCH parameters. For the conditions in table 4.2.11.2-1, a signal with the quality at the level Q_{out} can be generated by a $DPCCH_{Ec}/I_{or}$ ratio of -25 dB. The DL reference measurement channel 12,2 kbit/s is specified in ETSI TS 134 121-1 [1], clause C.3.1 and with static propagation conditions. The downlink physical channels, other than those specified in table 4.2.11.2-1, are as specified in table E.3.3 of annex E in ETSI TS 134 121-1 [1].

Parameter	Value	Unit
\hat{I}_{or}/I_{oc}	-1	dB
I_{oc}	-60	dBm/3,84 MHz
$\frac{DPDCH_{Ec}}{I_{or}}$	See figure 4.2.11.2-1: Before point A: <ul style="list-style-type: none"> -16,6 for UEs not supporting enhanced receiver performance type 1 for DCH -19,6 for UEs supporting enhanced receiver performance type 1 for DCH After point A not defined	dB
$\frac{DPCCH_{Ec}}{I_{or}}$	See figure 4.2.11.2-1	dB
Information Data Rate	12,2	kbit/s

Figure 4.2.11.2-1 and table 4.2.11.2-2 show an example scenario where the $DPCCH_{Ec}/I_{or}$ ratio varies from a level where the DPCH is demodulated under normal conditions, down to a level below Q_{out} where the UE shall shut its power off.

Test Procedure

Initial conditions

Test environment: normal (see annex B).

The frequencies to be tested are mid range as defined in ETSI TS 134 108 [2], clause 5.1:

- 1) Connect the SS to the UE antenna connector.
- 2) A call is set up according to the Generic call setup procedure, with the following exception according to table 5.3.10.1.1-1 for information elements in System Information Block type 1 found in ETSI TS 134 108 [2].

Table 5.3.10.1.1-1: System Information Block type 1 message

Information Element	Value
UE Timers and constants in connected mode	
- T313	15 s
- N313	200

- 3) RF parameters are set up according to table 4.2.11.2-1 with DPCCH_Ec/Ior ratio level according To table 4.2.11.2-2, 'before A'.
- 4) Enter the UE into loopback test mode and start the loopback test using the procedure defined in ETSI TS 134 109 [3], clause 5.3.

Test Data

Environmental Conditions

Temperature	18~22° C
Relative Humidity	45~66%
ATM Pressure	101.1~101.7kPa

Test Result: Pass.

5. PHOTOGRAPHS OF THE TEST SETUP

Radiated Spurious Emission Test



END OF REPORT