



# RADIO TEST REPORT

For

Shenzhen Huafului Technology Co., Ltd.

Smartphone

Test Model: KINGKONG X

Prepared for : Shenzhen Huafului Technology Co., Ltd.  
Address : Unit 601-03, 6/F, Block A, Building 1, Ganfeng Technology Building, No. 993 Jiaxian Road, Xiangjiaotang Community, Bantian Street, Longgang District, Shenzhen, P.R. China

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.  
Address : Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel : (+86)755-82591330  
Fax : (+86)755-82591332  
Web : www.LCS-cert.com  
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : April 01, 2024  
Number of tested samples : 2  
Sample No. : A240319085-1, A240319085-2  
Serial number : Prototype  
Date of Test : April 01, 2024 ~ May 09, 2024  
Date of Report : May 10, 2024





**RADIO TEST REPORT  
ETSI EN 303 413 V1.2.1 (2021-04)**

Satellite Earth Stations and Systems (SES); Global Navigation Satellite System (GNSS) receivers; Radio equipment operating in the 1 164 MHz to 1 300 MHz and 1 559 MHz to 1 610 MHz frequency bands; Harmonised Standard for access to radio spectrum

**Report Reference No.** : **LCSA03214077EL**  
Date of Issue : May 10, 2024

**Testing Laboratory Name** : **Shenzhen LCS Compliance Testing Laboratory Ltd.**  
Address..... : Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China  
Testing Location/ Procedure.... : Full application of Harmonised standards   
Partial application of Harmonised standards   
Other standard testing method

**Applicant's Name**..... : **Shenzhen Huafurui Technology Co., Ltd.**  
Address..... : Unit 601-03, 6/F, Block A, Building 1, Ganfeng Technology Building, No. 993 Jiaxian Road, Xiangjiaotang Community, Bantian Street, Longgang District, Shenzhen, P.R. China

**Test Specification**  
Standard..... : ETSI EN 303 413 V1.2.1 (2021-04)  
Test Report Form No. .... : LCSEMC-1.0  
TRF Originator..... : Shenzhen LCS Compliance Testing Laboratory Ltd.  
Master TRF..... : Dated 2017-06

**Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.**  
This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Test Item Description**..... : **Smartphone**  
Trade Mark..... : CUBOT  
Test Model..... : KINGKONG X  
Ratings ..... : Please Refer to Page 6  
**Result** ..... : **Positive**

**Compiled by:**

**Supervised by:**

**Approved by:**

Kevin Huang/ Administrator

Cary Luo/ Technique principal

Gavin Liang/ Manager





# RADIO -- TEST REPORT

<b>Test Report No. :</b> LCSA03214077EL	<u>May 10, 2024</u> Date of issue
---	--------------------------------------

Test Model..... : KINGKONG X  EUT..... : Smartphone
<b>Applicant..... : Shenzhen Huafurui Technology Co., Ltd.</b> Address..... : Unit 601-03, 6/F, Block A, Building 1, Ganfeng Technology Building, No. 993 Jiaxian Road, Xiangjiaotang Community, Bantian Street, Longgang District, Shenzhen, P.R. China  Telephone..... : / Fax..... : /
<b>Manufacturer..... : Shenzhen Huafurui Technology Co., Ltd.</b> Address..... : Unit 601-03, 6/F, Block A, Building 1, Ganfeng Technology Building, No. 993 Jiaxian Road, Xiangjiaotang Community, Bantian Street, Longgang District, Shenzhen, P.R. China  Telephone..... : / Fax..... : /
<b>Factory..... : Shenzhen Huafurui Technology Co., Ltd.</b> Address..... : Unit 601-03, 6/F, Block A, Building 1, Ganfeng Technology Building, No. 993 Jiaxian Road, Xiangjiaotang Community, Bantian Street, Longgang District, Shenzhen, P.R. China  Telephone..... : / Fax..... : /

<b>Test Result</b>	<b>Positive</b>
--------------------	-----------------

The test report merely corresponds to the test sample.  
 It is not permitted to copy extracts of these test result without the written permission of the test laboratory.





### Revision History

Report Version	Issue Date	Revision Content	Revised By
000	May 10, 2024	Initial Issue	---



Shenzhen LCS Compliance Testing Laboratory Ltd.  
Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China  
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com  
Scan code to check authenticity



# TABLE OF CONTENTS

**1. GENERAL INFORMATION ..... 6**

1.1. PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) ..... 6

1.2. OBJECTIVE ..... 10

1.3. RELATED SUBMITTAL(S)/GRANT(S) ..... 10

1.4. TEST METHODOLOGY ..... 10

1.5. DESCRIPTION OF TEST FACILITY ..... 10

1.6. SUPPORT EQUIPMENT LIST ..... 10

1.7. EXTERNAL I/O ..... 10

1.8. MEASUREMENT UNCERTAINTY ..... 11

1.9. DESCRIPTION OF TEST MODES ..... 11

**2. SYSTEM TEST CONFIGURATION ..... 12**

2.1. JUSTIFICATION ..... 12

2.2. EUT EXERCISE SOFTWARE ..... 12

2.3. SPECIAL ACCESSORIES ..... 12

2.4. BLOCK DIAGRAM/SCHEMATICS ..... 12

2.5. EQUIPMENT MODIFICATIONS ..... 12

2.6. CONFIGURATION OF TEST SETUP ..... 12

**3. SUMMARY OF TEST RESULTS ..... 13**

**4. TEST RESULTS ..... 14**

4.1. RECEIVER BLOCKING ..... 14

4.2. RECEIVER SPURIOUS EMISSIONS ..... 17

**5. LIST OF MEASURING EQUIPMENT ..... 20**

**6. PHOTOGRAPHS OF TEST SETUP ..... 21**

**7. PHOTOGRAPHS OF THE EUT ..... 21**





## 1. GENERAL INFORMATION

### 1.1. Product Description for Equipment Under Test (EUT)

EUT	: Smartphone
Test Model	: KINGKONG X
Ratings	: Input: DC 5.0V, 3.0A Adapter1 Model: HJ-PD33W-EU For AC Adapter Input: 100-240V~, 50/60Hz, 0.8A Adapter Output: 5.0V=3.0A 15.0W OR 9.0V=3.0A 27.0W OR 12.0V=2.75A 33.0W MAX Adapter2 Model: ZYH-J330 For AC Adapter Input: 200-240V~, 50/60Hz, 1.2A Max Adapter Output: 5.0V=3.0A, 15.0W; 9.0V=3.0A, 27.0W; 12.0V=2.5A, 30.0W; 15.0V=2.0A, 30.0W; 20.0V=1.5A, 30.0W MAX DC 3.87V by Rechargeable Li-ion Battery, 10200mAh
Hardware Version	: G2365-MUB-V2-BOM3
Software Version	: CUBOT_KINGKONG X_E021C_V01
Bluetooth	:
Frequency Range	: 2402MHz~2480MHz
Channel Number	: 79 channels for Bluetooth V5.2 (BDR/EDR) 40 channels for Bluetooth V5.2 (BT LE/ BT 2LE)
Channel Spacing	: 1MHz for Bluetooth V5.2 (BDR/EDR) 2MHz for Bluetooth V5.2 (BT LE/ BT 2LE)
Modulation Type	: GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth V5.2 (BDR/EDR) GFSK for Bluetooth V5.2 (BT LE/ BT 2LE)
Bluetooth Version	: V5.2
Antenna Description	: FPC Antenna, 0.6dBi(Max.)
WIFI(2.4G Band)	:
Frequency Range	: 2412MHz~2472MHz
Channel Spacing	: 5MHz
Channel Number	: 13 Channel for 20MHz bandwidth(2412~2472MHz) 9 channels for 40MHz bandwidth(2422~2462MHz)
Modulation Type	: 802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: FPC Antenna, 0.6dBi(Max.)
WIFI(5.2G Band)	:
Frequency Range	: 5180MHz~5240MHz
Channel Number	: 4 channels for 20MHz bandwidth(5180~5240MHz) 2 channels for 40MHz bandwidth(5190~5230MHz)



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



1 channels for 80MHz bandwidth(5210MHz)

Modulation Type : 802.11a/n: OFDM (64QAM, 16QAM, QPSK, BPSK)  
802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)

Antenna Description : Ant6: FPC Antenna, 0.4dBi(Max.)  
Ant7: FPC Antenna, -1.6dBi(Max.)

WIFI(5.8G Band) :

Frequency Range : 5745MHz~5825MHz

Channel Number : 5 channels for 20MHz bandwidth(5745~5825MHz)  
2 channels for 40MHz bandwidth(5755~5795MHz)  
1 channels for 80MHz bandwidth(5775MHz)

Modulation Type : 802.11a/n: OFDM (64QAM, 16QAM, QPSK, BPSK)  
802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)

Antenna Description : Ant6: FPC Antenna, 0.4dBi(Max.)  
Ant7: FPC Antenna, -1.6dBi(Max.)

2G :

Support Band :  GSM 900 (EU-Band)  DCS 1800 (EU-Band)  
 GSM 850 (U.S.-Band)  PCS 1900 (U.S.-Band)

Release Version : R99

GPRS Class : Class 12

EGPRS Class : Class 12

Uplink : GSM 900: 880MHz~915MHz  
DCS 1800: 1710MHz~1785MHz

Downlink : GSM 900: 925MHz~960MHz  
DCS 1800: 1805MHz~1880MHz

Type Of Modulation : GMSK for GSM/GPRS; GMSK/8PSK for EGPRS

Antenna Description : FPC Antenna  
-1.3dBi (max.) For GSM 900  
-3.0dBi (max.) For DCS 1800

Power Class : GSM 900: Level 5, DCS 1800: Level 0  
EGPRS 900: Level 8, EGPRS 1800: Level 2

3G :

Support Band :  WCDMA Band I (EU-Band)  
 WCDMA Band VIII (EU-Band)

Release Version : R8

Uplink : WCDMA Band I: 1920MHz~1980MHz  
WCDMA Band VIII: 880MHz~915MHz

Downlink : WCDMA Band I: 2110MHz~2170MHz  
WCDMA Band VIII: 925MHz~960MHz

Type Of Modulation : QPSK/16QAM

Antenna Description : FPC Antenna  
-2.5dBi (max.) For WCDMA Band I





-1.3dBi (max.) For WCDMA Band VIII

Power Class : Level 3

LTE :

- Support Band :  E-UTRA Band 1(EU-Band)
- E-UTRA Band 3(EU-Band)
- E-UTRA Band 7(EU-Band)
- E-UTRA Band 8(EU-Band)
- E-UTRA Band 20(EU-Band)
- E-UTRA Band 28(EU-Band)
- E-UTRA Band 38(EU-Band)
- E-UTRA Band 40(EU-Band)

LTE Release Version : R12

- FDD Band : Uplink: E-UTRA Band 1: 1920MHz~1980MHz
- E-UTRA Band 3: 1710MHz~1785MHz
- E-UTRA Band 7: 2500MHz~2570MHz
- E-UTRA Band 8: 880MHz~915MHz
- E-UTRA Band 20: 832MHz~862MHz
- E-UTRA Band 28: 703MHz~748MHz
- Downlink: E-UTRA Band 1: 2110MHz~2170MHz
- E-UTRA Band 3: 1805MHz~1880MHz
- E-UTRA Band 7: 2620MHz~2690MHz
- E-UTRA Band 8: 925MHz~960MHz
- E-UTRA Band 20: 791MHz~821MHz
- E-UTRA Band 28: 758MHz~803MHz

- TDD Band : E-UTRA Band 38: 2570MHz ~ 2620MHz
- E-UTRA Band 40: 2300MHz ~ 2400MHz

Type Of Modulation : QPSK/16QAM

- Antenna Description : FPC Antenna
- 2.5dBi (max.) For E-UTRA Band 1
- 2.6dBi (max.) For E-UTRA Band 3
- 0.6dBi (max.) For E-UTRA Band 7
- 1.3dBi (max.) For E-UTRA Band 8
- 1.0dBi (max.) For E-UTRA Band 20
- 3.3dBi (max.) For E-UTRA Band 28
- 0.6dBi (max.) For E-UTRA Band 38
- 1.5dBi (max.) For E-UTRA Band 40

Power Class : Class 3

NR :

- Operation Band : n1: UL: 1920MHz~1980MHz, DL: 2110MHz~2170MHz
- n3: UL: 1710MHz~1785MHz, DL:1805MHz~1880MHz
- n7: UL: 2500MHz~2570MHz, DL: 2620MHz~2690MHz





Support Type :  SA

Sub carrier Spacing : 15KHz

Modulation Type : DFT-BPSK, DFT-QPSK, DFT-16QAM, DFT-64QAM, DFT-256QAM, CP-QPSK, CP-16QAM, CP-64QAM, CP-256QAM

NR Release Version : 15

Power Class : NR Band 1/3/7: PC3

Antenna Description : FPC Antenna  
n1: -2.5dBi Max  
n3: -2.6dBi Max  
n7: -0.6dBi Max

GPS Receiver :

Receive Frequency : 1575.42MHz

Channel Number : 1

Antenna Description : FPC Antenna, 3.9dBi(Max.)

GLONASS Receiver :

Receive Frequency : 1602.5625MHz

Channel Number : 1

Antenna Description : FPC Antenna, 3.9dBi(Max.)

Galileo Receiver :

Receive Frequency : 1589.74MHz

Channel Number : 1

Antenna Description : FPC Antenna, 3.9dBi(Max.)

BDS Receiver :

Receive Frequency : 1561.098MHz

Channel Number : 1

Antenna Description : FPC Antenna, 3.9dBi(Max.)

NFC :

Frequency Range : 13.56MHz

Modulation Type : ASK

Antenna Description : FPC Antenna, 0dBi(Max.)





## 1.2. Objective

This Type approval report is prepared on behalf of **Shenzhen Huafurui Technology Co., Ltd.** in accordance with ETSI EN 303 413 V1.2.1 (2021-04), Satellite Earth Stations and Systems (SES); Global Navigation Satellite System (GNSS) receivers; Radio equipment operating in the 164 MHz to 1 300 MHz and 1 559 MHz to 1 610 MHz frequency bands; Harmonised Standard for access to radio spectrum.

The objective is to determine compliance with ETSI EN 303 413 V1.2.1 (2021-04).

## 1.3. Related Submittal(s)/Grant(s)

No Related Submittals.

## 1.4. Test Methodology

All measurements contained in this report were conducted with ETSI EN 303 413 V1.2.1 (2021-04).

## 1.5. Description of Test Facility

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier is CN0071.

CNAS Registration Number is L4595.

## 1.6. Support Equipment List

Manufacturer	Description	Model	Serial Number	Certificate
Shenzhen Huajin Electronics Co., Ltd	Fast Charger	HJ-PD33W-EU	---	CE
Zhengyuhong Electronics (dongguan) Co., Ltd	AC Power Adapter	ZYH-J330	---	CE

## 1.7. External I/O

I/O Port Description	Quantity	Cable
Type-C USB Port	1	USB Cable: 1.0m, unshielded
Headphone Port	1	Headphone Cable: 1.2m, unshielded



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



### 1.8. Measurement Uncertainty

Item	MU	Remark
Uncertainty for Power point Conducted Emissions Test	2.42dB	
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	3.54dB	Polarize: V
	4.1dB	Polarize: H
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 25GHz)	2.08dB	Polarize: H
	2.56dB	Polarize: V
Uncertainty for radio frequency	0.01ppm	
Uncertainty for conducted RF Power	0.65dB	
Uncertainty for temperature	0.2°C	
Uncertainty for humidity	1%	
Uncertainty for DC and low frequency voltages	0.06%	

### .9. Description Of Test Modes

The EUT has been tested under operating condition.

Mode 1: GPS Receiver

Mode 2: GLONASS Receiver

Mode 3: Galileo Receiver

Mode 4: BDS Receiver

This test was performed with EUT in X, Y, Z position and the worse case was found when EUT in Y position.





## 2. SYSTEM TEST CONFIGURATION

### 2.1. Justification

The system was configured for testing in engineering mode.

### 2.2. EUT Exercise Software

N/A.

### 2.3. Special Accessories

N/A.

### 2.4. Block Diagram/Schematics

Please refer to the related document.

### 2.5. Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

### 2.6. Configuration of Test Setup

Please refer to the test setup photo.





### 3. SUMMARY OF TEST RESULTS

RULES	DESCRIPTION OF TEST	RESULT
ETSI EN 303 413 V1.2.1 (2021-04)		
§ 4.2.1	Receiver blocking	Compliant
§ 4.2.2	Receiver spurious emissions	Compliant

Note: "N/A" means this test item is not applicable.





## 4. TEST RESULTS

### 4.1. Receiver blocking

#### 4.1.1 Definition and Limit

Receiver blocking is a measure of the capability of the GUE to receive a wanted signal without exceeding a given degradation due to the presence of an unwanted input signal operating in accordance with the allocation table of the ITU Radio Regulations [i.13] in frequency bands adjacent or near-adjacent to the relevant RNSS band.

The  $C/N_0$  metric reported by the GUE for all GNSS constellations and GNSS signals given in table 4-1 and supported by the GUE shall not degrade by more than the value given in equation (4-1) when a blocking signal is applied. The blocking signal is defined in table 4-4, with the frequencies and power levels defined in table 4-2 and/or in table 4-3 depending on the RNSS bands supported by the GUE

Equation 4-1: Maximum degradation in  $C/N_0$

$$\Delta C/N_0 \leq 1 \text{ dB} \quad (4-1)$$

**Table 4-2: Frequency bands, blocking signal test point centre frequencies and power levels for the 1 559 MHz to 1 610 MHz RNSS band**

Frequency band (MHz)	Test point centre frequency (MHz)	Blocking signal power level (dBm)	Comments
1518 to 1525	1524	-65	MSS (space-to-Earth) band
1525 to 1549	1548	-95	MSS (space-to-Earth) band
1549 to 1559	1554	-105	MSS (space-to-Earth) band
1559 to 1610	GUE RNSS band under test		
1610 to 1626	1615	-105	MSS (space-to-Earth) band
1626 to 1640	1627	-85	MSS (space-to-Earth) band

**Table 4-3: Frequency bands, blocking signal test point centre frequencies and power levels for the 1 164 MHz to 1 300 MHz RNSS band**

Frequency band (MHz)	Test point centre frequency (MHz)	Blocking signal power level (dBm)	Comments
960 to 1164	1154	-75	AM(R)S, ARNS band
1164 to 1215	GUE RNSS band under test		
1215 to 1260	GUE RNSS band under test		
1260 to 1300	GUE RNSS band under test		
1300 to 1350	1310	-85	Radiolocation, ARNS, RNSS (Earth-to-space) band

**Table 4-4: Blocking signal**

Parameter	Value	Comments
Frequency	See table 4-2 and table 4-3	
Power level	See table 4-2 and table 4-3	
Bandwidth	1 MHz	See clause B.1 for details
Format	AWGN	



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



### 4.1.2 Test Procedure

- 1) Configure the GNSS signal generator to simulate the GNSS constellations and GNSS signals from table 4-1 declared as supported by the GUE, with power levels and other details as specified in clause B.2.
- 2) With the blocking signal switched off, the EUT shall be given sufficient time to acquire all simulated satellites from the declared GNSS constellations.
- 3) Record the C/N<sub>0</sub> value(s) reported by the EUT under the condition in step 2). Sufficient filtering shall be used to obtain stable value(s). C/N<sub>0</sub> may be averaged over time and across all the simulated satellites for a particular GNSS constellation and GNSS signal. However, C/N<sub>0</sub> shall not be averaged across different satellite signals in the same GNSS constellation or across different GNSS constellations. For a multi-GNSS constellation and/or multi-GNSS signal EUT, there shall be a separate C/N<sub>0</sub> value recorded for each GNSS constellation and each GNSS signal supported.
- 4) The blocking signal generator shall be configured to generate the signal defined in table 4-4, at the first test point centre frequency and signal power level as specified in table 4-2.
- 5) The blocking signal shall be switched on, and the EUT's C/N<sub>0</sub> value(s) recorded as in step 3). The difference(s) between this value(s) and the value(s) recorded in step 3) is the C/N<sub>0</sub> degradation caused by the blocking signal for this test point.
- 6) Test point Pass/Fail Criteria: If the C/N<sub>0</sub> degradation from step 5) does not exceed the value in equation (4-1), then this test point is set to "pass". If the C/N<sub>0</sub> degradation exceeds the value in equation (4-1), then this test point is set to "fail". For a multi-GNSS constellation and/or multi-GNSS signal EUT, there shall be a separate pass/fail determination for each GNSS constellation and for each GNSS signal supported. If the C/N<sub>0</sub> degradation exceeds the value in equation (4-1) for any supported GNSS constellation or supported GNSS signal, then this test point is set to "fail".
- 7) Step 1) through step 6) shall be repeated for all test point centre frequencies (and associated signal power level) specified in table 4-2.

### 4.1.3 Test Result

#### Environmental Conditions

Temperature/ Humidity:	23.6°C/ 52.8%	ATM Pressure:	100.9 kPa
Operator:	Paddi Chen	Conclusion:	Pass

#### GPS Receiver

Frequency Band(MHz)	Test Point Center Frequency(MHz)	Blocking signal power level (dBm)	Test Result(dB)	Limit(dB) (ΔC/N <sub>0</sub> )
1518 to 1525	1524	-65	0.30	≤ 1
1525 to 1549	1548	-95	0.44	≤ 1
1 549 to 1 559	1554	-105	0.69	≤ 1
1 610 to 1 626	1615	-105	0.54	≤ 1
1 626 to 1 640	1627	-85	0.26	≤ 1





## GLONASS Receiver

Frequency Band(MHz)	Test Point Center Frequency(MHz)	Blocking signal power level (dBm)	Test Result(dB)	Limit(dB) ( $\Delta C/N_0$ )
1518 to 1525	1524	-65	0.38	$\leq 1$
1525 to 1549	1548	-95	0.30	$\leq 1$
1 549 to 1 559	1554	-105	0.69	$\leq 1$
1 610 to 1 626	1615	-105	0.73	$\leq 1$
1 626 to 1 640	1627	-85	0.50	$\leq 1$

## Galileo Receiver

Frequency Band(MHz)	Test Point Center Frequency(MHz)	Blocking signal power level (dBm)	Test Result(dB)	Limit(dB) ( $\Delta C/N_0$ )
1518 to 1525	1524	-65	0.27	$\leq 1$
1525 to 1549	1548	-95	0.48	$\leq 1$
1 549 to 1 559	1554	-105	0.63	$\leq 1$
1 610 to 1 626	1615	-105	0.59	$\leq 1$
1 626 to 1 640	1627	-85	0.33	$\leq 1$

## BDS Receiver

Frequency Band(MHz)	Test Point Center Frequency(MHz)	Blocking signal power level (dBm)	Test Result(dB)	Limit(dB) ( $\Delta C/N_0$ )
1518 to 1525	1524	-65	0.39	$\leq 1$
1525 to 1549	1548	-95	0.30	$\leq 1$
1 549 to 1 559	1554	-105	0.55	$\leq 1$
1 610 to 1 626	1615	-105	0.49	$\leq 1$
1 626 to 1 640	1627	-85	0.60	$\leq 1$



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



## 4.2. Receiver Spurious Emissions

### 4.2.1 Definition and Limit

Receiver spurious emissions are emissions at any frequency when the GUE is active.

Frequency range	Maximum power	Bandwidth
30 MHz to 1 GHz	-57 dBm	100 kHz
1 GHz to 8,3 GHz	-47 dBm	1 MHz

### 4.2.2 Test Procedure

Please refer to ETSI EN 303 413 V1.2.1 (2021-04) clause 5.5.3 for measurement method.

### 4.2.3 Test Result

#### Environmental Conditions

Temperature/ Humidity:	23.6°C / 52.8%	ATM Pressure:	100.9 kPa
Test Mode:	Mode 1-1575.42MHz	Operator:	Paddi Chen

#### Test Result For Receiving Mode(Detecting Frequency Range: 30MHz~1GHz)

Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Margin (dB)	Polarity (H/V)
67.03	-68.89	-57.00	-11.89	V
911.44	-70.27	-57.00	-13.27	V
165.08	-73.19	-57.00	-16.19	H
928.00	-73.30	-57.00	-16.30	H

#### Test Result For Receiving Mode(Detecting Frequency Range: Above 1GHz)

Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Margin (dB)	Polarity (H/V)
1713.77	-68.35	-47.00	-21.35	V
3562.69	-56.84	-47.00	-9.84	H
2020.14	-71.68	-47.00	-24.68	H
3565.81	-59.66	-47.00	-12.66	V



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity

**Environmental Conditions**

Temperature/ Humidity:	23.6°C/ 52.8%	ATM Pressure:	100.9 kPa
Test Mode:	Mode 2-1602.5625MHz	Operator:	Paddi Chen

**Test Result For Receiving Mode(Detecting Frequency Range: 30MHz~1GHz)**

Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Margin (dB)	Polarity (H/V)
66.34	-67.32	-57.00	-10.32	V
912.13	-68.93	-57.00	-11.93	V
165.03	-72.42	-57.00	-15.42	H
926.62	-74.03	-57.00	-17.03	H

**Test Result For Receiving Mode(Detecting Frequency Range: Above 1GHz)**

Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Margin (dB)	Polarity (H/V)
1715.79	-69.01	-47.00	-22.01	V
3565.74	-56.07	-47.00	-9.07	H
2017.38	-73.89	-47.00	-26.89	H
3567.71	-61.49	-47.00	-14.49	V

**Environmental Conditions**

Temperature/ Humidity:	23.6°C/ 52.8%	ATM Pressure:	100.9 kPa
Test Mode:	Mode 3-1589.74MHz	Operator:	Paddi Chen

**Test Result For Receiving Mode(Detecting Frequency Range: 30MHz~1GHz)**

Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Margin (dB)	Polarity (H/V)
65.27	-69.26	-57.00	-12.26	V
911.04	-69.19	-57.00	-12.19	V
163.63	-75.13	-57.00	-18.13	H
925.63	-74.16	-57.00	-17.16	H

**Test Result For Receiving Mode(Detecting Frequency Range: Above 1GHz)**

Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Margin (dB)	Polarity (H/V)
1713.98	-71.63	-47.00	-24.63	V
3563.12	-54.43	-47.00	-7.43	H
2019.21	-73.15	-47.00	-26.15	H
3567.68	-62.11	-47.00	-15.11	V



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity

**Environmental Conditions**

Temperature/ Humidity:	23.6°C / 52.8%	ATM Pressure:	100.9 kPa
Test Mode:	Mode 4-1561.098MHz	Operator:	Paddi Chen

**Test Result For Receiving Mode(Detecting Frequency Range: 30MHz~1GHz)**

Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Margin (dB)	Polarity (H/V)
66.18	-66.17	-57.00	-9.17	V
911.89	-68.67	-57.00	-11.67	V
164.63	-72.85	-57.00	-15.85	H
925.87	-75.54	-57.00	-18.54	H

**Test Result For Receiving Mode(Detecting Frequency Range: Above 1GHz)**

Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Margin (dB)	Polarity (H/V)
1712.28	-68.87	-47.00	-21.87	V
3564.15	-56.08	-47.00	-9.08	H
2018.66	-73.43	-47.00	-26.43	H
3568.27	-61.08	-47.00	-14.08	V

**Notes:**

1. Measuring frequencies from 25MHz~10th harmonic or 26.5GHz (which is less)
2. The emissions that at least 20dB below the official limit are not reported.



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity





## 5. LIST OF MEASURING EQUIPMENT

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	MXA Signal Analyzer	Agilent	N9020A	MY51250905	2023-10-18	2024-10-17
2	WIDEBAND RADIO COMMUNICATION TESTER	R&S	CMW 500	103818	2023-06-09	2024-06-08
3	MXG Vector Signal Generator	Agilent	N5182A	MY47071151	2023-06-09	2024-06-08
4	Combiner	N/A	N/A	SHWLCB2-52500S	2023-10-18	2024-10-17
5	EMI Test Software	Farad	EZ	/	N/A	N/A
6	3m Full Anechoic Chamber	MRDIANZI	FAC-3M	MR009	2022-08-17	2025-08-16
7	Positioning Controller	Max-Full	MF7802BS	MF780208586	N/A	N/A
8	By-log Antenna	SCHWARZBECK	VULB9163	9163-470	2021-09-12	2024-09-11
9	Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1925	2021-09-05	2024-09-04
10	EMI Test Receiver	R&S	ESR 7	101181	2023-08-15	2024-08-14
11	RS SPECTRUM ANALYZER	R&S	FSP40	100503	2023-07-17	2024-07-16
12	Low-frequency amplifier	SchwarzZBECK	BBV9745	00253	2023-10-18	2024-10-17
13	High-frequency amplifier	JS Denki Pte	PA0118-43	JSPA21009	2023-10-18	2024-10-17





## 6. PHOTOGRAPHS OF TEST SETUP

Please refer to separated files Appendix D for Photographs of Test Setup\_RF.

## 7. PHOTOGRAPHS OF THE EUT

Please refer to separated files Appendix C for Photographs of The EUT.

-----THE END OF REPORT-----

