

Certification
Issued Under the Authority of the
Federal Communications Commission
By:

MiCOM Labs
575 Boulder Court
Pleasanton, CA 94566

Date of Grant: 08/06/2026
Application Dated: 08/06/2026

Shenzhen Huafurui Technology Co., Ltd.
Unit 601-03, 6/F, Block A, Building 1,
Ganfeng Technology Building, No. 993 Jiaxian Road,
Shenzhen,
China

Attention: Paul Liu ,

NOT TRANSFERABLE

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is
VALID ONLY for the equipment identified hereon for use under the Commission's
Rules and Regulations listed below.

FCC IDENTIFIER: 2AHZ5DURA

Name of Grantee: Shenzhen Huafurui Technology Co.,
Ltd.

Equipment Class: PCS Licensed Transmitter held to ear
Notes: Smartphone

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
	22H	824.2 - 848.8	1.45881	0.015292 PM	250KGXW
	24E	1850.2 - 1907.6	0.90573	0.015292 PM	249KG7W
	24E	1852.4 - 1907.6	0.2023	0.011064 PM	4M15F9W
	27	1712.4 - 1752.6	0.17865	0.012157 PM	4M16F9W
	22H	826.4 - 846.6	0.22439	0.028396 PM	4M18F9W
	24E	1860.0 - 1900.0	0.12416	0.007796 PM	17M9G7D
	24E	1860.0 - 1900.0	0.10641	0.005212 PM	18M0W7D
	27	1720.0 - 1745.0	0.1219	0.005685 PM	17M9G7D
	27	1720.0 - 1745.0	0.10691	0.005588 PM	18M0W7D
	22H	829.0 - 844.0	0.13002	0.007858 PM	9M01G7D
	22H	829.0 - 844.0	0.11535	0.008014 PM	8M98W7D
	27	2510.0 - 2560.0	0.133352	0.003906 PM	17M2G7D
	27	2510.0 - 2560.0	0.11482	0.002795 PM	17M3W7D
	27	704.0 - 711.0	0.13002	0.014692 PM	9M00G7D
	27	704.0 - 711.0	0.12647	0.012723 PM	8M98W7D
	27	709.0 - 711.0	0.13836	0.014098 PM	9M00G7D
	27	709.0 - 711.0	0.11615	0.014756 PM	8M98W7D
	27	2580.0 - 2610.0	0.12618	0.00436 PM	18M0G7D
	27	2580.0 - 2610.0	0.12134	0.004057 PM	18M0W7D

Power output listed is ERP for frequencies below 1GHz and EIRP for frequencies above 1GHz. SAR compliance for body-worn operating configurations is limited to the specific configurations tested for this filing. Body-worn operations are restricted to belt-clips, holsters or similar accessories that have no metallic component in the assembly and must provide at least 10 mm separation between the device and the body of the user. End-users must be informed of the body-worn operating requirements for satisfying RF exposure compliance. The highest reported SAR for Head, body-worn, hotspot and Simultaneous SAR accessory are 0.531W/kg, 0.751 W/kg, 0.751 W/kg and 1.133 W/Kg respectively.