



RADIO TEST REPORT

For

Shenzhen Huafurui Technology Co., Ltd.

Smartphone

Test Model: KINGKONG ES PRO

Prepared for : Shenzhen Huafurui Technology Co., Ltd.
Address : Unit 601-03, 6/F, Block A, Building 1, Ganfeng Technology Building, No. 993 Jiaxian Road, Xiangjiaotang Community, Bantian Street, Longgang District, Shenzhen, P.R. China

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : Room 101/201, Building A, and Room 101/301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Tel : (+86)755-82591330
Fax : (+86)755-82591332
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : May 21, 2024
Number of tested samples : 2
Sample No. : A240520136-1, A240520136-2
Serial number : Prototype
Date of Test : May 21, 2024 ~ June 07, 2024
July 27, 2026 ~ July 31, 2026
Date of Report : August 03, 2026



RADIO TEST REPORT	
ETSI EN 301 908-1 V15.2.1 (2023-01) & ETSI EN 301 908-13 V13.3.1 (2024-10)	
Report Reference No.	LCSA07276088EJ
Date of Issue	August 03, 2026
Testing Laboratory Name	Shenzhen LCS Compliance Testing Laboratory Ltd.
Address	Room 101/201, Building A, and Room 101/301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong, China
Testing Location/ Procedure	Full application of Harmonised standards ☒ Partial application of Harmonised standards ☐ Other standard testing method ☐
Applicant's Name	Shenzhen Huafurui Technology Co., Ltd.
Address	Unit 601-03, 6/F, Block A, Building 1, Ganfeng Technology Building, No. 993 Jiaxian Road, Xiangjiaotang Community, Bantian Street, Longgang District, Shenzhen, P.R. China
Test Specification	
Standard	ETSI EN 301 908-1 V15.2.1 (2023-01) ETSI EN 301 908-13 V13.3.1 (2024-10)
Test Report Form No.	LCSEMC-1.0
TRF Originator	Shenzhen LCS Compliance Testing Laboratory Ltd.
Master TRF	Dated 2017-06
Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved. This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.	
Test Item Description : Smartphone	
Trade Mark	CUBOT
Test Model	KINGKONG ES PRO
Ratings	Please Refer to Page 6
Result	Positive

Compiled by:

Ling Zhu/ Administrator

Supervised by:

Jack Liu/ Technique principal

Approved by:

Gavin Liang/ Manager



RADIO -- TEST REPORT

Test Report No. : LCSA07276088EJ	August 03, 2026 Date of issue
----------------------------------	----------------------------------

Test Model.....	: KINGKONG ES PRO
EUT.....	: Smartphone
Applicant.....	: Shenzhen Huafurui Technology Co., Ltd.
Address.....	: Unit 601-03, 6/F, Block A, Building 1, Ganfeng Technology Building, No. 993 Jiaxian Road, Xiangjiaotang Community, Bantian Street, Longgang District, Shenzhen, P.R. China
Telephone.....	: /
Fax.....	: /
Manufacturer.....	: Shenzhen Huafurui Technology Co., Ltd.
Address.....	: Unit 601-03, 6/F, Block A, Building 1, Ganfeng Technology Building, No. 993 Jiaxian Road, Xiangjiaotang Community, Bantian Street, Longgang District, Shenzhen, P.R. China
Telephone.....	: /
Fax.....	: /
Factory.....	: Shenzhen Huafurui Technology Co., Ltd.
Address.....	: Unit 601-03, 6/F, Block A, Building 1, Ganfeng Technology Building, No. 993 Jiaxian Road, Xiangjiaotang Community, Bantian Street, Longgang District, Shenzhen, P.R. China
Telephone.....	: /
Fax.....	: /

Test Result	Positive
-------------	----------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.



Revision History

Report Version	Issue Date	Revision Content	Revised By
000	August 03, 2026	Initial Issue	---

Note : This test report is Updated test standard ETSI EN 301 908-13 based on original test report“LCSA05204088EJ”.and Band 41 testing data has been added.

Test Model: KINGKONG ES

Software Version: CUBOT_KINGKONG ES PRO_E081_V01

Change to

Test Model: KINGKONG ES PRO

Software Version: CUBOT_KINGKONG ES PRO_E083_V01



TABLE OF CONTENTS

1. GENERAL INFORMATION	6
1.1. PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	6
1.2. SUPPORT EQUIPMENT LIST	9
1.3. EXTERNAL I/O	9
1.4. OBJECTIVE	9
1.5. TEST CONDITIONS	9
1.6. DESCRIPTION OF TEST MODE	10
1.7. MEASUREMENT UNCERTAINTY (95% CONFIDENCE LEVELS, K=2)	10
1.8. DESCRIPTION OF TEST FACILITY	10
2. SYSTEM TEST CONFIGURATION	11
2.1. JUSTIFICATION	11
2.2. EUT EXERCISE SOFTWARE	11
2.3. SPECIAL ACCESSORIES	11
2.4. BLOCK DIAGRAM/SCHEMATICS	11
2.5. EQUIPMENT MODIFICATIONS	11
2.6. TEST SETUP	11
3. SUMMARY OF TEST RESULTS	12
4. LIST OF MEASURING EQUIPMENT	15
5. PHOTOGRAPHS OF TEST SETUP	17
6. PHOTOGRAPHS OF THE EUT	17



1. GENERAL INFORMATION

1.1. Product Description for Equipment Under Test (EUT)

EUT	: Smartphone
Test Model	: KINGKONG ES PRO
Ratings	: Input: DC 5V, 2000mA Adapter1 Model: HJ-0502000W2-EU For AC Adapter Input: 100-240V~, 50/60Hz, 0.3A Adapter Output: 5.0V=2.0A Output Power: 10W DC 3.87V by Rechargeable Li-ion Battery, 5100mAh
Hardware Version	: Q16-MB-V2.0
Software Version	: CUBOT_KINGKONG ES PRO_E083_V01
Bluetooth	:
Frequency Range	: 2402MHz~2480MHz
Channel Number	: 79 channels for Bluetooth V5.0 (BDR/EDR) 40 channels for Bluetooth V5.0 (BT LE/ BT 2LE)
Channel Spacing	: 1MHz for Bluetooth V5.0 (BDR/EDR) 2MHz for Bluetooth V5.0 (BT LE/ BT 2LE)
Modulation Type	: GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth V5.0 (BDR/EDR) GFSK for Bluetooth V5.0 (BT LE/ BT 2LE)
Bluetooth Version	: V5.0
Antenna Description	: PIFA Antenna, 2.64dBi(Max.)
WIFI(2.4G Band)	:
Frequency Range	: 2412MHz~2472MHz
Channel Spacing	: 5MHz
Channel Number	: 13 Channel for 20MHz bandwidth(2412~2472MHz) 9 channels for 40MHz bandwidth(2422~2462MHz)
Modulation Type	: 802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: PIFA Antenna, 2.64dBi(Max.)
WIFI(5.2G Band)	:
Frequency Range	: 5180MHz~5240MHz
Channel Number	: 4 channels for 20MHz bandwidth(5180~5240MHz) 2 channels for 40MHz bandwidth(5190~5230MHz) 1 channels for 80MHz bandwidth(5210MHz)
Modulation Type	: 802.11a/n: OFDM (64QAM, 16QAM, QPSK, BPSK) 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: PIFA Antenna, 5.40dBi(Max.)
WIFI(5.8G Band)	:



Frequency Range : 5745MHz~5825MHz
Channel Number : 5 channels for 20MHz bandwidth(5745~5825MHz)
2 channels for 40MHz bandwidth(5755~5795MHz)
1 channels for 80MHz bandwidth(5775MHz)
Modulation Type : 802.11a/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description : PIFA Antenna, 5.40dBi(Max.)

2G

Support Band : ☒ GSM 900 (EU-Band) ☒ DCS 1800 (EU-Band)
☒ GSM 850 (U.S.-Band) ☒ PCS 1900 (U.S.-Band)

Release Version : R99

GPRS Class : Class 12

EGPRS Class : Class 12

Uplink : GSM 900: 880MHz~915MHz
DCS 1800: 1710MHz~1785MHz

Downlink : GSM 900: 925MHz~960MHz
DCS 1800: 1805MHz~1880MHz

Type Of Modulation : GMSK for GSM/GPRS; GMSK/8PSK for EGPRS

Antenna Description : PIFA Antenna

0.03dBi (max.) For GSM 900

-2.58dBi (max.) For DCS 1800

Power Class : GSM 900: Level 5, DCS 1800: Level 0
EGPRS 900: Level 8, EGPRS 1800: Level 2

3G

Support Band : ☒ WCDMA Band I (EU-Band)
☒ WCDMA Band VIII (EU-Band)

Release Version : R9

Uplink : WCDMA Band I: 1920MHz~1980MHz
WCDMA Band VIII: 880MHz~915MHz

Downlink : WCDMA Band I: 2110MHz~2170MHz
WCDMA Band VIII: 925MHz~960MHz

Type Of Modulation : QPSK/16QAM

Antenna Description : PIFA Antenna

-2.31dBi (max.) For WCDMA Band I

0.03dBi (max.) For WCDMA Band VIII

Power Class : Level 3

LTE

Support Band : ☒ E-UTRA Band 1(EU-Band)
☒ E-UTRA Band 3(EU-Band)
☒ E-UTRA Band 7(EU-Band)
☒ E-UTRA Band 8(EU-Band)
☒ E-UTRA Band 20(EU-Band)



☒ E-UTRA Band 28(EU-Band)
☒ E-UTRA Band 41(EU-Band)
LTE Release Version : R9
FDD Band : Uplink: E-UTRA Band 1: 1920MHz~1980MHz
E-UTRA Band 3: 1710MHz~1785MHz
E-UTRA Band 7: 2500MHz~2570MHz
E-UTRA Band 8: 880MHz~915MHz
E-UTRA Band 20: 832MHz~862MHz
E-UTRA Band 28: 703MHz~748MHz
Downlink: E-UTRA Band 1: 2110MHz~2170MHz
E-UTRA Band 3: 1805MHz~1880MHz
E-UTRA Band 7: 2620MHz~2690MHz
E-UTRA Band 8: 925MHz~960MHz
E-UTRA Band 20: 791MHz~821MHz
E-UTRA Band 28: 758MHz~803MHz
TDD Band : E-UTRA Band 41: 2500MHz~2690MHz
Type Of Modulation : QPSK/16QAM
Antenna Description : PIFA Antenna
-2.31dBi (max.) For E-UTRA Band 1
2.93dBi (max.) For E-UTRA Band 3
-1.67dBi (max.) For E-UTRA Band 7
0.03dBi (max.) For E-UTRA Band 8
-6.25dBi (max.) For E-UTRA Band 20
0.03dBi (max.) For E-UTRA Band 28
-1.67dBi (max.) For E-UTRA Band 41
Power Class : Class 3
GPS Receiver :
Receive Frequency : 1575.42MHz
Channel Number : 1
Antenna Description : PIFA Antenna, 0dBi(Max.)
GLONASS Receiver :
Receive Frequency : 1602.5625MHz
Channel Number : 1
Antenna Description : PIFA Antenna, 0dBi(Max.)
Galileo Receiver :
Receive Frequency : 1589.74MHz
Channel Number : 1
Antenna Description : PIFA Antenna, 0dBi(Max.)



1.2. Support Equipment List

Manufacturer	Description	Model	Serial Number	Certificate
ShenZhen HuaJin Electronics CO.,LTD	AC Power Adapter	HJ-0502000 W2-EU	---	CE

1.3. External I/O

I/O Port Description	Quantity	Cable
Type-C USB Port	1	USB Cable: 0.8m, unshielded

1.4. Objective

Standard Referenced	Standard Title	Standard Version
ETSI EN 301 908-1	IMT cellular networks; Harmonised Standard for access to radio spectrum; Part 1: Introduction and common requirements; Release 15	V15.2.1 (2023-01)
ETSI EN 301 908-13	IMT cellular networks; Harmonised Standard for access to radio spectrum; Part 13: Evolved Universal Terrestrial Radio Access (E-UTRA) User Equipment (UE)	V13.3.1 (2024-10)
ETSI TS 136 521-1	LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) conformance specification; Radio transmission and reception; Part 1: Conformance testing (3GPP TS 36.521-1 version 17.7.0 Release 17)	V17.7.0 (2023-07)

The objective is to determine compliance with ETSI EN 301 908-1 V15.2.1 (2023-01) & ETSI EN 301 908-13 V13.3.1 (2024-10).

1.5. Test Conditions

Conditions	Temperature	Voltage
Normal	21-25℃	DC 3.87V
Low extreme Temperature/Low extreme Voltage (TL/VL);	-20℃	DC 3.48V
Low extreme Temperature/High extreme Voltage (TL/VH);	-20℃	DC 4.45V
High extreme Temperature/Low extreme Voltage (TH/VL);	45℃	DC 3.48V
High extreme Temperature/High extreme Voltage (TH/VH).	45℃	DC 4.45V

Note1: For all conditions, the humidity range is: 40-75%, the pressure range is 86-106kPa. The High Voltage DC 4.45V and Low Voltage DC 3.48V was declared by manufacturer



1.6. Description Of Test Mode

The following operating modes were applied for the related test items. For radiated measurement, the test was performed with EUT in X, Y, Z position and the worse case was found when EUT in Y position. All test modes were tested, only the result of the worst case was recorded in the report.

Band	Bandwidth (MHz)						Modulation		RB #			Test Channel		
	1.4	3	5	10	15	20	QPSK	16QAM	1	Part	Full	L	M	H
1	N/A	N/A	Y	/	/	Y	Y	Y	Y	Y	Y	Y	Y	Y
3	Y	/	Y	/	/	Y	Y	Y	Y	Y	Y	Y	Y	Y
7	N/A	N/A	Y	/	/	Y	Y	Y	Y	Y	Y	Y	Y	Y
8	Y	/	Y	Y	N/A	N/A	Y	Y	Y	Y	Y	Y	Y	Y
20	N/A	N/A	Y	/	/	Y	Y	Y	Y	Y	Y	Y	Y	Y
28	N/A	Y	Y	/	/	Y	Y	Y	Y	Y	Y	Y	Y	Y

Note:

- 1)The mark “Y” means that this configuration is chosen for testing.
- 2)The mark “/” means that this bandwidth is supported but is not chosen for testing.
- 3)The mark “N/A” means that this bandwidth is not supported.

1.7. Measurement Uncertainty (95% confidence levels, k=2)

Test Item	Uncertainty
Radio Frequency	0.9×10^{-4}
Total RF Power, Conducted	1.0 dB
RF Power Density, Conducted	1.8 dB
Spurious Emissions, Conducted	1.8 dB
All Emissions, Radiated	3.1 dB
Temperature	0.5°C
Humidity	1 %
DC And Low Frequency Voltages	1 %

1.8. Description of Test Facility

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier is CN0071.

CNAS Registration Number is L4595.



2. SYSTEM TEST CONFIGURATION

2.1. Justification

N/A

2.2. EUT Exercise Software

N/A

2.3. Special Accessories

The special accessories were supplied by Shenzhen LCS Compliance Testing Laboratory Ltd.

2.4. Block Diagram/Schematics

Please refer to the related document.

2.5. Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

2.6. Test Setup

Please refer to the test setup photo.



3. SUMMARY OF TEST RESULTS

Test Engineer	:	Paddi Chen
Temperature/ Humidity:	:	23.7°C/ 52.9%

Reference Clause No. (ETSI EN 301 908-13)	Description of Test Items	Result					
		E-UTRA Band					
		Band 1	Band 3	Band 7	Band 8	Band 20	Band 28
4.2.2	Transmitter Maximum Output Power						
	Normal	Pass	Pass	Pass	Pass	Pass	Pass
	TL/VL	Pass	Pass	Pass	Pass	Pass	Pass
	TL/VH	Pass	Pass	Pass	Pass	Pass	Pass
	TH/VL	Pass	Pass	Pass	Pass	Pass	Pass
	TH/VH	Pass	Pass	Pass	Pass	Pass	Pass
4.2.5	Transmitter Minimum Output Power						
	Normal	Pass	Pass	Pass	Pass	Pass	Pass
	TL/VL	Pass	Pass	Pass	Pass	Pass	Pass
	TL/VH	Pass	Pass	Pass	Pass	Pass	Pass
	TH/VL	Pass	Pass	Pass	Pass	Pass	Pass
	TH/VH	Pass	Pass	Pass	Pass	Pass	Pass
4.2.3	Transmitter Spectrum Emission Mask						
	Normal	Pass	Pass	Pass	Pass	Pass	Pass
4.2.11	Transmitter Adjacent Channel Leakage Power Ratio						
	Normal	Pass	Pass	Pass	Pass	Pass	Pass
	TL/VL	Pass	Pass	Pass	Pass	Pass	Pass
	TL/VH	Pass	Pass	Pass	Pass	Pass	Pass
	TH/VL	Pass	Pass	Pass	Pass	Pass	Pass
	TH/VH	Pass	Pass	Pass	Pass	Pass	Pass
4.2.4	Transmitter Spurious Emissions						
	Normal	Pass	Pass	Pass	Pass	Pass	Pass
4.2.10	Receiver Spurious Emissions						
	Normal	Pass	Pass	Pass	Pass	Pass	Pass
4.2.6	Receiver Adjacent Channel Selectivity (ACS)						
	Normal	Pass	Pass	Pass	Pass	Pass	Pass
4.2.7	Receiver Blocking Characteristics						
	Normal	Pass	Pass	Pass	Pass	Pass	Pass
4.2.8	Receiver Spurious Response						
	Normal	Pass	Pass	Pass	Pass	Pass	Pass
4.2.9	Receiver Intermodulation Characteristics						
	Normal	Pass	Pass	Pass	Pass	Pass	Pass
4.2.12	Receiver Reference Sensitivity Level						

Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101/201, Building A, and Room 101/301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com



	Normal	Pass	Pass	Pass	Pass	Pass	Pass
	TL/VL	Pass	Pass	Pass	Pass	Pass	Pass
	TL/VH	Pass	Pass	Pass	Pass	Pass	Pass
	TH/VL	Pass	Pass	Pass	Pass	Pass	Pass
	TH/VH	Pass	Pass	Pass	Pass	Pass	Pass

Reference Clause No. (ETSI EN 301 908-1)	Description of Test Items	Result					
		E-UTRA Band					
		Band 1	Band 3	Band 7	Band 8	Band 20	Band 28
4.2.2	Radiated emissions (UE)						
	Normal	Pass	Pass	Pass	Pass	Pass	Pass
4.2.4	Control and monitoring functions (UE)						
	Normal	Pass	Pass	Pass	Pass	Pass	Pass

Reference Clause No. (ETSI EN 301 908-13)	Description of Test Items	Result
		E-UTRA Band
		Band 41
4.2.2	Transmitter Maximum Output Power	
	Normal	Pass
	TL/VL	Pass
	TL/VH	Pass
	TH/VL	Pass
	TH/VH	Pass
4.2.5	Transmitter Minimum Output Power	
	Normal	Pass
	TL/VL	Pass
	TL/VH	Pass
	TH/VL	Pass
	TH/VH	Pass
4.2.3	Transmitter Spectrum Emission Mask	
	Normal	Pass
4.2.11	Transmitter Adjacent Channel Leakage Power Ratio	
	Normal	Pass
	TL/VL	Pass
	TL/VH	Pass
	TH/VL	Pass
	TH/VH	Pass
4.2.4	Transmitter Spurious Emissions	
	Normal	Pass
4.2.10	Receiver Spurious Emissions	
	Normal	Pass



4.2.6	Receiver Adjacent Channel Selectivity (ACS)	
	Normal	Pass
4.2.7	Receiver Blocking Characteristics	
	Normal	Pass
4.2.8	Receiver Spurious Response	
	Normal	Pass
4.2.9	Receiver Intermodulation Characteristics	
	Normal	Pass
4.2.12	Receiver Reference Sensitivity Level	
	Normal	Pass
	TL/VL	Pass
	TL/VH	Pass
	TH/VL	Pass
	TH/VH	Pass
4.2.2	Radiated emissions (UE)	
	Normal	Pass
4.2.4	Control and monitoring functions (UE)	
	Normal	Pass

Reference Clause No. (ETSI EN 301 908-1)	Description of Test Items	Result
		E-UTRA Band
		Band 41
4.2.2	Radiated emissions (UE)	
	Normal	Pass
4.2.4	Control and monitoring functions (UE)	
	Normal	Pass

***Note:

Result: Describes test result of Test Case.

Pass: Test Case passed on specified conformance test platform.

Normal(TN/VN): Normal temperature – 25°C; Normal voltage. – DC 3.87V

TH: High extreme Temperature – +45°C

VH: High extreme Voltage – DC 4.45V

TL: Low extreme Temperature – -20°C

VL: Low extreme Voltage – DC 3.48V

N/A: Not applicable.

—: Not test.



4. LIST OF MEASURING EQUIPMENT

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	LTE Test Software	Tonscend	JS1120-1	N/A	N/A	N/A
2	RF Control Unit	Tonscend	JS0806-1	158060009	2023-10-18	2024-10-17
3	MXA Signal Analyzer	Agilent	N9020A	MY51250905	2023-10-18	2024-10-17
4	DC Power Supply	Agilent	E3642A	N/A	2023-10-18	2024-10-17
5	MXG Vector Signal Generator	Agilent	N5182A	MY47071151	2023-06-09	2024-06-08
6	PSG Analog Signal Generator	Agilent	E8257D	MY4520521	2023-06-09	2024-06-08
7	Temperature & Humidity Chamber	GUANGZHOU GOGN WEN	GDS-100	70932	2023-10-05	2024-10-04
8	EMI Test Software	Farad	EZ	/	N/A	N/A
9	3m Full Anechoic Chamber	MRDIANZI	FAC-3M	MR009	2022-08-17	2025-08-16
10	Positioning Controller	Max-Full	MF7802BS	MF780208586	N/A	N/A
11	Active Loop Antenna	SCHWARZBECK	FMZB 1519B	00005	2021-08-29	2024-08-28
12	By-log Antenna	SCHWARZBECK	VULB9163	9163-470	2021-09-12	2024-09-11
13	Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1925	2021-09-05	2024-09-04
14	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	791	2021-08-29	2024-08-28
15	Broadband Preamplifier	SCHWARZBECK	BBV9719	9719-025	2021-08-29	2024-08-28
16	EMI Test Receiver	R&S	ESR 7	101181	2023-08-15	2024-08-14
17	RS SPECTRUM ANALYZER	R&S	FSP40	100503	2023-07-17	2024-07-16
18	Low-frequency amplifier	SchwarzZBECK	BBV9745	00253	2023-10-18	2024-10-17
19	High-frequency amplifier	JS Denki Pte	PA0118-43	JSPA21009	2023-10-18	2024-10-17
20	WIDEBAND RADIO COMMUNICATION TESTER	R&S	CMW 500	103818	2023-06-09	2024-06-08
21	RF Filter	Micro-Tronics	BRC50718	017	2023-10-18	2024-10-17
22	RF Filter	Micro-Tronics	BRC50719	011	2023-10-18	2024-10-17
23	RF Filter	Micro-Tronics	BRC50720	011	2023-10-18	2024-10-17
24	RF Filter	Micro-Tronics	BRC50721	013	2023-10-18	2024-10-17
25	RF Filter	Micro-Tronics	BRM50702	195	2023-08-15	2024-08-14
26	6dB Attenuator	/	100W/6dB	1172040	2023-06-09	2024-06-08
27	3dB Attenuator	/	2N-3dB	/	2023-10-18	2024-10-17

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	LTE Test Software	Tonscend	JS1120-1	N/A	N/A	N/A
2	RF Control Unit	Tonscend	JS0806-1	158060009	2025-11-07	2026-11-06
3	MXA Signal Analyzer	Agilent	N9020A	MY23311067	2026-04-21	2027-04-20
4	DC Power Supply	Agilent	E3642A	N/A	2025-09-27	2026-09-26
5	MXG Vector Signal Generator	Agilent	N5182A	MY47071151	2026-04-21	2027-04-20
6	PSG Analog Signal Generator	Agilent	E8257D	MY46410184	2025-12-05	2026-12-04
7	Temperature & Humidity Chamber	Baro	/	/	2026-05-06	2027-05-05
8	EMI Test Software	Farad	EZ-EMC	Ver. EMC-CON 3A1.1+	N/A	N/A

Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101/201, Building A, and Room 101/301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com



Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
9	3m Semi Anechoic Chamber	MRDIANZI	966	MR009	2025-08-16	2028-08-15
10	Positioning Controller	Max-Full	MF7802BS	MF780208586	N/A	N/A
11	Active Loop Antenna	SCHWARZBECK	FMZB 1519B	00005	2024-07-13	2027-07-12
12	By-log Antenna	SCHWARZBECK	VULB9163	9163-470	2024-08-03	2027-08-02
13	Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1925	2024-07-13	2027-07-12
14	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	791	2024-07-13	2027-07-12
15	Broadband Preamplifier	SCHWARZBECK	BBV9719	9719-025	2024-07-30	2027-07-29
16	EMI Test Receiver	R&S	ESR3	101181	2026-05-06	2027-05-05
17	RS SPECTRUM ANALYZER	R&S	FSP40	100503	2026-04-21	2027-04-20
18	Low-frequency amplifier	SchwarzZBECK	BBV9745	00253	2025-09-27	2026-09-26
19	High-frequency amplifier	JS Denki Pte	PA0118-43	JSPA21009	2025-09-27	2026-09-26
20	WIDEBAND RADIO COMMUNICATION TESTER	R&S	CMW 500	166586	2025-09-27	2026-09-26
21	RF Filter	Micro-Tronics	BRC50718	017	2025-09-27	2026-09-26
22	RF Filter	Micro-Tronics	BRC50719	011	2025-09-28	2026-09-27
23	RF Filter	Micro-Tronics	BRC50720	011	2025-09-27	2026-09-26
24	RF Filter	Micro-Tronics	BRC50721	013	2025-09-27	2026-09-26
25	RF Filter	Micro-Tronics	BRM50702	S/N-195	2026-04-21	2027-04-20
26	6dB Attenuator	/	100W/6dB	1172040	2026-04-21	2027-04-20
27	3dB Attenuator	/	2N-3dB	/	2025-09-28	2026-09-27



5. PHOTOGRAPHS OF TEST SETUP

Please refer to separated files Appendix D for Photographs of Test Setup_RF.

6. PHOTOGRAPHS OF THE EUT

Please refer to separated files Appendix C for Photographs of The EUT.



Annex A

Transmitter maximum output power

The Conducted Power Measurement Result for LTE Band					
Test Result for LTE Band 1					
Channel Bandwidth	Channel	RB Allocation		Average Power (dBm, QPSK)	Limit (dBm)
		RB Size	RB Offset		
5MHz	Low Range	1	1RB#0	20.73	20.3~25.7
			8RB#0	20.62	20.3~25.7
	Mid Range	1	1RB#0	21.15	20.3~25.7
			8RB#0	21.34	20.3~25.7
	High Range	1	1RB#24	20.43	20.3~25.7
			8RB#17	20.34	20.3~25.7
20MHz	Low Range	1	1RB#0	20.53	20.3~25.7
			18RB#0	20.41	20.3~25.7
	Mid Range	1	1RB#0	20.42	20.3~25.7
			18RB#0	20.61	20.3~25.7
	High Range	1	1RB#99	21.30	20.3~25.7
			18RB#82	21.45	20.3~25.7

The Conducted Power Measurement Result for LTE Band					
Test Result for LTE Band 3					
Channel Bandwidth	Channel	RB Allocation		Average Power (dBm, QPSK)	Limit (dBm)
		RB Size	RB Offset		
1.4MHz	Low Range	1	1RB#0	20.32	20.3~25.7
	Mid Range	1	1RB#0	20.39	20.3~25.7
	High Range	1	1RB#0	20.36	20.3~25.7
5MHz	Low Range	1	5RB#0	20.52	20.3~25.7
			1RB#0	20.45	20.3~25.7
	Mid Range	1	1RB#24	20.86	20.3~25.7
			1RB#0	20.96	20.3~25.7
	High Range	1	1RB#24	20.41	20.3~25.7
			1RB#0	20.33	20.3~25.7
20MHz	Low Range	1	1RB#24	21.28	20.3~25.7
			8RB#0	20.65	20.3~25.7
	Mid Range	1	1RB#0	20.50	20.3~25.7
			1RB#99	21.01	20.3~25.7
	High Range	1	1RB#0	20.78	20.3~25.7
			1RB#99	20.99	20.3~25.7
			1RB#0	21.67	20.3~25.7
			1RB#99	20.79	20.3~25.7
			18RB#0	21.43	20.3~25.7



The Conducted Power Measurement Result for LTE Band

Test Result for LTE Band 7

Channel Bandwidth	Channel	RB Allocation		Average Power (dBm, QPSK)	Limit (dBm)
		RB Size	RB Offset		
5MHz	Low Range	1	1RB#0	20.39	20.3~25.7
			1RB#24	20.70	20.3~25.7
	Mid Range	1	1RB#0	20.49	20.3~25.7
			1RB#24	20.81	20.3~25.7
	High Range	1	1RB#0	21.14	20.3~25.7
			1RB#24	21.01	20.3~25.7
20MHz	Low Range	1	1RB#0	20.96	20.3~25.7
			1RB#99	20.71	20.3~25.7
	Mid Range	1	1RB#0	20.55	20.3~25.7
			1RB#99	20.54	20.3~25.7
	High Range	1	1RB#0	21.58	20.3~25.7
			1RB#99	21.06	20.3~25.7
			18RB#0	21.73	20.3~25.7

The Conducted Power Measurement Result for LTE Band

Test Result for LTE Band 8

Channel Bandwidth	Channel	RB Allocation		Average Power (dBm, QPSK)	Limit (dBm)
		RB Size	RB Offset		
1.4MHz	Low Range	1	1RB#0	23.93	20.3~25.7
	Mid Range	1	1RB#0	23.45	20.3~25.7
	High Range	1	1RB#0	23.90	20.3~25.7
			5RB#0	23.96	20.3~25.7
5MHz	Low Range	1	1RB#0	23.89	20.3~25.7
			1RB#24	23.90	20.3~25.7
	Mid Range	1	1RB#0	23.40	20.3~25.7
			1RB#24	23.30	20.3~25.7
	High Range	1	1RB#0	23.90	20.3~25.7
			1RB#24	23.77	20.3~25.7
10MHz	Low Range	1	1RB#0	23.89	20.3~25.7
			1RB#49	23.90	20.3~25.7
	Mid Range	1	1RB#0	23.68	20.3~25.7
			1RB#49	23.38	20.3~25.7
	High Range	1	1RB#0	23.93	20.3~25.7
			1RB#49	23.71	20.3~25.7
			12RB#0	23.93	20.3~25.7



The Conducted Power Measurement Result for LTE Band

Test Result for LTE Band 20

Channel Bandwidth	Channel	RB Allocation		Average Power (dBm, QPSK)	Limit (dBm)
		RB Size	RB Offset		
5MHz	Low Range	1	1RB#0	24.03	20.3~25.7
			1RB#24	24.08	20.3~25.7
	Mid Range	1	1RB#0	24.25	20.3~25.7
			1RB#24	24.20	20.3~25.7
	High Range	1	1RB#0	24.18	20.3~25.7
			1RB#24	24.21	20.3~25.7
20MHz	Low Range	1	1RB#0	24.00	20.3~25.7
			1RB#99	24.20	20.3~25.7
	Mid Range	1	1RB#0	24.07	20.3~25.7
			1RB#99	24.15	20.3~25.7
	High Range	1	1RB#0	23.92	20.3~25.7
			1RB#99	24.18	20.3~25.7
			18RB#0	23.99	20.3~25.7

The Conducted Power Measurement Result for LTE Band

Test Result for LTE Band 28

Channel Bandwidth	Channel	RB Allocation		Average Power (dBm, QPSK)	Limit (dBm)
		RB Size	RB Offset		
3MHz	Low Range	1	1RB#0	23.60	20.3~25.7
			4RB#0	23.65	20.3~25.7
	Mid Range	1	1RB#0	23.73	20.3~25.7
			4RB#0	23.60	20.3~25.7
	High Range	1	1RB#14	23.54	20.3~25.7
			4RB#11	23.54	20.3~25.7
5MHz	Low Range	1	1RB#0	23.49	20.3~25.7
			8RB#0	23.49	20.3~25.7
	Mid Range	1	1RB#0	23.60	20.3~25.7
			8RB#0	23.52	20.3~25.7
	High Range	1	1RB#24	23.52	20.3~25.7
			8RB#17	23.59	20.3~25.7
20MHz	Low Range	1	1RB#0	23.58	20.3~25.7
			18RB#0	23.51	20.3~25.7
	Mid Range	1	1RB#0	23.61	20.3~25.7
			18RB#0	23.61	20.3~25.7
	High Range	1	1RB#99	23.42	20.3~25.7
			18RB#82	23.39	20.3~25.7



The Conducted Power Measurement Result for LTE Band					
Test Result for LTE Band 41					
Channel Bandwidth	Channel	RB Allocation		Average Power (dBm, QPSK)	Limit (dBm)
		RB Size	RB Offset		
5MHz	Low Range	1	1RB#0	23.44	18.8~25.7
			1RB#24	23.47	18.8~25.7
	Mid Range	1	1RB#0	23.88	20.3~25.7
			1RB#24	23.77	20.3~25.7
	High Range	1	1RB#0	23.87	18.8~25.7
			1RB#24	23.37	18.8~25.7
			8RB#0	23.25	18.8~25.7
20MHz	Low Range	1	1RB#0	23.46	18.8~25.7
			1RB#99	23.47	18.8~25.7
	Mid Range	1	1RB#0	23.82	20.3~25.7
			1RB#99	23.55	20.3~25.7
	High Range	1	1RB#0	23.85	18.8~25.7
			1RB#99	23.36	18.8~25.7
			18RB#0	23.00	18.8~25.7



Annex of Radiated spurious emission

Radiated spurious emissions - MS allocated a channel(Worst Case)

LTE Band 1(5MHz, RB allocation=25): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
54.15	Horizontal	-72.71	-36.00	Pass
996.25	H	-77.06	-36.00	
3902.95	H	-64.05	-30.00	
5852.09	H	-51.91	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
55.63	Vertical	-76.94	-36.00	Pass
949.41	V	-79.80	-36.00	
3905.02	V	-65.81	-30.00	
5853.06	V	-60.70	-30.00	

LTE Band 1(5MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
53.78	Horizontal	-71.62	-36.00	Pass
946.26	H	-80.38	-36.00	
3902.85	H	-68.19	-30.00	
5855.13	H	-59.28	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
58.42	Vertical	-70.70	-36.00	Pass
919.26	V	-70.69	-36.00	
3905.65	V	-63.18	-30.00	
5850.13	V	-56.49	-30.00	



LTE Band 1(20MHz, RB allocation=100): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
52.94	Horizontal	-74.16	-36.00	Pass
903.54	H	-73.27	-36.00	
3902.36	H	-68.54	-30.00	
5850.20	H	-51.25	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
59.36	Vertical	-75.16	-36.00	Pass
712.69	V	-80.62	-36.00	
3903.92	V	-66.58	-30.00	
5851.80	V	-50.23	-30.00	

LTE Band 1(20MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
55.95	Horizontal	-71.46	-36.00	Pass
770.17	H	-70.74	-36.00	
3905.65	H	-65.97	-30.00	
5852.78	H	-57.04	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
59.60	Vertical	-74.60	-36.00	Pass
803.88	V	-79.60	-36.00	
3902.40	V	-64.25	-30.00	
5851.78	V	-55.55	-30.00	



LTE Band 3(1.4MHz, RB allocation=6): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
50.28	Horizontal	-70.42	-36.00	Pass
986.93	H	-75.35	-36.00	
3505.71	H	-70.49	-30.00	
5254.66	H	-58.24	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
56.66	Vertical	-72.20	-36.00	Pass
939.83	V	-70.69	-36.00	
3504.54	V	-62.19	-30.00	
5253.52	V	-56.73	-30.00	

LTE Band 3(1.4MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
58.16	Horizontal	-77.42	-36.00	Pass
869.28	H	-75.08	-36.00	
3502.93	H	-67.36	-30.00	
5254.79	H	-60.63	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
59.28	Vertical	-70.24	-36.00	Pass
776.94	V	-79.54	-36.00	
3503.40	V	-70.94	-30.00	
5253.80	V	-60.71	-30.00	



LTE Band 3(5MHz, RB allocation=25): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
55.71	Horizontal	-79.95	-36.00	Pass
790.65	H	-79.59	-36.00	
3500.55	H	-70.26	-30.00	
5255.65	H	-51.07	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
60.90	Vertical	-74.60	-36.00	Pass
876.60	V	-74.75	-36.00	
3500.33	V	-61.33	-30.00	
5255.29	V	-54.47	-30.00	

LTE Band 3(5MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
50.36	Horizontal	-73.99	-36.00	Pass
888.83	H	-77.00	-36.00	
3503.15	H	-65.13	-30.00	
5251.28	H	-52.90	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
55.33	Vertical	-71.45	-36.00	Pass
813.08	V	-70.42	-36.00	
3500.74	V	-62.62	-30.00	
5251.88	V	-57.08	-30.00	



LTE Band 3(20MHz, RB allocation=100): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
59.64	Horizontal	-76.24	-36.00	Pass
873.62	H	-72.52	-36.00	
3505.68	H	-65.79	-30.00	
5255.26	H	-53.65	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
50.92	Vertical	-71.77	-36.00	Pass
744.70	V	-78.18	-36.00	
3500.95	V	-63.23	-30.00	
5251.86	V	-53.82	-30.00	

LTE Band 3(20MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
57.43	Horizontal	-75.26	-36.00	Pass
726.33	H	-79.90	-36.00	
3504.93	H	-68.11	-30.00	
5252.89	H	-58.89	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
60.39	Vertical	-72.50	-36.00	Pass
831.43	V	-79.26	-36.00	
3503.48	V	-66.65	-30.00	
5253.15	V	-57.42	-30.00	



LTE Band 7(5MHz, RB allocation=25): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
60.23	Horizontal	-80.29	-36.00	Pass
996.91	H	-78.93	-36.00	
5074.97	H	-60.97	-30.00	
7688.39	H	-59.55	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
52.83	Vertical	-72.40	-36.00	Pass
716.42	V	-72.65	-36.00	
5073.83	V	-60.92	-30.00	
7689.01	V	-55.42	-30.00	

LTE Band 7(5MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
50.86	Horizontal	-74.65	-36.00	Pass
800.11	H	-80.26	-36.00	
5072.69	H	-64.97	-30.00	
7686.83	H	-55.34	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
57.25	Vertical	-77.66	-36.00	Pass
934.16	V	-77.33	-36.00	
5073.19	V	-69.33	-30.00	
7686.06	V	-50.28	-30.00	



LTE Band 7(20MHz, RB allocation=100): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
57.76	Horizontal	-70.25	-36.00	Pass
979.86	H	-78.46	-36.00	
5071.12	H	-66.55	-30.00	
7687.20	H	-50.75	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
50.61	Vertical	-74.13	-36.00	Pass
761.87	V	-79.44	-36.00	
5074.29	V	-64.35	-30.00	
7689.52	V	-55.27	-30.00	

LTE Band 7(20MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
53.00	Horizontal	-75.14	-36.00	Pass
788.52	H	-76.79	-36.00	
5075.29	H	-64.85	-30.00	
7689.83	H	-59.68	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
57.64	Vertical	-76.36	-36.00	Pass
845.81	V	-75.46	-36.00	
5074.54	V	-70.92	-30.00	
7688.11	V	-59.54	-30.00	



LTE Band 8(1.4MHz, RB allocation=6): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
50.33	Horizontal	-73.37	-36.00	Pass
933.15	H	-77.58	-36.00	
1800.44	H	-61.54	-30.00	
2694.82	H	-50.28	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
51.01	Vertical	-78.42	-36.00	Pass
855.16	V	-80.98	-36.00	
1790.30	V	-70.53	-30.00	
2692.34	V	-51.19	-30.00	

LTE Band 8(1.4MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
59.94	Horizontal	-79.78	-36.00	Pass
768.92	H	-76.27	-36.00	
1797.70	H	-70.14	-30.00	
2693.96	H	-56.89	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
52.84	Vertical	-75.58	-36.00	Pass
723.75	V	-70.62	-36.00	
1795.31	V	-64.78	-30.00	
2693.00	V	-52.91	-30.00	



LTE Band 8(5MHz, RB allocation=25): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
50.10	Horizontal	-78.72	-36.00	Pass
854.22	H	-74.15	-36.00	
1800.94	H	-68.53	-30.00	
2691.40	H	-55.38	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
58.22	Vertical	-75.58	-36.00	Pass
914.12	V	-79.40	-36.00	
1796.84	V	-69.19	-30.00	
2692.78	V	-59.81	-30.00	

LTE Band 8(5MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
56.73	Horizontal	-78.17	-36.00	Pass
893.66	H	-77.31	-36.00	
1791.16	H	-69.71	-30.00	
2691.32	H	-58.96	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
51.95	Vertical	-74.83	-36.00	Pass
862.09	V	-79.98	-36.00	
1796.75	V	-67.28	-30.00	
2692.01	V	-60.87	-30.00	



LTE Band 8(10MHz, RB allocation=50): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
60.32	Horizontal	-74.43	-36.00	Pass
708.11	H	-78.57	-36.00	
1799.00	H	-62.66	-30.00	
2693.61	H	-52.52	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
57.47	Vertical	-79.84	-36.00	Pass
952.16	V	-71.89	-36.00	
1793.96	V	-66.98	-30.00	
2695.21	V	-56.95	-30.00	

LTE Band 8(10MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
51.40	Horizontal	-70.61	-36.00	Pass
784.56	H	-80.34	-36.00	
1793.64	H	-68.34	-30.00	
2694.55	H	-53.37	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
51.53	Vertical	-78.04	-36.00	Pass
918.57	V	-76.42	-36.00	
1792.31	V	-70.69	-30.00	
2694.00	V	-59.48	-30.00	



LTE Band 20(5MHz, RB allocation=25): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
53.99	Horizontal	-77.59	-36.00	Pass
956.09	H	-78.56	-36.00	
1691.37	H	-68.88	-30.00	
2544.32	H	-51.77	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
56.87	Vertical	-74.28	-36.00	Pass
922.30	V	-75.98	-36.00	
1700.01	V	-69.67	-30.00	
2545.87	V	-57.56	-30.00	

LTE Band 20(5MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
60.07	Horizontal	-75.51	-36.00	Pass
876.59	H	-79.19	-36.00	
1700.69	H	-61.45	-30.00	
2542.78	H	-58.04	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
59.15	Vertical	-76.64	-36.00	Pass
766.00	V	-77.45	-36.00	
1700.55	V	-64.04	-30.00	
2540.64	V	-57.88	-30.00	



LTE Band 20(20MHz, RB allocation=100): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
52.60	Horizontal	-73.13	-36.00	Pass
901.52	H	-74.79	-36.00	
1699.28	H	-60.34	-30.00	
2544.55	H	-59.67	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
50.47	Vertical	-74.29	-36.00	Pass
949.33	V	-71.47	-36.00	
1697.12	V	-64.61	-30.00	
2542.84	V	-57.91	-30.00	

LTE Band 20(20MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
57.72	Horizontal	-70.40	-36.00	Pass
856.00	H	-74.29	-36.00	
1698.88	H	-70.88	-30.00	
2544.09	H	-53.53	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
58.11	Vertical	-78.41	-36.00	Pass
944.93	V	-77.78	-36.00	
1700.30	V	-61.33	-30.00	
2540.24	V	-50.56	-30.00	



LTE Band 28(3MHz, RB allocation=15): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
60.48	Horizontal	-72.93	-36.00	Pass
849.50	H	-74.19	-36.00	
1447.41	H	-60.86	-30.00	
2171.75	H	-60.53	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
55.74	Vertical	-78.14	-36.00	Pass
783.56	V	-76.25	-36.00	
1453.36	V	-66.35	-30.00	
2180.61	V	-54.41	-30.00	

LTE Band 28(3MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
59.36	Horizontal	-78.89	-36.00	Pass
958.99	H	-70.08	-36.00	
1453.16	H	-62.02	-30.00	
2177.43	H	-51.68	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
50.26	Vertical	-71.13	-36.00	Pass
900.67	V	-79.89	-36.00	
1452.42	V	-60.33	-30.00	
2177.91	V	-60.53	-30.00	



LTE Band 28(5MHz, RB allocation=25): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
56.84	Horizontal	-80.29	-36.00	Pass
813.68	H	-71.24	-36.00	
1446.60	H	-60.92	-30.00	
2172.82	H	-50.91	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
52.38	Vertical	-80.78	-36.00	Pass
805.51	V	-75.71	-36.00	
1448.98	V	-63.43	-30.00	
2177.41	V	-51.79	-30.00	

LTE Band 28(5MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
58.18	Horizontal	-73.06	-36.00	Pass
762.21	H	-77.45	-36.00	
1447.34	H	-68.43	-30.00	
2177.87	H	-59.03	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
60.73	Vertical	-74.21	-36.00	Pass
738.02	V	-75.46	-36.00	
1454.04	V	-62.64	-30.00	
2174.45	V	-54.87	-30.00	



LTE Band 28(20MHz, RB allocation=100): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
54.09	Horizontal	-79.91	-36.00	Pass
732.93	H	-76.74	-36.00	
1455.75	H	-61.22	-30.00	
2175.47	H	-57.64	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
53.83	Vertical	-72.18	-36.00	Pass
815.09	V	-79.57	-36.00	
1451.43	V	-61.52	-30.00	
2174.24	V	-57.70	-30.00	

LTE Band 28(20MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
52.72	Horizontal	-71.01	-36.00	Pass
971.69	H	-80.24	-36.00	
1448.54	H	-69.25	-30.00	
2175.07	H	-56.39	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
60.63	Vertical	-75.34	-36.00	Pass
896.31	V	-73.00	-36.00	
1449.31	V	-67.66	-30.00	
2175.16	V	-51.43	-30.00	



LTE Band 41(5MHz, RB allocation=25): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
55.17	Horizontal	-72.93	-36.00	Pass
851.70	H	-79.75	-36.00	
1674.18	H	-63.35	-30.00	
2511.21	H	-51.16	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
50.83	Vertical	-79.63	-36.00	Pass
837.39	V	-71.40	-36.00	
1675.75	V	-66.15	-30.00	
2510.58	V	-57.52	-30.00	

LTE Band 41(5MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
55.93	Horizontal	-73.22	-36.00	Pass
732.80	H	-75.97	-36.00	
5070.06	H	-61.83	-30.00	
7686.07	H	-53.73	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
52.54	Vertical	-74.98	-36.00	Pass
719.68	V	-71.04	-36.00	
5071.39	V	-66.20	-30.00	
7689.40	V	-59.99	-30.00	



LTE Band 41(20MHz, RB allocation=100): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
57.18	Horizontal	-74.30	-36.00	Pass
866.05	H	-79.97	-36.00	
5071.66	H	-70.35	-30.00	
7688.55	H	-50.61	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
53.53	Vertical	-73.64	-36.00	Pass
743.34	V	-73.81	-36.00	
5070.29	V	-65.16	-30.00	
7689.38	V	-56.21	-30.00	

LTE Band 41(20MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
55.63	Horizontal	-70.51	-36.00	Pass
928.42	H	-77.23	-36.00	
5070.84	H	-62.93	-30.00	
7689.04	H	-57.09	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
55.83	Vertical	-75.03	-36.00	Pass
825.66	V	-79.20	-36.00	
5075.99	V	-70.13	-30.00	
7690.79	V	-53.18	-30.00	

-----THE END OF REPORT-----