

## FCC TEST REPORT

Shenzhen Huafului Technology Co., Ltd.

Wireless Earphone

Test Model: Neo 1a


Additional Model No.: Please Refer to Page 7

Prepared for	:	Shenzhen Huafului Technology Co., Ltd.
Address	:	Unit 601-03, 6/F, Block A, Building 1, Ganfeng Technology Building, No. 993 Jiaxian Road, Xiangjiaotang Community, Bantian Street, Longgang District, Shenzhen, P.R. China
Prepared by	:	Guangzhou LCS Compliance Testing Laboratory Ltd.
Address	:	No.44-1, Qianfeng North Road, Shiqi , Panyu District, Guangzhou, Guangdong, China
Tel	:	(+86) 020-39166689
Fax	:	(+86) 020-39166619
Web	:	www.LCS-cert.com
Mail	:	webmaster@LCS-cert.com
Date of receipt of test sample	:	May 13, 2026
Number of tested samples	:	2
Sample No.	:	C05126006-1, C05126006-2
Serial number	:	Prototype
Date of Test	:	May 13, 2026 ~ June 08, 2026
Date of Report	:	June 09, 2026



<b>FCC TEST REPORT</b>	
<b>FCC 47 CFR Part 15 Subpart B, Class B, ANSI C63.4a-2017(Amendment to ANSI C63.4-2014)</b>	
Report Reference No. .... : LCSC05126006E	
Date Of Issue ..... : June 09, 2026	
Testing Laboratory Name .... : <b>Guangzhou LCS Compliance Testing Laboratory Ltd.</b>	
Address ..... : No.44-1,Qianfeng North Road, Shiqi , Panyu District, Guangzhou, Guangdong, China	
Testing Location/ Procedure... : Full application of Harmonised standards ■ Partial application of Harmonised standards □ Other standard testing method □	
Applicant's Name..... : <b>Shenzhen Huafurui Technology Co., Ltd.</b>	
Address ..... : Unit 601-03, 6/F, Block A, Building 1, Ganfeng Technology Building, No. 993 Jiaxian Road, Xiangjiaotang Community, Bantian Street, Longgang District, Shenzhen, P.R. China	
<b>Test Specification</b>	
Standard.....	FCC 47 CFR Part 15 Subpart B, Class B, ANSI C63.4a-2017(Amendment to ANSI C63.4-2014)
Test Report Form No.....	TRF-4-E-010 A/0
TRF Originator.....	Guangzhou LCS Compliance Testing Laboratory Ltd.
Master TRF.....	Dated 2011-03
<b>Guangzhou LCS Compliance Testing Laboratory Ltd. All rights reserved.</b> This publication may be reproduced in whole or in part for non-commercial purposes as long as the Guangzhou LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Guangzhou LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.	
<b>Test Item Description. .... : Wireless Earphone</b>	
Trade Mark .....	CUBOT
Test Model .....	Neo 1a
Ratings .....	Please Refer to Page 7
<b>Result .....</b>	<b>PASS</b>

Compiled by:




Ace Yao/ Administrator

Reviewed by:



Justin Zhu/ Technique Director

Approved by:



Gavin Liang/ Manager

## FCC TEST REPORT

<b>Test Report No. :</b> LCSC05126006E	<u>June 09, 2026</u> Date of issue
--	---------------------------------------

Test Model ..... : Neo 1a

EUT..... : Wireless Earphone

**Applicant..... : Shenzhen Huafurui Technology Co., Ltd.**

Address..... : Unit 601-03, 6/F, Block A, Building 1, Ganfeng  
Technology Building, No. 993 Jiaxian Road,  
Xiangjiaotang Community, Bantian Street, Longgang  
District, Shenzhen, P.R. China

Telephone..... : /

Fax..... : /

**Manufacturer..... : Shenzhen Huafurui Technology Co., Ltd.**

Address..... : Unit 601-03, 6/F, Block A, Building 1, Ganfeng  
Technology Building, No. 993 Jiaxian Road,  
Xiangjiaotang Community, Bantian Street, Longgang  
District, Shenzhen, P.R. China

Telephone..... : /

Fax..... : /

**Factory..... : Shenzhen Huafurui Technology Co., Ltd.**

Address..... : Unit 601-03, 6/F, Block A, Building 1, Ganfeng  
Technology Building, No. 993 Jiaxian Road,  
Xiangjiaotang Community, Bantian Street, Longgang  
District, Shenzhen, P.R. China

Telephone..... : /

Fax..... : /

**Test Result** according to the standards on page 6: **PASS**

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revision History

Report Version	Issue Date	Revision Content	Revised By
000	June 09, 2026	Initial Issue	---



## TABLE OF CONTENTS

Test Report Description	Page
<b>1. SUMMARY OF STANDARDS AND RESULTS .....</b>	<b>6</b>
1.1. Description of Standards and Results .....	6
<b>2. GENERAL INFORMATION .....</b>	<b>7</b>
2.1. Description of Device (EUT) .....	7
2.2. Support Equipment List.....	8
2.3 External I/O Cable.....	8
2.4. Description of Test Facility .....	8
2.5. Statement of the Measurement Uncertainty .....	8
2.6. Measurement Uncertainty.....	9
<b>3. TEST RESULTS.....</b>	<b>10</b>
3.1. POWER LINE CONDUCTED EMISSION MEASUREMENT .....	10
3.2. Radiated emission Measurement .....	14
<b>4. PHOTOGRAPH .....</b>	<b>21</b>
<b>5. EXTERNAL AND INTERNAL PHOTOS OF THE EUT .....</b>	<b>23</b>

# 1. SUMMARY OF STANDARDS AND RESULTS

## 1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

EMISSION			
Description of Test Item	Standard	Limits	Results
Conducted disturbance at mains terminals	FCC 47 CFR Part 15 Subpart B, Class B, ANSI C63.4a-2017(Amendment to ANSI C63.4-2014)	Class B	PASS
Radiated disturbance	FCC 47 CFR Part 15 Subpart B, Class B, ANSI C63.4a-2017(Amendment to ANSI C63.4-2014)	Class B	PASS
N/A is an abbreviation for Not Applicable.			

Test mode:		
Mode 1	Normal Operation	Record

## 2. GENERAL INFORMATION

### 2.1. Description of Device (EUT)

EUT : Wireless Earphone

Test Model : Neo 1a

Additional Model No. : Neo 3, Neo 3a, Neo 3lite, Neo 3pro, Neo 5, Neo 5a, Neo 5pro, Neo 5lite, Neo Lite, Neo Pro, Neo Clip, Neo Clip S, Neo Bass, Neo S, Neo Fit

Model Declaration : PCB board, structure and internal of these model(s) are the same, So no additional models were tested

Ratings : Input: DC 5V, 1A  
Headset: DC 3.7V by Li-ion Battery(28mAh)  
Charging case: DC 3.7V by Li-ion Battery(350mAh)

Highest internal frequency (Fx) : Fx > 1 GHz

Highest internal frequency (Fx)	Highest measured frequency
Fx ≤ 108 MHz	1 GHz
108 MHz < Fx ≤ 500 MHz	2 GHz
500 MHz < Fx ≤ 1 GHz	5 GHz
Fx > 1 GHz	5 × Fx up to a maximum of 6 GHz
NOTE 1 For FM and TV broadcast receivers, Fx is determined from the highest frequency generated or used excluding the local oscillator and tuned frequencies. Where Fx is unknown, the radiated emission measurements shall be performed up to 6 GHz.	

## 2.2. Support Equipment List

Manufacturer	Description	Model	Serial Number	Certificate
SHENZHEN TIANYIN ELECTRONICS CO., LTD	Power Adapter	TPA-4605020 0UU	---	FCC

Note: Auxiliary equipment is provided by the laboratory.

## 2.3 External I/O Cable

I/O Port Description	Quantity	Cable
Type-C Port	1	N/A

## 2.4. Description of Test Facility

CNAS Registration Number is L11555  
 A2LA Certificate Number: 5099.01  
 FCC Designation Number is CN1379  
 Test Firm Registration Number: 729882

## 2.5. Statement of the Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

## 2.6. Measurement Uncertainty

Test	Parameters	Expanded Uncertainty (Ulab)	Expanded Uncertainty (Ucispr)
Conducted Emission	Level accuracy (9kHz to 150kHz) (150kHz to 30MHz)	$\pm 2.63$ dB $\pm 2.35$ dB	$\pm 3.8$ dB $\pm 3.4$ dB
Radiated Emission	Level accuracy (9kHz to 30MHz)	$\pm 3.68$ dB	N/A
Radiated Emission	Level accuracy (30MHz to 1000MHz)	$\pm 3.48$ dB	$\pm 5.3$ dB
Radiated Emission	Level accuracy (above 1000MHz)	$\pm 3.90$ dB	$\pm 5.2$ dB

(1) Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus.

(2) The reported expanded uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor of  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

3. TEST RESULTS


3.1. POWER LINE CONDUCTED EMISSION MEASUREMENT

3.1.1. Test Equipment

The following test equipments are used during the power line conducted measurement:

Item	GLCS Number	Test Equipment	Model No.	Manufacturer	Due date
1	GLCS-E-002	Shield Room#1	433	Maorui	N/A
2	GLCS-E-158	EMI Test Receiver	ESR7	ROHDE & SCHWARZ	2027/04/06
3	GLCS-E-017	EMI Test Software	EZ-EMC	Farad	N/A
4	GLCS-E-011	Artificial Mains Network	ESH2-Z5	ROHDE & SCHWARZ	2027/01/13
5	GLCS-E-080	10dB Attenuator	VTSD 9561-F	Schwarzbeck	2027/04/06

3.1.2. Block Diagram of Test Setup



3.1.3. Test Standard

Power Line Conducted Emission Limits (Class B)

Frequency (MHz)			Limit (dB $\mu$ V)	
			Quasi-peak Level	Average Level
0.15	~	0.50	66.0 ~ 56.0 *	56.0 ~ 46.0 *
0.50	~	5.00	56.0	46.0
5.00	~	30.00	60.0	50.0

NOTE1-The lower limit shall apply at the transition frequencies.  
NOTE2-The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.50MHz.

3.1.4. EUT Configuration on Test

The following equipments are installed on Power Line Conducted Emission Measurement to meet the commission requirement and operating regulations in a manner, which tends to maximize its emission characteristics in a normal application.

3.1.5. Operating Condition of EUT

3.1.5.1. Setup the EUT as shown on Section 3.1.2

3.1.5.2. Turn on the power of all equipments.

### 3.1.5.3. Let the EUT work in measuring Mode 1 and measure it.

### 3.1.6. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC/ANSI C63.4-2014 on Conducted Emission Measurement.

The bandwidth of the test receiver is set at 9kHz.


The frequency range from 150kHz to 30MHz is investigated

### 3.1.7. Test Results

**PASS.**

The test result please refer to the next page.


<b>Test Model</b>	Neo 1a	<b>Test Mode</b>	Mode 1
<b>Environmental Conditions</b>	22.1℃, 57.2% RH	<b>Test Engineer</b>	Zhang Hai
<b>Pol</b>	Line	<b>Test Voltage</b>	AC 120V/60Hz



No.	Mk.	Freq. MHz	Reading Level	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1544	46.89	10.17	57.06	65.76	-8.70	QP	
2		0.2040	9.01	10.09	19.10	53.45	-34.35	AVG	
3		0.3209	28.42	10.13	38.55	59.68	-21.13	QP	
4		0.3255	-1.63	10.12	8.49	49.57	-41.08	AVG	
5		0.8610	16.59	10.19	26.78	56.00	-29.22	QP	
6		0.8610	3.07	10.19	13.26	46.00	-32.74	AVG	
7		2.4180	18.03	10.23	28.26	56.00	-27.74	QP	
8		2.4224	4.78	10.23	15.01	46.00	-30.99	AVG	
9		5.6130	-2.67	10.28	7.61	50.00	-42.39	AVG	
10		5.6400	9.20	10.28	19.48	60.00	-40.52	QP	
11		17.5020	8.51	10.40	18.91	60.00	-41.09	QP	
12		22.0425	-1.75	10.36	8.61	50.00	-41.39	AVG	



<b>Test Model</b>	Neo 1a	<b>Test Mode</b>	Mode 1
<b>Environmental Conditions</b>	22.1℃, 57.2% RH	<b>Test Engineer</b>	Zhang Hai
<b>Pol</b>	Neutral	<b>Test Voltage</b>	AC 120V/60Hz



No.	Mk.	Freq. MHz	Reading Level dB	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1770	12.95	10.09	23.04	54.63	-31.59	AVG	
2	*	0.2265	41.75	10.12	51.87	62.58	-10.71	QP	
3		0.3390	24.99	10.08	35.07	59.23	-24.16	QP	
4		0.4964	0.19	10.07	10.26	46.06	-35.80	AVG	
5		0.8565	7.56	10.10	17.66	46.00	-28.34	AVG	
6		0.8610	17.48	10.10	27.58	56.00	-28.42	QP	
7		2.4224	5.51	10.25	15.76	46.00	-30.24	AVG	
8		2.4630	17.75	10.25	28.00	56.00	-28.00	QP	
9		5.6400	-3.08	10.22	7.14	50.00	-42.86	AVG	
10		5.9595	8.09	10.24	18.33	60.00	-41.67	QP	
11		14.3204	-2.11	10.37	8.26	50.00	-41.74	AVG	
12		15.4860	9.45	10.38	19.83	60.00	-40.17	QP	

Note: Margin= Reading level + Correct factor – Limit  
Correct Factor= Lisen Factor+Cable Factor



## 3.2. Radiated emission Measurement

### 3.2.1. Test Equipment

The following test equipments are used during the radiated emission measurement:

Item	GLCS Number	Test Equipment	Model No.	Manufacturer	Due date
1	GLCS-E-001	Semi Anechoic Chamber#1	966	Maorui	2027/04/20
2	GLCS-E-047	Hygrothermograph #5	3in1	Baro	2027/04/08
3	GLCS-E-017	EMI Test Software	EZ-EMC(Ver.FA-03A2 RE+)	Farad	N/A
4	GLCS-E-192	EMI Test Receiver	ESR7	ROHDE & SCHWARZ	2027/04/06
5	GLCS-E-019	Biconical Antenna	VHBB 9124	ROHDE & SCHWARZ	2026/07/18
6	GLCS-E-352	By-log Antenna	VULB 9163	ROHDE & SCHWARZ	2028/08/15
7	GLCS-E-286	Broadband Preamplifier	LNPA 30MO6G-40(18G Hz)	Cesheng Technology	2027/04/06

### 3.2.2. Block Diagram of Test Setup



### 3.2.3. Radiated Emission Limit (Class B)

Limits for Radiated Disturbance Below 1GHz			
FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		$\mu\text{V/m}$	$\text{dB}(\mu\text{V})/\text{m}$
30 ~ 88	3	100	40
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46
960 ~ 1000	3	500	54
Remark: (1) Emission level $(\text{dB})\mu\text{V} = 20 \log \text{Emission level } \mu\text{V/m}$ (2) The smaller limit shall apply at the cross point between two frequency bands. (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.			
Limits for Radiated Emission Above 1GHz			
Frequency (MHz)	Distance (Meters)	Peak Limit ( $\text{dB}\mu\text{V/m}$ )	Average Limit ( $\text{dB}\mu\text{V/m}$ )
Above 1000	3	74	54
***Note: The lower limit applies at the transition frequency.			

### 3.2.4. EUT Configuration on Measurement

The following equipment are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

### 3.2.5. Operating Condition of EUT

3.2.5.1. Setup the EUT as shown in Section 3.2.2.

3.2.5.2. Let the EUT work in test Mode 1 and measure it.

### 3.2.6. Test Procedure

EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated by-log antenna) is used as receiving antenna. Both horizontal and vertical polarization of the antenna is set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4-2014 on radiated emission measurement.

### 3.2.7. Measuring Instruments and Setting

Please refer to equipment list in this report. The following table is the setting of spectrum analyzer and receiver

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB/VB 200Hz/1KHz for QP/AVG
Start ~ Stop Frequency	150kHz~30MHz / RB/VB 9kHz/30KHz for QP/AVG
Start ~ Stop Frequency	30MHz~1000MHz / RB/VB 120kHz/1MHz for QP

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average


The frequency range from 30MHz to 1000MHz and above 1000MHz is checked.

### 3.2.8. Radiated Emission Noise Measurement Result

**PASS.**


The scanning waveforms please refer to the next page.

<b>Test Model</b>	Neo 1a	<b>Test Mode</b>	Mode 1
<b>Environmental Conditions</b>	23.5℃, 52.1% RH	<b>Detector Function</b>	Quasi-peak
<b>Pol</b>	Horizontal	<b>Distance</b>	3m
<b>Test Engineer</b>	Zhang Hai	<b>Test Voltage</b>	AC 120V/60Hz



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		47.8260	5.03	20.70	25.73	40.00	-14.27	QP	
2		106.0126	4.49	19.24	23.73	43.50	-19.77	QP	
3		199.2855	6.07	19.40	25.47	43.50	-18.03	QP	
4		313.2760	6.16	22.26	28.42	46.00	-17.58	QP	
5		485.6092	7.15	26.05	33.20	46.00	-12.80	QP	
6	*	790.6187	6.84	31.38	38.22	46.00	-7.78	QP	

<b>Test Model</b>	Neo 1a	<b>Test Mode</b>	Mode 1
<b>Environmental Conditions</b>	23.5°C, 52.1% RH	<b>Detector Function</b>	Quasi-peak
<b>Pol</b>	Vertical	<b>Distance</b>	3m
<b>Test Engineer</b>	Zhang Hai	<b>Test Voltage</b>	AC 120V/60Hz




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		41.7129	6.58	20.33	26.91	40.00	-13.09	QP	
2		98.4866	6.12	18.83	24.95	43.50	-18.55	QP	
3		213.0151	6.44	19.14	25.58	43.50	-17.92	QP	
4		365.5390	5.88	23.68	29.56	46.00	-16.44	QP	
5		584.7894	6.73	28.37	35.10	46.00	-10.90	QP	
6	*	922.5157	7.26	32.70	39.96	46.00	-6.04	QP	

Note: Margin= Reading Level+Correct Factor – Limit


Correct Factor=Antenna Factor+Cable Factor – Pre-Amplifier Factor

<b>Test Model</b>	Neo 1a	<b>Test Mode</b>	Mode 1 (Above 1GHz)
<b>Environmental Conditions</b>	23.5℃, 52.1% RH	<b>Detector Function</b>	Peak + AV
<b>Pol</b>	Horizontal	<b>Distance</b>	3m
<b>Test Engineer</b>	Zhang Hai	<b>Test Voltage</b>	AC 120V/60Hz



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		1202.678	49.53	-14.73	34.80	74.00	-39.20	peak	
2		1642.661	47.87	-12.39	35.48	74.00	-38.52	peak	
3		2561.707	46.54	-7.29	39.25	74.00	-34.75	peak	
4		3436.736	46.12	-1.62	44.50	74.00	-29.50	peak	
5		4512.583	41.81	4.11	45.92	74.00	-28.08	peak	
6	*	5747.456	43.20	9.41	52.61	74.00	-21.39	peak	

<b>Test Model</b>	Neo 1a	<b>Test Mode</b>	Mode 1 (Above 1GHz)
<b>Environmental Conditions</b>	23.5℃, 52.1% RH	<b>Detector Function</b>	Peak + AV
<b>Pol</b>	Vertical	<b>Distance</b>	3m
<b>Test Engineer</b>	Zhang Hai	<b>Test Voltage</b>	AC 120V/60Hz



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		1097.650	48.40	-14.82	33.58	74.00	-40.42	peak	
2		1730.272	48.43	-11.82	36.61	74.00	-37.39	peak	
3		2617.383	46.18	-6.59	39.59	74.00	-34.41	peak	
4		3639.545	43.42	-0.39	43.03	74.00	-30.97	peak	
5		4668.851	41.85	4.92	46.77	74.00	-27.23	peak	
6	*	5615.128	40.80	9.52	50.32	74.00	-23.68	peak	

**Note:**

1. Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
2. Measurements above show only up to 6 maximum emissions noted.
3. Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Factor = Antenna Factor + Cable Loss + Amplifier Factor  
Emission Level = Reading level + Factor  
Margin = Emission Level - Limit



#### 4. PHOTOGRAPH



Photo of Power Line Conducted Measurement



Photo of Radiated Measurement(Below 1GHz)



Photo of Radiated Measurement (Above 1GHz)

## 5. EXTERNAL AND INTERNAL PHOTOS OF THE EUT



Fig. 1



Fig. 2





Fig. 3



Fig. 4



Fig. 5



Fig. 6





Fig. 7



Fig. 8



Fig. 9



Fig. 10





Fig. 11



Fig. 12





Fig. 13




Fig. 14





Fig. 15



Fig. 16






Fig. 17



Fig. 18





Fig. 19



Fig. 20






Fig. 21




Fig. 22






Fig. 23




Fig. 24






Fig. 25




Fig. 26






Fig. 27




Fig. 28






Fig. 29




Fig. 30






Fig. 31




Fig. 32



Fig. 33



Fig. 34






Fig. 35



Fig. 36






Fig. 37




Fig. 38






Fig. 39




Fig. 40






Fig. 41




Fig. 42

-----THE END OF TEST REPORT-----