

Appendix B

RF Test Data for BT LE (Conducted Measurement)

Product Name: Wireless Earphone

Test Model: Vibe R3

Environmental Conditions


Temperature:	23.5°C
Relative Humidity:	52.1%
ATM Pressure:	100.0 kPa
Test Engineer:	Zhang hai
Supervised by:	Fengliu Tang


B.1 6dB Bandwidth


Test Result

TestMode	Antenna	Freq(MHz)	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.512	2401.656	2402.168	0.5	PASS
		2440	0.504	2439.660	2440.164	0.5	PASS
		2480	0.508	2479.660	2480.168	0.5	PASS
BLE_2M	Ant1	2402	0.836	2401.412	2402.248	0.5	PASS
		2440	0.840	2439.412	2440.252	0.5	PASS
		2480	0.848	2479.412	2480.260	0.5	PASS

Test Graphs









B.2 Maximum Peak conducted output power


Test Result Peak

TestMode	Antenna	Freq(MHz)	Conducted Peak Power[dBm]	Conducted Limit[dBm]	Verdict
BLE_1M	Ant1	2402	-0.92	≤30	PASS
		2440	-1.91	≤30	PASS
		2480	-2.96	≤30	PASS
BLE_2M	Ant1	2402	-0.95	≤30	PASS
		2440	-1.74	≤30	PASS
		2480	-2.77	≤30	PASS

Test Graphs Peak









B.3 Maximum power spectral density


Test Result

TestMode	Antenna	Freq(MHz)	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-19.58	≤8.00	PASS
		2440	-20.30	≤8.00	PASS
		2480	-21.20	≤8.00	PASS
BLE_2M	Ant1	2402	-21.46	≤8.00	PASS
		2440	-22.38	≤8.00	PASS
		2480	-23.47	≤8.00	PASS

Test Graphs









B.4 Band edge measurements

Test Result

TestMode	Antenna	ChName	Freq(MHz)	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	Low	2402	-1.12	-41.23	≤ -21.12	PASS
		High	2480	-4.05	-44.14	≤ -24.05	PASS
BLE_2M	Ant1	Low	2402	-1.84	-34.17	≤ -21.84	PASS
		High	2480	-4.53	-44.89	≤ -24.53	PASS

Test Graphs







B.5 Conducted Spurious Emission


Test Result


TestMode	Antenna	Freq(MHz)	FreqRange [MHz]	RefLevel [dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	Reference	-1.44	-1.44	---	PASS
			30~1000	-1.44	-48.64	≤-21.44	PASS
			1000~26500	-1.44	-30.33	≤-21.44	PASS
		2440	Reference	-2.64	-2.64	---	PASS
			30~1000	-2.64	-49.3	≤-22.64	PASS
			1000~26500	-2.64	-38.39	≤-22.64	PASS
		2480	Reference	-3.67	-3.67	---	PASS
			30~1000	-3.67	-49.08	≤-23.67	PASS
			1000~26500	-3.67	-30.17	≤-23.67	PASS
BLE_2M	Ant1	2402	Reference	-1.70	-1.70	---	PASS
			30~1000	-1.70	-48.53	≤-21.7	PASS
			1000~26500	-1.70	-30.36	≤-21.7	PASS
		2440	Reference	-2.74	-2.74	---	PASS
			30~1000	-2.74	-48.93	≤-22.74	PASS
			1000~26500	-2.74	-32.57	≤-22.74	PASS
		2480	Reference	-3.79	-3.79	---	PASS
			30~1000	-3.79	-48.61	≤-23.79	PASS
			1000~26500	-3.79	-28.32	≤-23.79	PASS


Test Graphs

























B.6 Duty Cycle


Test Result

TestMode	Antenna	Freq(MHz)	ON Time [ms]	Period [ms]	X	DC [%]	xFactor	Limit	Verdict
BLE_1M	Ant1	2402	0.05	0.62	0.0806	8.06	10.94	---	---
		2440	0.07	0.63	0.1111	11.11	9.54	---	---
		2480	0.06	0.63	0.0952	9.52	10.21	---	---
BLE_2M	Ant1	2402	0.06	0.63	0.0952	9.52	10.21	---	---
		2440	0.07	0.63	0.1111	11.11	9.54	---	---
		2480	0.07	0.63	0.1111	11.11	9.54	---	---

Test Graphs







B.7 Emissions in Restricted Bands


Test Result


TestMode	Antenna	ChName	Freq(MHz)	Detector	Freq [MHz]	Result [dBm]	Limit [dBm]	Gain [dBi]	DC Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Verdict
BLE_1M	Ant1	Low	2402	AV	2310.000	-56.96	≤-54.14	2.00	10.94	51.18	≤54	PASS
				AV	2363.315	-56.46	≤-54.14	2.00	10.94	51.68	≤54	PASS
				AV	2390.000	-56.86	≤-54.14	2.00	10.94	51.28	≤54	PASS
				Peak	2310.000	-48	≤-23.20	2.00	0.00	49.20	≤74	PASS
				Peak	2367.935	-45.37	≤-23.20	2.00	0.00	51.83	≤74	PASS
				Peak	2390.000	-47.86	≤-23.20	2.00	0.00	49.34	≤74	PASS
		High	2480	AV	2483.500	-56.09	≤-53.41	2.00	10.21	51.32	≤54	PASS
				AV	2485.120	-55.97	≤-53.41	2.00	10.21	51.44	≤54	PASS
				AV	2500.000	-56.67	≤-53.41	2.00	10.21	50.74	≤54	PASS
				Peak	2483.500	-46.57	≤-23.20	2.00	0.00	50.63	≤74	PASS
				Peak	2485.360	-39.36	≤-23.20	2.00	0.00	57.84	≤74	PASS
				Peak	2500.000	-47.2	≤-23.20	2.00	0.00	50.00	≤74	PASS
BLE_2M	Ant1	Low	2402	AV	2310.000	-57.01	≤-53.41	2.00	10.21	50.40	≤54	PASS
				AV	2361.635	-56.39	≤-53.41	2.00	10.21	51.02	≤54	PASS
				AV	2390.000	-56.73	≤-53.41	2.00	10.21	50.68	≤54	PASS
				Peak	2310.000	-47.39	≤-23.20	2.00	0.00	49.81	≤74	PASS
				Peak	2330.345	-45.01	≤-23.20	2.00	0.00	52.19	≤74	PASS
				Peak	2390.000	-48.26	≤-23.20	2.00	0.00	48.94	≤74	PASS
		High	2480	AV	2483.500	-56.33	≤-52.74	2.00	9.54	50.41	≤54	PASS
				AV	2485.840	-55.74	≤-52.74	2.00	9.54	51.00	≤54	PASS
				AV	2500.000	-56.53	≤-52.74	2.00	9.54	50.21	≤54	PASS
				Peak	2483.500	-48.03	≤-23.20	2.00	0.00	49.17	≤74	PASS
				Peak	2485.440	-39.49	≤-23.20	2.00	0.00	57.71	≤74	PASS
				Peak	2500.000	-46.86	≤-23.20	2.00	0.00	50.34	≤74	PASS

Note:


1. The Antenna Gain is compensated in the graph.
2. The limit in dBm for average detector is conversion from 54dBuV/m, according to 15.209(a). The limit in dBm for peak detector is 20dB above the limit of average detector in dBm.

Test Graphs





BLE_1M_Ant1_High_2480_Peak



BLE_2M_Ant1_Low_2402_AV

